

MARINE/RV

INTIMIDATOR[®]

AGM

FEATURES AND BENEFITS

- Premium maintenance-free starting, cycling, and deep cycle service
- Micro-porous glass mat separators prevents acid spills and terminal corrosion
- Lower internal resistance ensures higher discharge rates and faster starts
- 2x the cycle life* extends performance and life
- 20x more vibration protection* resists wave-pounding
- Spillproof design enables flexible installation (upside-down not recommended) and safe handling around electronics
- High freeze-resistance provides better all weather service

* Compared to conventional designs



From starting performance to a boatload of trolling and accessory power, Intimidator batteries won't have any trouble in meeting marine or RV needs. A premium spillproof design brings essential convenience and safety to the boating and RV enthusiast.

Intimidator Starting and Cycling Service batteries means high starting and moderate deep cycle power. Ideal for boaters that want high cranking power and still enjoy dependable power for more electronic accessories.

Intimidator Heavy-Duty Deep Cycle batteries have more fish-finding trolling and accessory power. Ideal for heavy deep cycle demands, with moderate starting power. Provides advanced protection against the typical deep discharge of extended trolling use.



Intimidator® AGM Solutions for Intimidating Battery Needs

Intimidator is a pioneer brand in the development of the form, fit, and function of AGM battery technology. It has been tested and proven to best meet the criteria for the various types of dependable marine power needs.



ADVANCED DURABILITY DESIGNS

- Fortified posts, straps, and welds resist vibration damage
- Maximize current transfer over life of battery



POWER-PERFORM FULL-FRAME POSITIVE & NEGATIVE PLATES

- Better withstands rigorous marine demands
- Prevents life-robbing electrical shorts from exposed wire



ENHANCED ELECTROLYTE SUSPENSION SYSTEM

- Absorbs more electrolyte, protects internal components
- Micro-porous glass separators prevents acid spills and terminal corrosion

MARINE/RV INTIMIDATOR® AGM BATTERIES

GROUP NO.	PART NO.	PERFORMANCE LEVEL				APPROX. WEIGHT (lbs.)	MAXIMUM OVERALL DIMENSIONS						FOOTNOTES
		CCA @ 0°F	RES. CAP.	REF. MCA	20 AH RATE		Length		Width		Height		
							inch	mm	inch	mm	inch	mm	
DUAL PURPOSE ABSORBED GLASS MAT (AGM) VALVE REGULATED													
34M	9A34M	775	120	955	55	42.5	10 3/4	273	6 3/4	175	8 3/4	212	2,17,46,78,U
12 VOLT HEAVY-DUTY DEEP CYCLE ABSORBED GLASS MAT (AGM) VALVE REGULATED													
U1	8AU1	200	45	240	32	23	7 3/4	197	5 1/2	130	7 1/4	184	2,38,39,44,Y
U1	8AUIH	200	45	240	32	23	8 5/8	211	5 1/2	130	7 1/4	184	2,17,38,39,44,Y
22NF	8A22NF	350	85	420	55	37	9	228	5 1/2	140	9 1/4	235	2,38,39,44,G
24M	8A24M	525	135	800	79	52	10 7/8	276	6 3/4	171	9 3/8	238	2,17,38,39,44,U
27M	8A27M	580	175	900	92	61.5	12 3/4	324	6 3/4	171	9 3/8	238	2,17,38,39,44,U
31M	8A31DTM	800	200	1000	105	67.5	12 15/16	329	6 3/4	171	9 3/8	238	2,16,17,38,39,44,A
4D	8A4D	1110	380	1420	198	131.5	20 3/4	527	8 1/2	216	10	254	2,17,44S
8D	8A8D	1450	480	1800	245	163	20 3/4	527	11	279	10	254	2,17,44S
6 VOLT HEAVY-DUTY DEEP CYCLE ABSORBED GLASS MAT (AGM) VALVE REGULATED													
GC2	8AGC2	680	380	900	190	68	10 1/4	260	7 1/2	181	10 7/8	276	2,44,U

All batteries have SAE automotive posts unless noted

FOOTNOTES: 2. Black cover / Gray case 16. Dual terminal universal design 17. Includes handle 38. "Non-spillable" defined by DOT (Department of Transportation) definitions 39. "Non-spillable" defined by ICAO (International Commercial Airline Organization) and IATA (International Airline Transport Association) definitions 44. Free replacement warranty is 3 months in full electric vehicle use. 46. If battery is used in on-highway vehicles equipped with 2-way radios (such as taxis, police, and emergency vehicles), marine applications, off-highway use, and other non-automotive usage, Free warranty replacement period will be 18 months. Free replacement warranty is 12 months in deep-cycle use, and 3 months in full electric vehicle use. 78. Shipped with 22mm height adapter. A. Flush combination terminal w/ 3/8" stud and SAE post, hex nut included. G. Offset post w/ horizontal hole, stainless steel 5/16" bolt and hex nut (T881) U. Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs & hex nuts Y. Small L terminal with round holes. S. SAE "Automotive type" post (TSAE).

PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**

Experience the East Penn Advantage

East Penn's A³™ Advanced-Cubed precision-focused manufacturing approach ensures the process behind the technology delivers critical quality at each stage of battery production. INTIMIDATOR batteries are supported by A³ manufacturing to optimize the life, power, and durability of the battery's design and performance.



East Penn Manufacturing Co. Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781 www.eastpenn-deka.com