



Power
for the road ahead.



Help your customers find the power they need with Deka's complete line of battery options.

Our robust line of products are strategically designed to provide the right power choices for vehicles today and as they evolve into the future. From solutions for the 12-volt systems in EVs to engines that come to life from the dependability of the Deka standard design, you'll have your customers covered and ready to boldly power down the road ahead.



Power
for the road ahead.

Complete Battery Line Specifications

GROUP NO.	PART NO.	CCA	RC	REF. CA	20 HR CAP	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
							in	mm	in	mm	in	mm			
12-VOLT — AGM — INTIMIDATOR® — VALVE REGULATED															
34/78	9A78DT	750	120	860	55	43	10-3/4	273	6-7/8	175	8	203	1.0	30	2,16,17,38,39,46,P
24F	9A24F	710	110	825	65	44.5	11-1/8	282	6-5/8	168	9	229	1.0	30	2,17,38,39,46
34	9A34	750	120	860	55	42.5	10-3/4	273	6-7/8	175	8	203	1.0	30	2,17,28,38,39,46
34R	9A34R	750	120	860	55	42.5	10-3/4	273	6-7/8	175	8	203	1.0	30	2,17,28,38,39,46
35/85	9A35/85	640	100	755	50	40	9-9/16	242	6-3/4	171	7-3/4	197	1.0	30	2,17,18,37,38,39,46
47 (H5/L2)	9A47	600	100	690	60	39	9-9/16	242	6-7/8	175	7-1/2	190	1.0	30	17,22,38,39,46
48 (H6/L3)	9A48	760	120	875	70	47.5	11	278	6-7/8	175	7-1/2	190	1.0	30	17,22,46
49 (H8/L5)	9A49	850	170	975	92	58	13-15/16	354	6-7/8	175	7-1/2	190	1.0	30	17,22,38,39,46
51R	9A51RT	500	75	580	46	31.5	9-5/16	236	5	127	8-5/8	219	1.0	30	2,38,39,46
65	9A65	750	150	860	75	47.5	12	305	7-3/8	187	7-5/8	194	1.0	30	2,17,38,39,46
78	9A78	750	120	860	55	43	10-3/4	273	6-7/8	175	7-1/4	184	1.0	30	2,17,38,39,46,E
94R (H7/L4)	9A94R	800	140	920	80	52	12-7/16	315	6-7/8	175	7-1/2	190	1.0	30	17,22,38,39,46
95R (H9/L6)	9A95R	950	190	1050	105	65	15-1/2	394	6-7/8	175	7-1/2	190	1.0	30	17,22,24,38,39,46
140R (H4/LN1)	9A140R	535	80	615	50	34	8-1/8	207	6-7/8	175	7-1/2	190	1.0	30	2,38,39,46
34M	9A34M	750	120	860	55	42.5	10-3/4	273	6-7/8	175	8-3/8	212	1.0	12	2,17,38,39,43,U
S46B24R (Prius)	9A51P	325	60	390	46	29.5	9-1/4	235	5	127	8-5/8	220	1.0	24	22,38,39,46,J
12-VOLT — AGM — INTIMIDATOR® — AUTOMOTIVE AUXILIARY															
401	AUX12	180	—	—	10	9.5	5-7/8	150	3-7/16	88	5-1/8	130	0.2	12	K
400	AUX14	200	—	—	12	11.5	5-7/8	150	3-7/16	88	5-3/4	145	0.2	12	38,39,K
AUX	AUX18L	300	—	—	20	18	8-1/8	206	3-9/16	91	6-3/8	163	0.2	12	38,39,K
AUX	AUX30LP	400	—	—	26	20.5	7-1/16	180	5-9/16	141	7-1/2	190	0.2	12	38,39
12 VOLT — EFB — ENHANCED FLOODED — ULTIMATE®															
47 (H5/L2)	47EFB	600	—	740	60	36.5	9-9/16	242	6-7/8	175	7-1/2	190	1.0	24	8,17,43,45
48 (H6/L3)	48EFB	700	—	860	70	42	11	278	6-7/8	175	7-1/2	190	1.0	24	8,17,43,45

EHP (Electric & Hybrid Performance)

GROUP NO.	PART NO.	CCA	RC	REF. CA	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES	
						in	mm	in	mm	in	mm				
12 VOLT — ULTIMATE®															
34/78	778DT	800	115	985	40.5	10-3/4	273	6-7/8	175	8	203	1.0	30	14,16,17,18,22,28,45,P	
24	724MF	725	120	890	42.5	10-3/4	273	6-3/4	171	9	229	1.0	30	17,22,45	
24F	724FMF	725	120	890	42.5	10-3/4	273	6-3/4	171	9	229	1.0	30	17,22,45	
25	725MF	625	95	770	37	9-3/4	248	6-7/8	175	8-7/8	225	1.0	30	17,22,45	
27	727MF	840	140	1035	50.5	12-5/8	321	6-3/4	171	9	229	1.0	30	17,21,45	
27F	727FMF	840	140	1035	50.5	12-5/8	321	6-3/4	171	9	229	1.0	30	17,21,45	
34	734MF	800	115	985	40	10-3/4	273	6-7/8	175	8	203	1.0	30	17,18,22,28,45	
34R	734RMF	800	115	985	40	10-3/4	273	6-7/8	175	8	203	1.0	30	17,18,22,28,45	
35	735MF	640	95	785	37	9-9/16	247	6-7/8	175	8-7/8	225	1.0	30	17,22,45	
48 (H6/L3)	748MF	730	120	900	41.5	11	278	6-7/8	175	7-1/2	190	1.0	30	17,22,45	
65	765MF	750	140	925	44	12	305	7-3/8	187	7-5/8	194	1.0	30	17,22,45	
75	775MF	690	95	850	35	9-3/4	248	7	178	7-1/4	184	1.0	30	17,22,45,E	
78	778MF	800	115	985	40	10-3/4	273	6-7/8	175	7-1/4	184	1.0	30	17,22,45,E	
79	779MF	840	140	1035	43	12-1/16	307	7-1/16	179	7-3/8	188	1.0	30	22,45,E	
86	786MF	690	95	850	35	9	229	6-7/8	175	8-1/8	206	1.0	30	22,45	



Power
for the road ahead.

Complete Battery Line Specifications

GROUP NO.	PART NO.	CCA	RC	REF. CA	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY	FOOTNOTES
						in	mm	in	mm	in	mm		FREE MO.	
12-VOLT — GOLD														
75/86	675DT	650	90	800	34.5	9-3/4	248	7	178	8-1/8	206	1.0	24	14,16,17,18,22,37,45,P
24	624MF	650	115	800	39.5	10-3/4	273	6-3/4	171	9	229	1.0	24	17,22,45
24F	624FMF	650	115	800	39.5	10-3/4	273	6-3/4	171	9	229	1.0	24	17,22,45
27	627MF	710	120	875	49	12	305	6-3/4	171	9	229	1.0	24	45
27F	627FMF	710	120	875	49	12-3/8	314	6-3/4	171	9	229	1.0	24	45
34	634MF	690	110	850	37.5	10-3/4	273	6-7/8	175	8	203	1.0	24	17,18,22,28,45
34R	634RMF	690	110	850	37.5	10-3/4	273	6-7/8	175	8	203	1.0	24	17,18,22,28,45
36R	636RMF	650	120	800	39	10-1/4	260	7-1/4	184	8	203	1.0	24	45
40R (T6/LB3)	640RMF	650	105	800	37	11	278	6-7/8	175	6-7/8	175	1.0	24	17,22,45
41 (T65)	641MF	650	100	800	38	11-9/16	293	6-7/8	175	6-7/8	175	1.0	24	22,45
42/58R	642/58R	580	85	715	32.5	10	254	7-1/4	184	6-7/8	175	1.0	24	17,22,45
42 (T5/LB2)	642MF	475	70	585	29	9-9/16	242	6-7/8	175	6-7/8	175	1.0	24	45
47 (H5/L2)	647MF	650	100	800	35.5	9-9/16	242	6-7/8	175	7-1/2	190	1.0	24	17,22,45
48 (H6/L3)	648MF	680	120	835	40	11	278	6-7/8	175	7-1/2	190	1.0	24	17,22,45
148 (H6R)	648RMF	680	120	835	40	11	278	6-7/8	175	7-1/2	190	1.0	24	17,22,45
49 (H8/L5)	649MF	900	185	1105	52.5	13-15/16	354	6-7/8	175	7-1/2	190	1.0	24	17,22,45
50	650MF	600	108	740	43	13-3/8	340	5-3/8	136	8-7/8	225	1.0	24	17,45
51	651MF	500	75	615	28.5	9-3/8	238	5	127	8-3/4	222	1.0	24	22,45
51R	651RMF	500	75	615	28.5	9-3/8	238	5	127	8-3/4	222	1.0	24	22,45
55	655MF	540	75	665	32.5	8-3/4	222	6	152	8-1/2	216	1.0	24	17,18,45
58	658MF	580	85	715	32	10	254	7-1/4	184	6-7/8	178	1.0	24	17,22,45
58R	658RMF	580	85	715	32	10	254	7-1/4	184	6-7/8	175	1.0	24	17,22,45
59	659MF	590	100	725	38.5	9-1/2	241	7-7/16	189	7-1/2	190	1.0	24	17,45
65	665MF	850	150	1045	46.5	12	305	7-3/8	187	7-5/8	194	1.0	24	17,22,45
67R	667RMF	390	65	480	25	8-1/4	210	6-7/8	175	6-7/8	175	1.0	24	17,22
75	675MF	650	90	800	34	9-3/4	248	7	178	7-1/4	184	1.0	24	17,22,45,E
78	678MF	690	110	850	37.5	10-3/4	273	6-7/8	175	7-1/4	184	1.0	24	17,22,45,E
85	685MF	650	110	800	34	9	229	6-7/8	175	8-1/8	206	1.0	24	22,45
90 (T5/LB2)	690MF	600	90	740	33.5	9-9/16	242	6-7/8	175	6-7/8	175	1.0	24	17,22,45
91 (T6/LB3)	691MF	700	100	860	37	11	278	6-7/8	175	6-7/8	175	1.0	24	17,22,45
92 (T7/LB4)	692MF	650	130	800	43	12-1/2	317	6-7/8	175	6-7/8	175	1.0	24	17,22,45
93 (T8/LB5)	693MF	800	130	985	46	13-15/16	354	6-7/8	175	6-7/8	175	1.0	24	17,22,45
94R (H7/L4)	694RMF	790	140	970	45.5	12-7/16	315	6-7/8	175	7-1/2	190	1.0	24	17,22,45
95R (H9/L6)	695RMF	850	190	1045	61.5	15-1/2	394	6-7/8	175	7-1/2	190	1.0	24	17,22,45
96R	696RMF	600	90	740	32.5	9-9/16	242	6-7/8	175	6-7/8	175	1.0	24	17,22,45
97R (H5/L2)	697RMF	600	95	740	37	9-9/16	242	6-7/8	175	7-1/2	190	1.0	24	17,22,45
101	6101MF	650	110	800	36	10-1/4	260	7-1/16	179	6-11/16	170	1.0	24	22,45,E
121R	6121RMF	550	80	675	30.5	8-1/4	210	6-15/16	177	8-1/8	206	1.0	24	22,45
124	6124MF	700	100	860	37.5	10-1/4	260	6-7/8	175	8-3/8	212	1.0	24	22,45
124R	6124RMF	700	100	860	37.5	10-1/4	260	6-7/8	175	8-3/8	212	1.0	24	22,45



Power
for the road ahead.

Complete Battery Line Specifications

GROUP NO.	PART NO.	CCA	RC	REF. CA	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
						in	mm	in	mm	in	mm			
12 VOLT														
24	524MF	550	90	675	37	10-3/4	273	6-3/4	171	9	229	1.0	18	17,22,45
24	424MF	460	70	565	34	10-3/4	273	6-3/4	171	9	229	1.0	18	17,22,45
24F	524FMF	550	90	675	37	10-3/4	273	6-3/4	171	9	229	1.0	18	17,22,45
24F	424FMF	460	70	565	34	10-3/4	273	6-3/4	171	9	229	1.0	18	17,22,45
25	525MF	550	90	675	34	9-3/4	248	6-7/8	175	8-7/8	225	1.0	18	17,22,45
26	526MF	540	80	665	29	8-3/4	222	6-3/4	171	8	203	1.0	18	17,18,22,37,45
26	426MF	450	55	555	27	8-3/4	222	6-3/4	171	8	203	1.0	18	17,18,22,37,45
26R	526RMF	540	80	665	29	8-3/4	222	6-3/4	171	8	203	1.0	18	17,18,22,37,45
26R	426RMF	450	55	555	27	8-3/4	222	6-3/4	171	8	203	1.0	18	17,18,22,37,45
34	534MF	600	90	740	34	10-3/4	273	6-7/8	175	8	203	1.0	18	17,18,22,28,45
35	535MF	550	90	675	34	9-9/16	247	6-7/8	175	8-7/8	225	1.0	18	17,22,45
42/58R	542/58R	500	75	615	29.5	10	254	7-1/4	184	6-7/8	175	1.0	18	17,22,45
45	545MF	485	65	595	31	9-3/8	238	5-1/2	140	9	229	1.0	18	45
48 (H6/L3)	548MF	615	95	755	37	11	278	6-7/8	175	7-1/2	190	1.0	18	17,22,45
51	551MF	450	70	555	28	9-3/8	238	5	127	8-3/4	222	1.0	18	22,45
51R	551RMF	450	70	555	28	9-3/8	238	5	127	8-3/4	222	1.0	18	22,45
58	558MF	500	75	615	29.5	10	254	7-1/4	184	6-7/8	178	1.0	18	17,22,45
65	565MF	675	130	830	41.5	12	305	7-3/8	187	7-5/8	194	1.0	18	17,22,45
70	570MF	540	80	665	29	8-3/4	222	7	178	7-1/8	181	1.0	18	17,18,22,37,45,E
75	575MF	540	85	665	31.5	9-3/4	248	7	178	7-1/4	184	1.0	18	17,22,45,E
78	578MF	600	90	740	34	10-3/4	273	6-7/8	175	7-1/4	184	1.0	18	17,22,45,E
86	586MF	540	85	665	31.5	9	229	6-7/8	175	8-1/8	206	1.0	18	22,45
99R (T4)	599RMF	450	68	555	26.5	8-1/4	210	6-7/8	175	6-7/8	175	1.0	18	17,45
140R (H4/LN1)	5140RMF	445	76	545	28	8-1/4	210	6-7/8	175	7-1/2	190	1.0	18	17,22,45
151R	5151RMF	340	55	410	22.5	7-3/4	197	5-1/8	129	8-7/8	226	1.0	18	17,22,45
46A24L (Miata)	8AMU1R	320	45	400	24	7-3/4	197	5-1/8	130	7-1/8	181	0.5	18	2,13,38,39,45

- Batteries are maintenance-free calcium grids, except where noted
- Batteries manufactured in black polypropylene cases & covers, except where noted
- SAE & DIN automotive posts used, unless noted
- Warranty is suggested months
- Weights are approximates
- CA and MCA ratings @ 32°F are approximations for comparison only
- Ratings other than CCA and RC, are "nominal"
- CCA and RC ratings conform to B.C.I. specifications
- CCA on 8 Volt Marine & Industrial types is for reference only

FOOTNOTES

- Black cover / Gray case
- Gray cover / Gray case
- Black cover / Brown case
- Black cover / White case
- Low maintenance-low antimony grids
- Hybrid construction
- Absorbed Glass Mat technology (AGM)
- Centerline terminal posts
- Hard rubber, one-piece cover construction
- Dual terminal, universal design
- Includes handle
- Includes top adapter
- Includes lifting ledges
- Hard rubber, multi-cell cover construction
- Anchor locked elements
- Flush manifold vented cover
- CCA is an EN rating
- With individual vent caps
- For height with adaptor add 5/8" (16mm)
- Fahrenheit Thermal Shielding Technology
- Ratings after 15 cycles
- Deduct 15% from CCA and CA to allow for double insulation (glass mat)
- Peak performance capacity
- For height with adapter add 7/8" (22mm)
- "Non-spillable" as defined by DOT (Department of Transportation) definitions
- "Non-spillable" as defined by ICAO (International Civil Aviation Organization) and IATA (International Air Transport Association) definitions
- Height without adapter
- Free replacement warranty is 12 months in deep-cycle use and 3 months in full electric vehicle use
- Free replacement warranty is 3 months in full electric vehicle use
- If battery is used in on-highway vehicles equipped with two-way radios (such as taxis, police, and emergency vehicles), marine applications, off-highway use, and other non-automotive usage, free warranty replacement period will be 6 months and 3 months in full electric vehicle use
- If battery is used in on-highway vehicles equipped with two-way radios (such as taxis, police, and emergency vehicles), marine applications, off-highway use, and other non-automotive usage, free warranty replacement period will be 18 months, free replacement warranty is 12 months in deep-cycle use and 3 months in full electric vehicle use
- Shipped with 20mm height adapter
- Shipped with two 17mm height adapters
- Shipped with 10mm height adapter
- Shipped with 22mm height adapter

PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**

