



Time in the great outdoors is precious. Campers shouldn't have to compromise when it comes to their home away from home. These batteries may say Marine Master on the label, but they're built **Road Ready**—perfect for land and sea.

All batteries in the Marine Master line are equipped with starting power and varying levels of deep cycle service to best accommodate house power and accessory roads.

An upgrade to premium AGM or Gel technology provides the ultimate maintenance-free experience with a spillproof and vibration-proof design that maximizes reliability season-after-season.

Adventure | **The Power**
Awaits. | **is Yours.**®




Complete Battery Line Specifications



| GROUP NO. | PART NO. | CCA | REF. MCA | 20 HR CAP | MINS @ 25 A | WEIGHT (lb) | LENGTH | | WIDTH | | HEIGHT | | Core Value | WARRANTY FREE MO. | FOOTNOTES |
|--|----------|----------|----------|-----------|-------------|-------------|----------|-----|-------|-----|--------|-----|------------|-------------------|-----------------------|
| | | | | | | | in | mm | in | mm | in | mm | | | |
| 12-VOLT STARTING | | | | | | | | | | | | | | | |
| 24 | 24M7 | 800 | 1000 | — | 130 | 44 | 10-3/4 | 273 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 17,22,U |
| | 24M5 | 550 | 675 | — | 90 | 37 | 10-3/4 | 273 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 17,22,U |
| 27 | 27M6 | 840 | 1050 | — | 182 | 53 | 12-1/2 | 318 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 17,U |
| 12-VOLT DEEP CYCLE SERVICE | | | | | | | | | | | | | | | |
| 24 | DP24 | 575 | 705 | 65 | 130 | 44 | 10-3/4 | 273 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 12,17,44,U |
| 27 | DP27 | 675 | 830 | 80 | 175 | 51 | 12-1/2 | 318 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 12,17,44,U |
| 31 | DP31DT | 725 | 890 | 100 | 190 | 58.5 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 12 | 17,21,22,44,A |
| 12-VOLT HEAVY-DUTY DEEP CYCLE SERVICE | | | | | | | | | | | | | | | |
| 24 | DC24 | 525 | 645 | 75 | 135 | 45.5 | 10-3/4 | 273 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 12,17,35,44,U |
| 27 | DC27 | 625 | 765 | 90 | 180 | 53.5 | 12-1/2 | 318 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 12,17,35,44,U |
| 31 | DC31DT | 675 | 830 | 105 | 195 | 60 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 12 | 12,17,21,22,35,44,A |
| <i>"DC" (deep cycle flooded) part numbers include double insulated glass mat separators.</i> | | | | | | | | | | | | | | | |
| 12-VOLT AGM DEEP CYCLE SERVICE | | | | | | | | | | | | | | | |
| 34/24 | 9A34M | 750 | 860 | 55 | 120 | 42.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8-3/8 | 212 | 1.0 | 12 | 2,13,17,18,38,39,44,U |
| 12-VOLT AGM HEAVY-DUTY DEEP CYCLE SERVICE | | | | | | | | | | | | | | | |
| 24M | 8A24M | 525 | 800 | 79 | 145 | 52 | 10-7/8 | 276 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 2,17,38,39,44,U |
| 27M | 8A27M | 580 | 900 | 92 | 185 | 61.5 | 12-3/4 | 324 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 2,17,38,39,44,U |
| 31M | 8A31DTM | 800 | 1000 | 105 | 210 | 67.5 | 12-15/16 | 329 | 6-3/4 | 171 | 9-3/8 | 238 | 1.5 | 12 | 2,16,17,38,39,44,A |
| 12-VOLT GEL EXTREME DEEP CYCLE SERVICE | | | | | | | | | | | | | | | |
| 24M | 8G24M | 410 | 575 | 73.6 | 140 | 51.5 | 10-7/8 | 276 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 4,17,34,38,39,U |
| 27M | 8G27M | 505 | 700 | 88 | 170 | 62 | 12-3/4 | 324 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12 | 4,17,34,38,39,U |
| 31M | 8G31DTM | 550 | 780 | 97.6 | 190 | 68.5 | 12-15/16 | 329 | 6-3/4 | 171 | 9-3/8 | 238 | 1.5 | 12 | 4,16,17,34,38,39,A |
| GROUP NO. | PART NO. | REF. CCA | REF. MCA | 8 HR CAP | 6 HR CAP | WEIGHT (lb) | LENGTH | | WIDTH | | HEIGHT | | Core Value | WARRANTY FREE MO. | FOOTNOTES |
| | | | | | | | in | mm | in | mm | in | mm | | | |
| 8-VOLT MARINE HEAVY-DUTY DEEP CYCLE COMMERCIAL SERVICE | | | | | | | | | | | | | | | |
| 983 | 819 | 510 | 625 | 167 | 158 | 119 | 24-1/2 | 622 | 7-1/2 | 191 | 10-1/2 | 267 | 3.0 | 6 | 11,17,20,25,T |
| 984 | 821 | 530 | 650 | 187 | 177 | 135 | 27-1/2 | 699 | 7-1/2 | 191 | 10-1/2 | 267 | 3.0 | 6 | 11,17,20,25,T |
| 985 | 825 | 730 | 900 | 224 | 212 | 160 | 26-7/8 | 683 | 8-1/2 | 216 | 11-3/4 | 298 | 4.0 | 6 | 11,17,20,25,F |

- Batteries are maintenance-free calcium grids, except where noted
- Batteries manufactured in black polypropylene cases & covers, except where noted
- Warranty is suggested months
- Weights are approximates
- MCA and CA ratings @ 32°F are approximations for comparison only
- Ratings other than CCA and RC, are "nominal"
- CCA and RC ratings conform to B.C.I. specifications
- CCA on 8 Volt Marine batteries is for reference only

PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**



TERMINAL PICTURE FOOTNOTES

- A. Flush Combination terminal w/ 5/16" Stud and SAE post, Hex nuts included
- F. Double Wide L Terminal w/ two 3/8" holes (T230)
- T. Heavy Duty L terminal w/ 3/8" diameter hole (T975)
- U. Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs and wing nuts

FOOTNOTES

- 2. Black cover / Gray case
- 4. Gray cover / Gray case
- 11. Low maintenance-low antimony grids
- 12. Hybrid construction
- 13. AGM Technology
- 16. Dual terminal universal design
- 17. Includes handle

- 18. Includes Height Adaptor
- 20. Hard rubber, multi-cell cover construction
- 21. Anchor locked elements
- 22. Flush manifold vented cover
- 25. With individual vent caps
- 34. Ratings after 15 cycles
- 35. Deduct 15% from CCA and CA rating to allow for double insulation (glass mat)
- 38. "Non-spillable" defined by DOT (Department of Transportation) definitions
- 39. "Non-spillable" defined by ICAO (International Civil Aviation Organization) and IATA (International Air Transport Association) definitions
- 44. Free replacement warranty is 3 months in full electric vehicle use

