



SPACESAVER™ SYSTEMS AVR45 DISCHARGE RATES IN AMPS

Ratings in Amperes at 77°F (25°C) to 1.75 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	52.3	38.8	31.4	23.8	19.3	16.5	14.3	12.7	11.4	10.4	9.60	8.31	6.49	5.36	4.58	2.43	1.66	1.21
AVR45-7	78.4	58.2	47.1	35.7	28.9	24.7	21.5	19.0	17.1	15.6	14.4	12.5	9.74	8.04	6.88	3.64	2.50	1.81
AVR45-9	105	77.6	62.9	47.6	38.6	32.9	28.7	25.4	22.9	20.8	19.2	16.6	13.0	10.7	9.17	4.86	3.33	2.42
AVR45-11	131	97.1	78.6	59.5	48.2	41.1	35.8	31.7	28.6	26.1	24.0	20.8	16.2	13.4	11.5	6.07	4.16	3.02
AVR45-13	157	116	94.3	71.4	57.9	49.4	43.0	38.1	34.3	31.3	28.8	24.9	19.5	16.1	13.8	7.28	4.99	3.63
AVR45-15	183	136	110	83.3	67.5	57.6	50.2	44.4	40.0	36.5	33.6	29.1	22.7	18.8	16.0	8.50	5.83	4.23
AVR45-17	209	155	126	95.2	77.1	65.8	57.3	50.8	45.7	41.7	38.4	33.2	26.0	21.4	18.3	9.71	6.66	4.84
AVR45-19	235	175	141	107	86.8	74.1	64.5	57.1	51.4	46.9	43.2	37.4	29.2	24.1	20.6	10.9	7.49	5.44
AVR45-21	261	194	157	119	96.4	82.3	71.7	63.5	57.1	52.1	48.0	41.6	32.5	26.8	22.9	12.1	8.32	6.05
AVR45-23	288	214	173	131	106	90.5	78.8	69.8	62.9	57.3	52.8	45.7	35.7	29.5	25.2	13.4	9.16	6.65
AVR45-25	314	233	189	143	116	98.7	86.0	76.2	68.6	62.5	57.6	49.9	38.9	32.2	27.5	14.6	10.0	7.26
AVR45-27	340	252	204	155	125	107	93.2	82.5	74.3	67.8	62.4	54.0	42.2	34.8	29.8	15.8	10.8	7.86
AVR45-29	366	272	220	167	135	115	100	88.9	80.0	73.0	67.2	58.2	45.4	37.5	32.1	17.0	11.7	8.47
AVR45-31	392	291	236	179	145	123	108	95.2	85.7	78.2	72.0	62.3	48.7	40.2	34.4	18.2	12.5	9.07
AVR45-33	418	311	251	190	154	132	115	102	91.4	83.4	76.8	66.5	51.9	42.9	36.7	19.4	13.3	9.68

Ratings in Amperes at 77°F (25°C) to 1.78 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	49.7	37.4	30.6	23.1	19.0	16.2	14.0	12.5	11.3	10.3	9.49	8.17	6.39	5.28	4.52	2.42	1.65	1.21
AVR45-7	74.6	56.1	45.9	34.7	28.5	24.3	21.1	18.8	17.0	15.5	14.2	12.3	9.59	7.93	6.79	3.63	2.48	1.81
AVR45-9	99.4	74.8	61.1	46.3	38.0	32.3	28.1	25.0	22.6	20.6	19.0	16.3	12.8	10.6	9.05	4.84	3.31	2.41
AVR45-11	124	93.5	76.4	57.9	47.5	40.4	35.1	31.3	28.3	25.8	23.7	20.4	16.0	13.2	11.3	6.05	4.13	3.01
AVR45-13	149	112	91.7	69.4	57.0	48.5	42.1	37.5	34.0	30.9	28.5	24.5	19.2	15.9	13.6	7.26	4.96	3.62
AVR45-15	174	131	107	81.0	66.5	56.6	49.2	43.8	39.6	36.1	33.2	28.6	22.4	18.5	15.8	8.47	5.79	4.22
AVR45-17	199	150	122	92.6	76.0	64.7	56.2	50.1	45.3	41.2	37.9	32.7	25.6	21.1	18.1	9.68	6.62	4.82
AVR45-19	224	168	138	104	85.5	72.8	63.2	56.3	50.9	46.4	42.7	36.8	28.8	23.8	20.4	10.9	7.44	5.42
AVR45-21	249	187	153	116	95.0	80.9	70.2	62.6	56.6	51.6	47.4	40.8	32.0	26.4	22.6	12.1	8.27	6.03
AVR45-23	273	206	168	127	105	88.9	77.3	68.8	62.3	56.7	52.2	44.9	35.1	29.1	24.9	13.3	9.10	6.63
AVR45-25	298	224	183	139	114	97.0	84.3	75.1	67.9	61.9	56.9	49.0	38.3	31.7	27.1	14.5	9.92	7.23
AVR45-27	323	243	199	150	124	105	91.3	81.3	73.6	67.0	61.7	53.1	41.5	34.3	29.4	15.7	10.8	7.84
AVR45-29	348	262	214	162	133	113	98.3	87.6	79.2	72.2	66.4	57.2	44.7	37.0	31.7	16.9	11.6	8.44
AVR45-31	373	281	229	174	143	121	105	93.8	84.9	77.3	71.1	61.3	47.9	39.6	33.9	18.2	12.4	9.04
AVR45-33	398	299	245	185	152	129	112	100	90.6	82.5	75.9	65.3	51.1	42.3	36.2	19.4	13.2	9.64



SPACE SAVER™ SYSTEMS AVR45 DISCHARGE RATES IN AMPS (cont.)

Ratings in Amperes at 77°F (25°C) to 1.80 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	48.2	36.6	30.2	22.9	18.8	16.1	13.9	12.4	11.2	10.2	9.39	8.10	6.35	5.25	4.50	2.41	1.65	1.20
AVR45-7	72.3	55.0	45.3	34.3	28.1	24.1	20.9	18.6	16.8	15.3	14.1	12.2	9.52	7.88	6.75	3.62	2.47	1.80
AVR45-9	96.3	73.3	60.4	45.8	37.5	32.1	27.8	24.8	22.4	20.4	18.8	16.2	12.7	10.5	9.00	4.82	3.29	2.40
AVR45-11	120	91.6	75.5	57.2	46.9	40.1	34.8	31.0	28.1	25.5	23.5	20.3	15.9	13.1	11.2	6.03	4.11	3.00
AVR45-13	145	110	90.6	68.7	56.3	48.2	41.8	37.2	33.7	30.6	28.2	24.3	19.0	15.8	13.5	7.23	4.94	3.60
AVR45-15	169	128	106	80.1	65.7	56.2	48.7	43.4	39.3	35.8	32.9	28.4	22.2	18.4	15.7	8.44	5.76	4.20
AVR45-17	193	147	121	91.5	75.0	64.2	55.7	49.6	44.9	40.9	37.6	32.4	25.4	21.0	18.0	9.65	6.58	4.80
AVR45-19	217	165	136	103	84.4	72.3	62.6	55.8	50.5	46.0	42.3	36.5	28.6	23.6	20.2	10.9	7.40	5.40
AVR45-21	241	183	151	114	93.8	80.3	69.6	62.0	56.1	51.1	46.9	40.5	31.7	26.3	22.5	12.1	8.23	6.00
AVR45-23	265	202	166	126	103	88.3	76.6	68.2	61.7	56.2	51.6	44.6	34.9	28.9	24.7	13.3	9.05	6.60
AVR45-25	289	220	181	137	113	96.3	83.5	74.4	67.3	61.3	56.3	48.6	38.1	31.5	27.0	14.5	9.87	7.20
AVR45-27	313	238	196	149	122	104	90.5	80.6	73.0	66.4	61.0	52.7	41.3	34.1	29.2	15.7	10.7	7.80
AVR45-29	337	257	211	160	131	112	97.4	86.8	78.6	71.5	65.7	56.7	44.4	36.8	31.5	16.9	11.5	8.40
AVR45-31	361	275	226	172	141	120	104	93.0	84.2	76.6	70.4	60.8	47.6	39.4	33.7	18.1	12.3	9.00
AVR45-33	385	293	242	183	150	128	111	99.2	89.8	81.7	75.1	64.8	50.8	42.0	36.0	19.3	13.2	9.60

Ratings in Amperes at 77°F (25°C) to 1.81 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	47.4	36.3	30.0	22.8	18.6	16.0	13.9	12.3	11.2	10.2	9.34	8.07	6.33	5.24	4.49	2.41	1.64	1.20
AVR45-7	71.1	54.4	45.0	34.1	28.0	24.0	20.8	18.5	16.8	15.3	14.0	12.1	9.49	7.86	6.73	3.61	2.46	1.80
AVR45-9	94.8	72.6	60.0	45.5	37.3	32.0	27.7	24.7	22.4	20.3	18.7	16.1	12.7	10.5	8.98	4.81	3.28	2.39
AVR45-11	119	90.7	75.0	56.9	46.6	40.0	34.6	30.9	27.9	25.4	23.4	20.2	15.8	13.1	11.2	6.02	4.10	2.99
AVR45-13	142	109	90.0	68.3	55.9	48.0	41.6	37.0	33.5	30.5	28.0	24.2	19.0	15.7	13.5	7.22	4.92	3.59
AVR45-15	166	127	105	79.7	65.2	56.0	48.5	43.2	39.1	35.6	32.7	28.3	22.1	18.3	15.7	8.42	5.74	4.19
AVR45-17	190	145	120	91.0	74.6	64.0	55.4	49.4	44.7	40.7	37.4	32.3	25.3	21.0	18.0	9.63	6.56	4.79
AVR45-19	213	163	135	102	83.9	72.0	62.4	55.6	50.3	45.8	42.0	36.3	28.5	23.6	20.2	10.8	7.38	5.39
AVR45-21	237	181	150	114	93.2	80.0	69.3	61.7	55.9	50.8	46.7	40.4	31.6	26.2	22.4	12.0	8.20	5.99
AVR45-23	261	200	165	125	103	88.0	76.2	67.9	61.5	55.9	51.4	44.4	34.8	28.8	24.7	13.2	9.03	6.58
AVR45-25	285	218	180	137	112	96.0	83.1	74.1	67.1	61.0	56.1	48.4	38.0	31.4	26.9	14.4	9.85	7.18
AVR45-27	308	236	195	148	121	104	90.1	80.3	72.7	66.1	60.7	52.5	41.1	34.0	29.2	15.6	10.7	7.78
AVR45-29	332	254	210	159	130	112	97.0	86.4	78.2	71.2	65.4	56.5	44.3	36.7	31.4	16.8	11.5	8.38
AVR45-31	356	272	225	171	140	120	104	92.6	83.8	76.3	70.1	60.5	47.5	39.3	33.7	18.1	12.3	8.98
AVR45-33	379	290	240	182	149	128	111	98.8	89.4	81.3	74.7	64.6	50.6	41.9	35.9	19.3	13.1	9.58

Ratings in Amperes at 77°F (25°C) to 1.84 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	44.0	34.3	28.7	22.0	18.0	15.4	13.6	12.0	10.9	9.92	9.14	7.91	6.21	5.15	4.42	2.36	1.62	1.18
AVR45-7	66.0	51.4	43.1	33.0	27.0	23.1	20.4	18.1	16.3	14.9	13.7	11.9	9.31	7.72	6.63	3.54	2.42	1.77
AVR45-9	88.0	68.6	57.4	44.0	36.0	30.9	27.1	24.1	21.7	19.8	18.3	15.8	12.4	10.3	8.83	4.72	3.23	2.36
AVR45-11	110	85.7	71.8	55.0	45.0	38.6	33.9	30.1	27.1	24.8	22.9	19.8	15.5	12.9	11.0	5.91	4.04	2.94
AVR45-13	132	103	86.1	66.0	54.0	46.3	40.7	36.1	32.6	29.7	27.4	23.7	18.6	15.4	13.3	7.09	4.85	3.53
AVR45-15	154	120	100	77.0	63.0	54.0	47.5	42.1	38.0	34.7	32.0	27.7	21.7	18.0	15.5	8.27	5.65	4.12
AVR45-17	176	137	115	88.0	72.0	61.7	54.3	48.2	43.4	39.7	36.6	31.6	24.8	20.6	17.7	9.45	6.46	4.71
AVR45-19	198	154	129	99.0	81.0	69.4	61.1	54.2	48.9	44.6	41.1	35.6	27.9	23.2	19.9	10.6	7.27	5.30
AVR45-21	220	171	144	110	90.0	77.1	67.9	60.2	54.3	49.6	45.7	39.5	31.0	25.7	22.1	11.8	8.08	5.89
AVR45-23	242	189	158	121	99.0	84.9	74.6	66.2	59.7	54.5	50.3	43.5	34.1	28.3	24.3	13.0	8.89	6.48
AVR45-25	264	206	172	132	108	92.6	81.4	72.2	65.1	59.5	54.9	47.4	37.3	30.9	26.5	14.2	9.69	7.07
AVR45-27	286	223	187	143	117	100	88.2	78.3	70.6	64.4	59.4	51.4	40.4	33.5	28.7	15.4	10.5	7.66
AVR45-29	308	240	201	154	126	108	95.0	84.3	76.0	69.4	64.0	55.3	43.5	36.0	30.9	16.5	11.3	8.24
AVR45-31	330	257	215	165	135	116	102	90.3	81.4	74.4	68.6	59.3	46.6	38.6	33.1	17.7	12.1	8.83
AVR45-33	352	274	230	176	144	123	109	96.3	86.9	79.3	73.1	63.2	49.7	41.2	35.3	18.9	12.9	9.42

Ratings in Amperes at 77°F (25°C) to 1.88 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	41.1	32.4	27.3	20.8	17.1	14.7	12.9	11.5	10.4	9.52	8.77	7.67	5.99	4.94	4.23	2.24	1.53	1.11
AVR45-7	61.7	48.5	40.9	31.1	25.7	22.0	19.4	17.3	15.6	14.3	13.2	11.5	8.98	7.41	6.34	3.37	2.29	1.67
AVR45-9	82.3	64.7	54.6	41.5	34.3	29.4	25.8	23.0	20.9	19.0	17.5	15.3	12.0	9.89	8.45	4.49	3.06	2.23
AVR45-11	103	80.9	68.2	51.9	42.9	36.7	32.3	28.8	26.1	23.8	21.9	19.2	15.0	12.4	10.6	5.61	3.82	2.79
AVR45-13	123	97.1	81.8	62.3	51.4	44.1	38.7	34.5	31.3	28.6	26.3	23.0	18.0	14.8	12.7	6.73	4.59	3.34
AVR45-15	144	113	95.5	72.7	60.0	51.4	45.2	40.3	36.5	33.3	30.7	26.8	21.0	17.3	14.8	7.86	5.35	3.90
AVR45-17	165	129	109	83.0	68.6	58.7	51.6	46.0	41.7	38.1	35.1	30.7	23.9	19.8	16.9	8.98	6.12	4.46
AVR45-19	185	146	123	93.4	77.1	66.1	58.1	51.8	46.9	42.8	39.5	34.5	26.9	22.2	19.0	10.1	6.88	5.01
AVR45-21	206	162	136	104	85.7	73.4	64.5	57.6	52.1	47.6	43.9	38.3	29.9	24.7	21.1	11.2	7.65	5.57
AVR45-23	226	178	150	114	94.3	80.8	71.0	63.3	57.4	52.3	48.2	42.2	32.9	27.2	23.2	12.3	8.41	6.13
AVR45-25	247	194	164	125	103	88.1	77.4	69.1	62.6	57.1	52.6	46.0	35.9	29.7	25.4	13.5	9.18	6.68
AVR45-27	267	210	177	135	111	95.4	83.9	74.8	67.8	61.9	57.0	49.8	38.9	32.1	27.5	14.6	9.94	7.24
AVR45-29	288	226	191	145	120	103	90.3	80.6	73.0	66.6	61.4	53.7	41.9	34.6	29.6	15.7	10.7	7.80
AVR45-31	309	243	205	156	129	110	96.8	86.3	78.2	71.4	65.8	57.5	44.9	37.1	31.7	16.8	11.5	8.36
AVR45-33	329	259	218	166	137	117	103	92.1	83.4	76.1	70.2	61.3	47.9	39.5	33.8	18.0	12.2	8.91

Ratings in Amperes at 77°F (25°C) to 1.90 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	37.1	29.8	25.4	19.5	16.1	13.8	12.2	10.9	9.93	9.06	8.34	7.24	5.71	4.75	4.08	2.18	1.48	1.08
AVR45-7	55.7	44.6	38.1	29.3	24.2	20.7	18.4	16.4	14.9	13.6	12.5	10.9	8.56	7.12	6.13	3.27	2.22	1.62
AVR45-9	74.3	59.5	50.9	39.0	32.3	27.7	24.5	21.9	19.9	18.1	16.7	14.5	11.4	9.49	8.17	4.35	2.96	2.16
AVR45-11	92.9	74.4	63.6	48.8	40.4	34.6	30.6	27.3	24.8	22.6	20.9	18.1	14.3	11.9	10.2	5.44	3.71	2.70
AVR45-13	111	89.3	76.3	58.6	48.4	41.5	36.7	32.8	29.8	27.2	25.0	21.7	17.1	14.2	12.3	6.53	4.45	3.24
AVR45-15	130	104	89.0	68.3	56.5	48.4	42.8	38.3	34.7	31.7	29.2	25.3	20.0	16.6	14.3	7.62	5.19	3.78
AVR45-17	149	119	102	78.1	64.6	55.3	48.9	43.8	39.7	36.2	33.4	29.0	22.8	19.0	16.3	8.71	5.93	4.32
AVR45-19	167	134	114	87.8	72.6	62.2	55.1	49.2	44.7	40.8	37.5	32.6	25.7	21.4	18.4	9.80	6.67	4.86
AVR45-21	186	149	127	97.6	80.7	69.1	61.2	54.7	49.6	45.3	41.7	36.2	28.5	23.7	20.4	10.9	7.41	5.40
AVR45-23	204	164	140	107	88.8	76.1	67.3	60.2	54.6	49.8	45.9	39.8	31.4	26.1	22.5	12.0	8.15	5.94
AVR45-25	223	179	153	117	96.8	83.0	73.4	65.6	59.6	54.3	50.1	43.4	34.2	28.5	24.5	13.1	8.89	6.48
AVR45-27	241	193	165	127	105	89.9	79.5	71.1	64.5	58.9	54.2	47.0	37.1	30.9	26.5	14.2	9.63	7.02
AVR45-29	260	208	178	137	113	96.8	85.7	76.6	69.5	63.4	58.4	50.7	40.0	33.2	28.6	15.2	10.4	7.56
AVR45-31	279	223	191	146	121	104	91.8	82.0	74.5	67.9	62.6	54.3	42.8	35.6	30.6	16.3	11.1	8.10
AVR45-33	297	238	203	156	129	111	97.9	87.5	79.4	72.5	66.7	57.9	45.7	38.0	32.7	17.4	11.9	8.64



SPACESAVER™ SYSTEMS AVR45 DISCHARGE RATES IN AMPS (cont.)

Ratings in Amperes at 77°F (25°C) to 1.94 v.p.c.

Cell Type	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR45-5	33.1	26.6	22.7	17.8	14.6	12.6	11.0	9.86	8.93	8.15	7.51	6.57	5.18	4.31	3.70	1.92	1.31	0.95
AVR45-7	49.7	39.9	34.1	26.7	22.0	18.9	16.6	14.8	13.4	12.2	11.3	9.86	7.77	6.46	5.55	2.88	1.96	1.43
AVR45-9	66.3	53.1	45.4	35.6	29.3	25.1	22.1	19.7	17.9	16.3	15.0	13.1	10.4	8.61	7.41	3.84	2.62	1.90
AVR45-11	82.9	66.4	56.8	44.5	36.6	31.4	27.6	24.6	22.3	20.4	18.8	16.4	12.9	10.8	9.26	4.80	3.27	2.38
AVR45-13	99.4	79.7	68.1	53.4	43.9	37.7	33.1	29.6	26.8	24.5	22.5	19.7	15.5	12.9	11.1	5.76	3.93	2.85
AVR45-15	116	93.0	79.5	62.3	51.2	44.0	38.7	34.5	31.2	28.5	26.3	23.0	18.1	15.1	13.0	6.73	4.58	3.33
AVR45-17	133	106	90.8	71.2	58.6	50.3	44.2	39.4	35.7	32.6	30.1	26.3	20.7	17.2	14.8	7.69	5.24	3.80
AVR45-19	149	120	102	80.1	65.9	56.6	49.7	44.3	40.2	36.7	33.8	29.6	23.3	19.4	16.7	8.65	5.89	4.28
AVR45-21	166	133	114	89.0	73.2	62.9	55.2	49.3	44.6	40.8	37.6	32.9	25.9	21.5	18.5	9.61	6.55	4.76
AVR45-23	182	146	125	97.9	80.5	69.1	60.8	54.2	49.1	44.8	41.3	36.1	28.5	23.7	20.4	10.6	7.20	5.23
AVR45-25	199	159	136	107	87.8	75.4	66.3	59.1	53.6	48.9	45.1	39.4	31.1	25.8	22.2	11.5	7.86	5.71
AVR45-27	215	173	148	116	95.2	81.7	71.8	64.1	58.0	53.0	48.8	42.7	33.7	28.0	24.1	12.5	8.51	6.18
AVR45-29	232	186	159	125	102	88.0	77.3	69.0	62.5	57.1	52.6	46.0	36.3	30.1	25.9	13.5	9.17	6.66
AVR45-31	249	199	170	134	110	94.3	82.9	73.9	67.0	61.1	56.4	49.3	38.8	32.3	27.8	14.4	9.82	7.13
AVR45-33	265	213	182	142	117	101	88.4	78.8	71.4	65.2	60.1	52.6	41.4	34.4	29.6	15.4	10.5	7.61

EAST PENN manufacturing co., inc.

DISTRIBUTED BY:

Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781

Order Department Hotline: 610-682-3263

www.eastpennunigy.com

e-mail: sales@eastpennunigy.com

E.P.M. Form No. 1151 6/10 © 2010 by EPM Printed in U.S.A.

All data subject to change without notice.
No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.