



SPACE SAVER™ SYSTEMS AVR95 DISCHARGE RATES IN AMPS

Ratings in Amperes at 77°F (25°C) to 1.60 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	522	452	391	347	313	260	171	130	106	77.9	62.2	52.2	45.2	40.0	36.0	32.8	30.1	26.1	20.6	17.1	14.7	7.99	5.5	4.1
AVR95-9	696	602	521	462	417	346	228	173	141	104	82.9	69.6	60.3	53.4	48.0	43.7	40.2	34.7	27.5	22.8	19.5	10.7	7.4	5.4
AVR95-11	870	753	651	578	521	433	286	217	176	130	104	87.0	75.4	66.7	60.0	54.6	50.2	43.4	34.4	28.6	24.4	13.3	9.2	6.8
AVR95-13	1044	904	781	694	626	520	343	260	212	156	124	104	90.4	80.1	72.0	65.6	60.3	52.1	41.3	34.3	29.3	16.0	11.1	8.1
AVR95-15	1218	1054	911	809	730	606	400	303	247	182	145	122	106	93.4	84.0	76.5	70.3	60.8	48.1	40.0	34.2	18.7	12.9	9.5
AVR95-17	1392	1205	1042	925	834	693	457	347	282	208	166	139	121	107	96.0	87.4	80.4	69.5	55.0	45.7	39.1	21.3	14.8	10.8
AVR95-19	1566	1355	1172	1040	938	779	514	390	318	234	187	157	136	120	108	98.3	90.4	78.2	61.9	51.4	44.0	24.0	16.6	12.2
AVR95-21	1740	1506	1302	1156	1043	866	571	433	353	260	207	174	151	133	120	109	100	86.8	68.8	57.1	48.9	26.6	18.4	13.6
AVR95-23	1914	1657	1432	1272	1147	953	628	477	388	286	228	191	166	147	132	120	110	95.5	75.7	62.8	53.8	29.3	20.3	14.9
AVR95-25	2088	1807	1562	1387	1251	1039	685	520	424	312	249	209	181	160	144	131	121	104	82.5	68.5	58.6	32.0	22.1	16.3
AVR95-27	2262	1958	1693	1503	1355	1126	742	563	459	338	270	226	196	174	156	142	131	113	89.4	74.2	63.5	34.6	24.0	17.6
AVR95-29	2436	2108	1823	1618	1460	1212	799	607	494	364	290	243	211	187	168	153	141	122	96.3	79.9	68.4	37.3	25.8	19.0
AVR95-31	2610	2259	1953	1734	1564	1299	857	650	529	390	311	261	226	200	180	164	151	130	103	85.7	73.3	40.0	27.7	20.3
AVR95-33	2784	2410	2083	1850	1668	1386	914	693	565	416	332	278	241	214	192	175	161	139	110	91.4	78.2	42.6	29.5	21.7

Ratings in Amperes at 77°F (25°C) to 1.63 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	495	430	374	333	302	253	168	129	105	77.6	62.0	52.0	45.1	39.9	35.9	32.7	30.0	26.0	20.6	17.1	14.6	8.0	5.5	4.1
AVR95-9	660	574	498	444	402	338	225	172	140	103	82.6	69.4	60.1	53.2	47.9	43.6	40.1	34.6	27.4	22.8	19.5	10.6	7.4	5.4
AVR95-11	825	717	623	555	503	422	281	215	174	129	103	86.7	75.2	66.6	59.8	54.5	50.1	43.3	34.3	28.5	24.3	13.3	9.2	6.8
AVR95-13	990	860	747	666	603	506	337	258	209	155	124	104	90.2	79.9	71.8	65.4	60.1	51.9	41.1	34.1	29.2	15.9	11.0	8.1
AVR95-15	1155	1004	872	777	704	591	393	301	244	181	145	121	105	93.2	83.8	76.3	70.1	60.6	48.0	39.8	34.1	18.6	12.9	9.5
AVR95-17	1320	1147	996	888	804	675	449	344	279	207	165	139	120	106	95.7	87.1	80.1	69.2	54.8	45.5	39.0	21.3	14.7	10.8
AVR95-19	1485	1291	1121	999	905	760	505	387	314	233	186	156	135	120	108	98.0	90.1	77.9	61.7	51.2	43.8	23.9	16.6	12.2
AVR95-21	1650	1434	1245	1110	1005	844	561	430	349	259	207	173	150	133	120	109	100	86.6	68.5	56.9	48.7	26.6	18.4	13.5
AVR95-23	1815	1577	1370	1221	1106	928	617	473	384	285	227	191	165	146	132	120	110	95.2	75.4	62.6	53.6	29.2	20.2	14.9
AVR95-25	1980	1721	1494	1332	1206	1013	674	516	419	310	248	208	180	160	144	131	120	104	82.2	68.3	58.4	31.9	22.1	16.2
AVR95-27	2145	1864	1619	1443	1307	1097	730	559	453	336	269	225	195	173	156	142	130	113	89.1	74.0	63.3	34.6	23.9	17.6
AVR95-29	2310	2008	1743	1554	1407	1182	786	602	488	362	289	243	210	186	168	153	140	121	95.9	79.7	68.2	37.2	25.8	19.0
AVR95-31	2475	2151	1868	1665	1508	1266	842	645	523	388	310	260	225	200	179	163	150	130	103	85.4	73.0	39.9	27.6	20.3
AVR95-33	2640	2294	1992	1776	1608	1350	898	688	558	414	331	278	241	213	191	174	160	138	110	91.1	77.9	42.5	29.5	21.7

Ratings in Amperes at 77°F (25°C) to 1.67 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	434	392	350	315	287	244	166	128	105	77.2	61.8	51.9	45.0	39.8	35.8	32.6	30.0	25.9	20.5	17.0	14.6	7.95	5.5	4.1
AVR95-9	578	523	466	420	382	325	222	170	139	103	82.4	69.2	60.0	53.1	47.7	43.4	39.9	34.5	27.3	22.7	19.4	10.6	7.3	5.4
AVR95-11	723	654	583	525	478	406	277	213	174	129	103	86.5	75.0	66.4	59.7	54.3	49.9	43.1	34.1	28.3	24.3	13.3	9.2	6.8
AVR95-13	868	785	699	630	573	487	332	256	209	154	124	104	89.9	79.7	71.6	65.2	59.9	51.8	41.0	34.0	29.1	15.9	11.0	8.1
AVR95-15	1012	916	816	735	669	568	388	298	244	180	144	121	105	92.9	83.6	76.0	69.9	60.4	47.8	39.7	34.0	18.6	12.9	9.5
AVR95-17	1157	1046	932	840	764	650	443	341	279	206	165	138	120	106	95.5	86.9	79.9	69.0	54.6	45.4	38.8	21.2	14.7	10.8
AVR95-19	1301	1177	1049	945	860	731	499	383	314	232	185	156	135	119	107	97.8	89.9	77.7	61.5	51.0	43.7	23.9	16.5	12.2
AVR95-21	1446	1308	1166	1050	956	812	554	426	349	257	206	173	150	133	119	109	99.8	86.3	68.3	56.7	48.5	26.5	18.4	13.5
AVR95-23	1591	1439	1282	1155	1051	893	609	469	383	283	227	190	165	146	131	119	110	94.9	75.1	62.4	53.4	29.2	20.2	14.9
AVR95-25	1735	1570	1399	1260	1147	974	665	511	418	309	247	208	180	159	143	130	120	104	81.9	68.0	58.2	31.8	22.0	16.2
AVR95-27	1880	1700	1515	1365	1242	1056	720	554	453	335	268	225	195	173	155	141	130	112	88.8	73.7	63.1	34.5	23.9	17.6
AVR95-29	2024	1831	1632	1470	1338	1137	775	596	488	360	288	242	210	186	167	152	140	121	95.6	79.4	67.9	37.1	25.7	18.9
AVR95-31	2169	1962	1748	1575	1433	1218	831	639	523	386	309	259	225	199	179	163	150	129	102	85.0	72.8	39.8	27.5	20.3
AVR95-33	2314	2093	1865	1680	1529	1299	886	682	558	412	330	277	240	212	191	174	160	138	109	90.7	77.6	42.4	29.4	21.6



SPACESAVER™ SYSTEMS

AVR95 DISCHARGE RATES IN AMPS (cont.)

Ratings in Amperes at 77°F (25°C) to 1.70 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	414	372	331	298	273	233	162	127	104	76.9	61.6	51.8	44.8	39.7	35.7	32.5	29.9	25.9	20.5	17.0	14.5	7.9	5.5	4.0
AVR95-9	552	495	442	398	364	311	217	169	138	103	82.2	69.0	59.8	53.0	47.7	43.4	39.9	34.5	27.3	22.6	19.4	10.6	7.3	5.4
AVR95-11	690	619	552	497	455	389	271	211	173	128	103	86.3	74.7	66.2	59.6	54.2	49.9	43.1	34.1	28.3	24.2	13.2	9.2	6.7
AVR95-13	828	743	662	596	546	467	325	253	207	154	123	104	89.7	79.5	71.5	65.1	59.8	51.7	40.9	34.0	29.1	15.9	11.0	8.1
AVR95-15	966	867	773	696	637	545	379	296	242	179	144	121	105	92.7	83.4	75.9	69.8	60.3	47.7	39.6	33.9	18.5	12.8	9.4
AVR95-17	1104	991	883	795	728	622	433	338	277	205	164	138	120	106	95.3	86.8	79.8	68.9	54.6	45.3	38.8	21.2	14.7	10.8
AVR95-19	1242	1115	994	895	819	700	487	380	311	231	185	155	135	119	107	97.6	89.7	77.6	61.4	51.0	43.6	23.8	16.5	12.1
AVR95-21	1380	1238	1104	994	911	778	542	422	346	256	205	173	149	132	119	108	99.7	86.2	68.2	56.6	48.4	26.5	18.3	13.5
AVR95-23	1518	1362	1214	1093	1002	856	596	465	380	282	226	190	164	146	131	119	110	94.8	75.0	62.3	53.3	29.1	20.2	14.8
AVR95-25	1656	1486	1325	1193	1093	934	650	507	415	308	246	207	179	159	143	130	120	103	81.8	67.9	58.1	31.8	22.0	16.2
AVR95-27	1794	1610	1435	1292	1184	1011	704	549	450	333	267	224	194	172	155	141	130	112	88.7	73.6	63.0	34.4	23.8	17.5
AVR95-29	1932	1734	1546	1392	1275	1089	758	591	484	359	288	242	209	185	167	152	140	121	95.5	79.3	67.8	37.1	25.7	18.9
AVR95-31	2070	1858	1656	1491	1366	1167	812	634	519	385	308	259	224	199	179	163	150	129	102	84.9	72.7	39.7	27.5	20.2
AVR95-33	2208	1981	1766	1590	1457	1245	867	676	553	410	329	276	239	212	191	174	160	138	109	90.6	77.5	42.4	29.3	21.6

Ratings in Amperes at 77°F (25°C) to 1.75 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	360	326	296	271	250	217	157	123	102	76.1	61.2	51.5	44.7	39.6	35.6	32.4	29.8	25.8	20.4	16.9	14.5	7.9	5.5	4.03
AVR95-9	480	434	395	362	334	290	209	164	136	102	81.6	68.7	59.6	52.8	47.5	43.2	39.8	34.4	27.2	22.6	19.3	10.6	7.3	5.38
AVR95-11	600	543	494	452	417	362	261	205	170	127	102	85.8	74.5	66.0	59.4	54.1	49.7	43.0	34.0	28.2	24.2	13.2	9.1	6.72
AVR95-13	720	652	592	542	500	434	313	246	204	152	122	103	89.4	79.2	71.2	64.9	59.6	51.6	40.8	33.9	29.0	15.8	11.0	8.07
AVR95-15	840	760	691	633	584	507	365	287	238	178	143	120	104	92.4	83.1	75.7	69.6	60.2	47.6	39.5	33.8	18.5	12.8	9.41
AVR95-17	960	869	790	723	667	579	418	329	272	203	163	137	119	106	95.0	86.5	79.5	68.8	54.4	45.2	38.7	21.1	14.6	10.8
AVR95-19	1080	977	888	814	751	652	470	370	306	228	184	154	134	119	107	97.3	89.5	77.4	61.2	50.8	43.5	23.7	16.5	12.1
AVR95-21	1200	1086	987	904	834	724	522	411	339	254	204	172	149	132	119	108	99.4	85.9	68.0	56.5	48.3	26.4	18.3	13.4
AVR95-23	1320	1195	1086	994	917	796	574	452	373	279	224	189	164	145	131	119	109	94.5	74.8	62.1	53.2	29.0	20.1	14.8
AVR95-25	1440	1303	1184	1085	1001	869	626	493	407	305	245	206	179	158	142	130	119	103	81.6	67.8	58.0	31.7	21.9	16.1
AVR95-27	1560	1412	1283	1175	1084	941	679	534	441	330	265	223	194	172	154	141	129	112	88.4	73.4	62.8	34.3	23.8	17.5
AVR95-29	1680	1520	1382	1266	1168	1014	731	575	475	355	286	240	209	185	166	151	139	120	95.2	79.1	67.7	36.9	25.6	18.8
AVR95-31	1800	1629	1481	1356	1251	1086	783	616	509	381	306	257	223	198	178	162	149	129	102	84.7	72.5	39.6	27.4	20.2
AVR95-33	1920	1738	1579	1446	1334	1158	835	657	543	406	326	275	238	211	190	173	159	138	109	90.4	77.3	42.2	29.2	21.5

Ratings in Amperes at 77°F (25°C) to 1.80 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	315	288	264	242	224	196	146	117	98.0	74.2	60.1	50.7	44.1	39.1	35.3	32.1	29.6	25.6	20.3	16.9	14.4	7.9	5.5	4.0
AVR95-9	420	384	352	322	299	262	195	156	131	98.9	80.1	67.6	58.8	52.2	47.0	42.9	39.4	34.1	27.0	22.5	19.2	10.5	7.3	5.3
AVR95-11	525	480	440	403	374	327	244	195	163	124	100	84.6	73.5	65.2	58.8	53.6	49.3	42.7	33.8	28.1	24.0	13.1	9.1	6.7
AVR95-13	630	576	527	484	448	392	293	234	196	148	120	101	88.2	78.3	70.5	64.3	59.2	51.2	40.6	33.7	28.8	15.8	10.9	8.0
AVR95-15	735	672	615	564	523	458	341	273	229	173	140	118	103	91.3	82.3	75.0	69.0	59.7	47.3	39.3	33.7	18.4	12.7	9.4
AVR95-17	840	768	703	645	598	523	390	312	261	198	160	135	118	104	94.0	85.7	78.9	68.3	54.1	44.9	38.5	21.0	14.5	10.7
AVR95-19	945	864	791	725	672	589	439	351	294	223	180	152	132	117	106	96.4	88.8	76.8	60.9	50.6	43.3	23.6	16.4	12.0
AVR95-21	1050	960	879	806	747	654	488	390	327	247	200	169	147	130	118	107	98.6	85.3	67.6	56.2	48.1	26.3	18.2	13.4
AVR95-23	1155	1056	967	887	822	719	537	429	359	272	220	186	162	144	129	118	108	93.9	74.4	61.8	52.9	28.9	20.0	14.7
AVR95-25	1260	1152	1055	967	896	785	585	468	392	297	240	203	176	157	141	129	118	102	81.1	67.4	57.7	31.5	21.8	16.0
AVR95-27	1365	1248	1143	1048	971	850	634	507	425	321	260	220	191	170	153	139	128	111	87.9	73.0	62.5	34.1	23.6	17.4
AVR95-29	1470	1344	1231	1128	1046	916	683	546	457	346	280	237	206	183	165	150	138	119	94.7	78.6	67.3	36.8	25.4	18.7
AVR95-31	1575	1440	1319	1209	1121	981	732	585	490	371	300	254	221	196	176	161	148	128	101	84.3	72.1	39.4	27.3	20.1
AVR95-33	1680	1536	1406	1290	1195	1046	780	624	523	396	320	271	235	209	188	171	158	137	108	89.9	76.9	42.0	29.1	21.4



SPACE SAVER™ SYSTEMS

AVR95 DISCHARGE RATES IN AMPS (cont.)

Ratings in Amperes at 77°F (25°C) to 1.85 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	252	236	221	208	195	175	133	108	91.5	70.3	57.4	49.6	42.5	37.9	34.2	31.2	28.8	25.0	19.8	16.5	14.1	7.7	5.3	3.9
AVR95-9	336	314	295	277	260	233	177	144	122	93.7	76.6	66.2	56.7	50.5	45.6	41.6	38.4	33.3	26.5	22.0	18.8	10.3	7.1	5.2
AVR95-11	420	393	369	346	326	292	222	180	153	117	95.7	82.7	70.9	63.1	57.0	52.0	48.0	41.6	33.1	27.5	23.6	12.9	8.9	6.5
AVR95-13	504	472	443	415	391	350	266	216	183	141	115	99.3	85.1	75.7	68.4	62.4	57.6	49.9	39.7	33.0	28.3	15.5	10.7	7.9
AVR95-15	588	550	517	484	456	408	311	253	214	164	134	116	99.3	88.3	79.8	72.9	67.2	58.3	46.3	38.5	33.0	18.0	12.5	9.2
AVR95-17	672	629	590	554	521	466	355	289	244	187	153	132	113	101	91.2	83.3	76.8	66.6	52.9	44.0	37.7	20.6	14.3	10.5
AVR95-19	756	707	664	623	586	525	399	325	275	211	172	149	128	114	103	93.7	86.4	74.9	59.5	49.5	42.4	23.2	16.0	11.8
AVR95-21	840	786	738	692	651	583	444	361	305	234	191	165	142	126	114	104	96.0	83.2	66.1	55.0	47.1	25.8	17.8	13.1
AVR95-23	924	865	812	761	716	641	488	397	336	258	211	182	156	139	125	114	106	91.6	72.8	60.5	51.8	28.3	19.6	14.4
AVR95-25	1008	943	886	830	781	700	532	433	366	281	230	199	170	151	137	125	115	99.9	79.4	66.0	56.5	30.9	21.4	15.7
AVR95-27	1092	1022	959	900	846	758	577	469	397	305	249	215	184	164	148	135	125	108	86.0	71.5	61.3	33.5	23.2	17.0
AVR95-29	1176	1100	1033	969	911	816	621	505	427	328	268	232	199	177	160	146	134	117	92.6	77.0	66.0	36.1	24.9	18.3
AVR95-31	1260	1179	1107	1038	977	875	665	541	458	351	287	248	213	189	171	156	144	125	99.2	82.5	70.7	38.6	26.7	19.6
AVR95-33	1344	1258	1181	1107	1042	933	710	577	488	375	306	265	227	202	182	167	154	133	106	88.0	75.4	41.2	28.5	21.0

Ratings in Amperes at 77°F (25°C) to 1.86 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	243	229	215	201	190	170	130	107	89.7	69.1	56.6	48.7	42.0	37.4	33.8	30.9	28.5	24.7	19.7	16.4	14.0	7.6	5.3	3.9
AVR95-9	323	305	286	268	253	227	173	142	120	92.1	75.4	64.9	56.0	49.9	45.1	41.2	38.0	33.0	26.2	21.8	18.7	10.2	7.1	5.2
AVR95-11	404	381	358	335	316	283	216	178	150	115	94.3	81.1	70.0	62.3	56.3	51.5	47.5	41.2	32.8	27.3	23.3	12.7	8.8	6.5
AVR95-13	485	457	429	402	379	340	260	213	179	138	113	97.3	84.0	74.8	67.6	61.8	57.0	49.5	39.3	32.7	28.0	15.3	10.6	7.8
AVR95-15	566	533	501	469	443	397	303	249	209	161	132	114	98.0	87.3	78.9	72.1	66.5	57.7	45.9	38.2	32.7	17.8	12.4	9.1
AVR95-17	647	610	572	536	506	453	346	284	239	184	151	130	112	100	90.1	82.4	76.0	65.9	52.4	43.6	37.3	20.4	14.1	10.4
AVR95-19	728	686	644	604	569	510	389	320	269	207	170	146	126	112	101	92.7	85.5	74.2	59.0	49.1	42.0	22.9	15.9	11.7
AVR95-21	809	762	715	671	632	567	433	355	299	230	189	162	140	125	113	103	95.0	82.4	65.5	54.5	46.7	25.5	17.6	13.0
AVR95-23	890	838	787	738	696	623	476	391	329	253	207	178	154	137	124	113	104	90.7	72.1	60.0	51.4	28.0	19.4	14.3
AVR95-25	970	914	858	805	759	680	519	426	359	276	226	195	168	150	135	124	114	98.9	78.6	65.4	56.0	30.6	21.2	15.6
AVR95-27	1051	991	930	872	822	737	562	462	389	299	245	211	182	162	146	134	123	107	85.2	70.9	60.7	33.1	22.9	16.9
AVR95-29	1132	1067	1001	939	885	794	606	497	419	322	264	227	196	175	158	144	133	115	91.7	76.3	65.4	35.7	24.7	18.2
AVR95-31	1213	1143	1073	1006	949	850	649	533	449	345	283	243	210	187	169	154	142	124	98.3	81.8	70.0	38.2	26.5	19.4
AVR95-33	1294	1219	1144	1073	1012	907	692	568	478	368	302	259	224	199	180	165	152	132	105	87.2	74.7	40.8	28.2	20.7

Ratings in Amperes at 77°F (25°C) to 1.88 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	225	215	202	189	179	161	124	103	86.2	66.7	54.9	46.8	41.0	36.6	33.1	30.3	27.9	24.3	19.3	16.1	13.7	7.5	5.2	3.8
AVR95-9	300	287	269	252	239	214	165	138	115	88.9	73.1	62.4	54.6	48.7	44.1	40.3	37.2	32.3	25.7	21.4	18.3	10.0	6.9	5.1
AVR95-11	375	358	336	315	299	268	206	172	144	111	91.4	77.9	68.3	60.9	55.1	50.4	46.5	40.4	32.2	26.8	22.9	12.5	8.7	6.4
AVR95-13	450	430	403	378	358	322	247	207	172	133	110	93.5	82.0	73.1	66.1	60.5	55.8	48.5	38.6	32.1	27.5	15.0	10.4	7.6
AVR95-15	525	501	470	441	418	375	288	241	201	156	128	109	95.6	85.3	77.1	70.6	65.1	56.6	45.0	37.5	32.1	17.5	12.1	8.9
AVR95-17	600	573	538	504	478	429	329	275	230	178	146	125	109	97.5	88.1	80.7	74.4	64.7	51.5	42.8	36.7	20.0	13.8	10.2
AVR95-19	675	645	605	567	537	482	371	310	259	200	165	140	123	110	99.2	90.8	83.7	72.8	57.9	48.2	41.2	22.5	15.6	11.4
AVR95-21	750	716	672	630	597	536	412	344	287	222	183	156	137	122	110	101	93.0	80.8	64.3	53.5	45.8	24.9	17.3	12.7
AVR95-23	825	788	739	693	657	590	453	379	316	244	201	171	150	134	121	111	102	88.9	70.8	58.9	50.4	27.4	19.0	14.0
AVR95-25	900	860	806	756	716	643	494	413	345	267	219	187	164	146	132	121	112	97.0	77.2	64.2	55.0	29.9	20.8	15.3
AVR95-27	975	931	874	819	776	697	535	447	373	289	238	203	178	158	143	131	121	105	83.6	69.6	59.6	32.4	22.5	16.5
AVR95-29	1050	1003	941	882	836	750	576	482	402	311	256	218	191	171	154	141	130	113	90.1	74.9	64.2	34.9	24.2	17.8
AVR95-31	1125	1075	1008	945	896	804	618	516	431	333	274	234	205	183	165	151	140	121	96.5	80.3	68.7	37.4	26.0	19.1
AVR95-33	1200	1146	1075	1008	955	858	659	551	460	356	293	249	219	195	176	161	149	129	103	85.6	73.3	39.9	27.7	20.3



SPACE SAVER™ SYSTEMS AVR95 DISCHARGE RATES IN AMPS (cont.)

Ratings in Amperes at 77°F (25°C) to 1.90 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	207	198	187	175	167	150	116	95.9	81.9	63.9	52.7	45.1	39.6	35.4	32.1	29.4	27.1	23.6	18.7	15.6	13.4	7.3	5.0	3.7
AVR95-9	276	264	250	234	222	200	155	128	109	85.2	70.3	60.2	52.8	47.2	42.8	39.2	36.2	31.4	25.0	20.8	17.8	9.7	6.7	4.9
AVR95-11	345	330	312	292	278	251	194	160	136	107	87.8	75.2	66.0	59.1	53.5	49.0	45.2	39.3	31.2	26.0	22.3	12.2	8.4	6.2
AVR95-13	414	396	374	350	333	301	232	192	164	128	105	90.3	79.2	70.9	64.2	58.8	54.3	47.1	37.5	31.2	26.7	14.6	10.1	7.4
AVR95-15	483	462	437	409	389	351	271	224	191	149	123	105	92.4	82.7	74.8	68.5	63.3	55.0	43.7	36.4	31.2	17.0	11.8	8.6
AVR95-17	552	528	499	467	444	401	310	256	218	170	141	120	106	94.5	85.5	78.3	72.4	62.8	50.0	41.6	35.6	19.5	13.4	9.9
AVR95-19	621	594	562	526	500	451	349	288	246	192	158	135	119	106	96.2	88.1	81.4	70.7	56.2	46.8	40.1	21.9	15.1	11.1
AVR95-21	690	660	624	584	555	501	387	320	273	213	176	150	132	118	107	97.9	90.4	78.5	62.5	52.0	44.5	24.3	16.8	12.3
AVR95-23	759	726	686	642	611	551	426	352	300	234	193	166	145	130	118	108	99.5	86.4	68.7	57.2	49.0	26.8	18.5	13.6
AVR95-25	828	792	749	701	666	601	465	384	327	256	211	181	158	142	128	118	109	94.2	75.0	62.4	53.4	29.2	20.2	14.8
AVR95-27	897	858	811	759	722	651	503	415	355	277	228	196	172	154	139	127	118	102	81.2	67.6	57.9	31.6	21.8	16.0
AVR95-29	966	924	874	818	777	701	542	447	382	298	246	211	185	165	150	137	127	110	87.5	72.8	62.3	34.1	23.5	17.3
AVR95-31	1035	990	936	876	833	752	581	479	409	320	263	226	198	177	160	147	136	118	93.7	78.0	66.8	36.5	25.2	18.5
AVR95-33	1104	1056	998	934	888	802	620	511	437	341	281	241	211	189	171	157	145	126	100	83.2	71.3	38.9	26.9	19.7

Ratings in Amperes at 77°F (25°C) to 1.94 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	NA	NA	NA	NA	NA	NA	99.3	82.9	71.7	56.7	47.3	40.7	35.9	32.2	29.2	26.8	24.7	21.5	17.2	14.3	12.2	6.7	4.6	3.4
AVR95-9	NA	NA	NA	NA	NA	NA	132	111	95.6	75.6	63.1	54.3	47.9	42.9	39.0	35.7	33.0	28.7	22.9	19.0	16.3	8.9	6.2	4.5
AVR95-11	NA	NA	NA	NA	NA	NA	165	138	119	94.6	78.8	67.9	59.9	53.7	48.7	44.7	41.2	35.9	28.6	23.8	20.4	11.2	7.7	5.7
AVR95-13	NA	NA	NA	NA	NA	NA	199	166	143	113	94.6	81.5	71.9	64.4	58.5	53.6	49.5	43.0	34.3	28.5	24.5	13.4	9.2	6.8
AVR95-15	NA	NA	NA	NA	NA	NA	232	194	167	132	110	95.0	83.9	75.2	68.2	62.5	57.7	50.2	40.0	33.3	28.6	15.6	10.8	7.9
AVR95-17	NA	NA	NA	NA	NA	NA	265	221	191	151	126	109	95.9	85.9	77.9	71.5	66.0	57.4	45.7	38.0	32.6	17.9	12.3	9.0
AVR95-19	NA	NA	NA	NA	NA	NA	298	249	215	170	142	122	108	96.6	87.7	80.4	74.2	64.6	51.5	42.8	36.7	20.1	13.9	10.2
AVR95-21	NA	NA	NA	NA	NA	NA	331	276	239	189	158	136	120	107	97.4	89.3	82.5	71.7	57.2	47.5	40.8	22.3	15.4	11.3
AVR95-23	NA	NA	NA	NA	NA	NA	364	304	263	208	173	149	132	118	107	98.3	90.7	78.9	62.9	52.3	44.9	24.6	16.9	12.4
AVR95-25	NA	NA	NA	NA	NA	NA	397	332	287	227	189	163	144	129	117	107	99.0	86.1	68.6	57.0	48.9	26.8	18.5	13.6
AVR95-27	NA	NA	NA	NA	NA	NA	430	359	311	246	205	177	156	140	127	116	107	93.2	74.3	61.8	53.0	29.0	20.0	14.7
AVR95-29	NA	NA	NA	NA	NA	NA	463	387	335	265	221	190	168	150	136	125	115	100	80.0	66.5	57.1	31.3	21.6	15.8
AVR95-31	NA	NA	NA	NA	NA	NA	496	415	358	284	237	204	180	161	146	134	124	108	85.8	71.3	61.2	33.5	23.1	17.0
AVR95-33	NA	NA	NA	NA	NA	NA	529	442	382	303	252	217	192	172	156	143	132	115	91.5	76.0	65.3	35.7	24.7	18.1



DISTRIBUTED BY:

Lyon Station, PA 19536-0147 Phone: 610-682-3263 Fax: 610-682-0891

Order Department Hotline: 610-682-4231

www.dekabatteries.com

e-mail: reservepowersales@dekabatteries.com