



INDUSTRIAL BATTERIES

ATLET

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)	Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No		
APM, APC, APH 32.75 x 12.8125 x 23.625 Atlet #56147	24	12-D85-13 sp	11.87	510	85	3315	32.5	12.75	22.625	1053		X	B 24	SBX6370
	24	12-H80-13 sp	11.17	480	80	3315	32.5	12.75	22.625	1011		X	B 24	SBX6370
	24	12-P95-13 sp	13.27	570	95	3315	32.5	12.75	22.625	1064		X	B 24	SBX6370
AJN 2200, AJN 2650 ATF 2200 Junior, NPL 34.125 x 8.3125 x 23.625 Atlet #58116 NEW TRAY REQUIRED 24 Volt												X	B 24	SBX6370
ASN 2750, ASN 3500 ASN 4400, ATF 2200 Senior 34.125 x 12.75 x 23.625 Atlet #58316	24	12-D85-13 sp	11.87	510	85	3315	32.5	12.75	22.625	1053		X	B 24	SBX6370
	24	12-H80-13 sp	11.17	480	80	3315	32.5	12.75	22.625	1011		X	B 24	SBX6370
	24	12-P95-13 sp	13.27	570	95	3315	32.5	12.75	22.625	1064		X	B 24	SBX6370
U 2650 (R Chassis) U 3000 (R Chassis) U 3500 (R Chassis) U 4400 (R Chassis) UF (R Chassis) UH (R Chassis) 48.4375 x 11.4375 x 26.625 Atlet #69598 Compartment A NEW TRAY REQUIRED 24 Volt												X	B 24	SBX6341

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector	
			KWH	Ah			Length X	Width Y	Height Z		Yes	No				
U 2650 (R Chassis) U 3000 (R Chassis) U 3500 (R Chassis) U 4400 (R Chassis) UF (R Chassis) UH (R Chassis) 48.4375 x 11.5 x 26.625 Atlet #69598 Compartment A NEW TRAY REQUIRED 48 Volt												X	B	24	SBX6341	
U 2650 (R Chassis) U 3000 (R Chassis) U 3500 (R Chassis) U 4400 (R Shassis) UF (R Chassis) UH (R Chassis) 48.4375 x 12.8125 x 26.625 Atlet #69598 Compartment B NEW TRAY REQUIRED 24 Volt												X	B	24	SBX6341	
U 2650 (R Chassis) U 3000 (R Chassis) U 3500 (R Chassis) U 4400 (R Chassis) UF (R Chassis) UH (R Chassis) 48.4375 x 14.25 x 26.625 Atlet #69598 Compartment C NEW TRAY REQUIRED 24 Volt												X	B	24	SBX6341	
U 2650 (R Chassis) U 3000 (R Chassis) U 3500 (R Chassis) U 4400 (R Chassis) UF (R Chassis) UH (R Chassis) 48.4375 x 14.25 x 26.625 Atlet #69598 Compartment C	48	24-D100-9	sp	18.62	400	100	7194	48.4375	14.25	26.625	1766		X	B	24	SBX6341

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
U 2650 (R Chassis) U 3000 (R Chassis) U 3500 (R Chassis) U 4400 (R Chassis) UF (R Chassis) UH (R Chassis) 48.4375 x 15.75 x 26.625 Atlet #69598 Compartment D NEW TRAY REQUIRED 24 Volt												X	B	24	SBX6341
U 2650 (R Chassis) U 3000 (R Chassis) U 3500 (R Chassis) U 4400 (R Chassis) UF (R Chassis) UH (R Chassis) 48.4375 x 16.5 x 26.625 Atlet #69598 Compartment E	48	24-D100-11 SP	23.28	500	100	7226	48.4375	16.5	27.875	2157		X	B	24	SBX6341
U 2650 (X Chassis) U 3000 (X Chassis) U 3500 (X Chassis) U 4400 (X Chassis) UF (X Chassis) UH (X Chassis) 48.4375 x 11.4375 x 24.4375 Atlet #69904 Compartment A NEW TRAY REQUIRED 24 Volt												X	B	24	SBX6341
U 2650 (X Chassis) U 3000 (X Chassis) U 3500 (X Chassis) U 4400 (X Chassis) UF (X Chassis) UH (X Chassis) 48.4375 x 11.4375 x 24.4375 Atlet #69904 Compartment A NEW TRAY REQUIRED 48 Volt												X	B	24	SBX6341

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
U 2650 (X Chassis) U 3000 (X Chassis) U 3500 (X Chassis) U 4400 (X Chassis) UF (X Chassis) UH (X Chassis) 48.4375 x 12.8125 x 24.4375 Atlet #69904 Compartment B NEW TRAY REQUIRED 24 Volt												X	B	24	SBX6341
U 2650 (X Chassis) U 3000 (X Chassis) U 3500 (X Chassis) U 4400 (X Chassis) UF (X Chassis) UH (X Chassis) 48.4375 x 14.25 x 24.4375 Atlet #69904 Compartment C NEW TRAY REQUIRED 24 Volt												X	B	24	SBX6341
U 2650 (X Chassis) U 3000 (X Chassis) U 3500 (X Chassis) U 4400 (X Chassis) UF (X Chassis) UH (X Chassis) 48.4375 x 14.25 x 24.4375 Atlet #69904 Compartment C	48	24-D85-9	15.83	340	85	7665	47.5625	13.5	22.625	1436		X	B	24	SBX6341
	48	24-H80-9	14.90	320	80	7665	47.5625	13.5	22.625	1379		X	B	24	SBX6341
	48	24-P95-9	17.69	380	95	7665	47.5625	13.5	22.625	1450		X	B	24	SBX6341
U 2650 (X CHASSIS) U 3000 (X CHASSIS) U 3500 (X CHASSIS) U 4400 (X CHASSIS) UF (X CHASSIS) UH (X CHASSIS) 48.4375 x 15.625 x 24.4375 Atlet #69904 Compartment D NEW TRAY REQUIRED 24 Volt												X	B	24	SBX6341

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating KWH	Ah	Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector	
							Length X	Width Y	Height Z		Yes	No				
U 2650 (X CHASSIS)	48	24-D85-11	SP	19.79	425	85	7429	48.25	16.1875	24.375	2059		X	B	24	SBX6341
U 3000 (X CHASSIS)	48	24-H80-11	SP	18.62	400	80	7429	48.25	16.1875	24.375	1977		X	B	24	SBX6341
U 3500 (X CHASSIS)	48	24-P95-11	SP	22.12	475	95	7429	48.25	16.1875	24.375	2080		X	B	24	SBX6341
U 4400 (X CHASSIS) UF (X CHASSIS) UH (X CHASSIS) 48.4375 x 16.5 x 24.4375 Atlet #69904 Compartment E Min. Battery Wt. - 2030 lbs.																
US 3000 (R CHASSIS) US 3500 (R CHASSIS) US 4400 (R CHASSIS) 43.75 x 16.25 x 26.625 Atlet #71141 Compartment C NEW TRAY REQUIRED 48 Volt													X	B	24	SBX6341
US 3000 (R CHASSIS) US 3500 (R CHASSIS) US 4400 (R CHASSIS) 43.75 x 20.25 x 26.625 Atlet #71141 Compartment E NEW TRAY REQUIRED 48 Volt													X	B	24	SBX6341
US 3000 (X CHASSIS) US 3500 (X CHASSIS) US 4400 (X CHASSIS) 42.75 x 16.25 x 24.8125 Atlet #71147 Compartment C NEW TRAY REQUIRED 48 Volt													X	B	24	SBX6341
US 3000 (X CHASSIS) US 3500 (X CHASSIS) US 4400 (X CHASSIS) 42.75 x 20.25 x 24.8125 Atlet #71147 Compartment E NEW TRAY REQUIRED 48 Volt													X	B	24	SBX6341

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
				KWH	Ah			Length X	Width Y	Height Z		Yes	No			
UCR 2200, UCT 2200 47.5 x 19.4375 x 27.25 Atlet #77585 See Note A	48	24-D85-15	SP	27.70	595	85	7291	47.5	19.375	25.4375	2429		X	B	24	SBX6341
	48	24-H80-15	SP	26.07	560	80	7291	47.5	19.375	25.4375	2332		X	B	24	SBX6341
	48	24-P95-15	SP	30.96	665	95	7291	47.5	19.375	25.4375	2453		X	B	24	SBX6341
XJN 2200, XJN 2650, XLL XML JUNIOR XTF 2200 JUNIOR 37.8125 x 8.75 x 26 Atlet #84764	24	12-D85-9	sp	7.92	340	85	3246	37.6875	8.625	22.625	775		X	B	24	SBX6370
	24	12-H80-9	sp	7.45	320	80	3246	37.6875	8.625	22.625	744		X	B	24	SBX6370
	24	12-P95-9	sp	8.85	380	95	3246	37.6875	8.625	22.625	783		X	B	24	SBX6370
XSN, XML SENIOR XTF 2200 SENIOR 37.8125 x 12.8125 x 26 Atlet #84770 XLL SENIOR 37.8125 x 12.875 x 26	24	12-D85-13	sp	11.87	510	85	3277	37.6875	12.75	22.625	1125		X	B	24	SBX6370
	24	12-H80-13	sp	11.17	480	80	3277	37.6875	12.75	22.625	1080		X	B	24	SBX6370
	24	12-P95-13	sp	13.27	570	95	3277	37.6875	12.75	22.625	1136		X	B	24	SBX6370
	24	12-D85-15	sp	13.85	595	85	3313	37.6875	12.875	22.625	1211		X	B	24	SBX6370
	24	12-H80-15	sp	13.04	560	80	3313	37.6875	12.875	22.625	1163		X	B	24	SBX6370
UNS MODEL E 48 x 13.8125 x 30.9375 Atlet #72644 See Note A	48	24-D125-9		23.28	500	125	7394	47.5625	12.875	30.5625	2078		X	B	18	SBE6341
	48	24-H120-9		22.35	480	120	7394	47.5625	12.875	30.5625	2057		X	B	18	SBE6341
	48	24-P140-9		26.07	560	140	7394	47.5625	12.875	30.5625	2099		X	B	18	SBE6341
UNS MODEL F 48 x 16.75 x 30.9375 Atlet #72645 See Note A	48	24-D125-11		29.10	625	125	7512	47.5625	16.3125	30.5625	2579		X	B	18	SBE6341
	48	24-H120-11		27.94	600	120	7512	47.5625	16.3125	30.5625	2553		X	B	18	SBE6341
	48	24-P140-11		32.59	700	140	7512	47.5625	16.3125	30.5625	2605		X	B	18	SBE6341
UNS MODEL G, URF, UTF 48 x 19.5 x 30.9375 Atlet #72646 See Note A	48	24-D125-15	SP	40.74	875	125	7407	48	19.5	30.875	3321		X	B	18	SBE6341
	48	24-H120-15	SP	39.11	840	120	7407	48	19.5	30.875	3288		X	B	18	SBE6341
	48	24-P140-15	SP	45.63	980	140	7407	48	19.5	30.875	3354		X	B	18	SBE6341
LL (A CHASSIS) LPL (A CHASSIS) LPV (A CHASSIS) 15.75 x 6.75 x 22.8125 Atlet #75042 See Note A	12	6-D85-5		1.98	170	85	1282	12.5	6.5	22.5625	201		X	B	24	SBX6370
	12	6-H80-5		1.86	160	80	1282	12.5	6.5	22.5625	193		X	B	24	SBX6370
	12	6-P95-5		2.21	190	95	1282	12.5	6.5	22.5625	203		X	B	24	SBX6370

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
LS 2200, LL (B CHASSIS)	12	6-D85-7	2.97	255	85	1197	18.75	6.4375	22.5625	292		X	B	24	SBX6370
LPL (B CHASSIS)	12	6-H80-7	2.79	240	80	1197	18.75	6.4375	22.5625	280		X	B	24	SBX6370
LPV (B CHASSIS), LS 3000 18.75 x 6.75 x 22.8125 Atlet #75847 See Note A	12	6-P95-7	3.32	285	95	1197	18.75	6.4375	22.5625	295		X	B	24	SBX6370
TLP	24	12-D85-7	5.94	255	85	3555	27.875	9.6875	25.3125	643		X	A-Rear	18	SB6325
27.875 x 9.75 x 23.4375	24	12-H80-7	5.59	240	80	3555	27.875	9.6875	25.3125	617		X	A-Rear	18	SB6325
Atlet #78224 See Note A	24	12-P95-7	6.63	285	95	3555	27.875	9.6875	25.3125	649		X	A-Rear	18	SB6325
TPD 200	24	12-D85-9	7.92	340	85	3703	30.1875	11.625	24.6875	756		X	Mounted	0	EBC160
30.1875 x 11.6875 x 24.6875	24	12-H80-9	7.45	320	80	3703	30.1875	11.625	24.6875	726		X	Mounted	0	EBC160
Atlet #100688 See Note A	24	12-P95-9	8.85	380	95	3703	30.1875	11.625	24.6875	764		X	Mounted	0	EBC160
OPM100	24	12-D85-13	11.87	510	85	3809	36.25	15	25.6875	1164		X	Mounted	0	SBE6378
36.3125 x 15 x 25.6875	24	12-H80-13	11.17	480	80	3809	36.25	15	25.6875	1117		X	Mounted	0	SBE6378
Atlet #103194 See Note A	24	12-P95-13	13.27	570	95	3809	36.25	15	25.6875	1176		X	Mounted	0	SBE6378
UFS200 MODEL C	48	24-D125-7	17.46	375	125	7677	48	11	30.5	1710		X	A	12	SBE6341
48 x 11 x 30.9375	48	24-H120-7	16.76	360	120	7677	48	11	30.5	1693		X	A	12	SBE6341
Atlet #111710 See Note A	48	24-P140-7	19.56	420	140	7677	48	11	30.5	1727		X	A	12	SBE6341
UFS200 MODEL E	48	24-D125-9	23.28	500	125	7288	48.125	13.8125	30.5625	2116		X	A	9	SBE6341
48.125 x 13.8125 x 30.9375	48	24-H120-9	22.35	480	120	7288	48.125	13.8125	30.5625	2095		X	A	9	SBE6341
Atlet #111711 See Note A	48	24-P140-9	26.07	560	140	7288	48.125	13.8125	30.5625	2137		X	A	9	SBE6341
UFS200 MODEL F	48	24-D125-11	29.10	625	125	7512	47.5625	16.3125	30.5625	2579		X	A	12	SBE6341
48 x 16.75 x 30.9375	48	24-H120-11	27.94	600	120	7512	47.5625	16.3125	30.5625	2553		X	A	12	SBE6341
Atlet #111712 See Note A	48	24-P140-11	32.59	700	140	7512	47.5625	16.3125	30.5625	2605		X	A	12	SBE6341
APS 2200	24	12-D125-13	17.46	750	125	3412	35	13	31.9375	1497		X	B	24	SBE6378
35 x 13 x 31.9375	24	12-H120-13	16.76	720	120	3412	35	13	31.9375	1482		X	B	24	SBE6378
Atlet #58636B See Note A	24	12-P140-13	19.56	840	140	3412	35	13	31.9375	1512		X	B	24	SBE6378

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating KWH Ah		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector	
								Length X	Width Y	Height Z		Yes	No				
URF 2200 (H CHASSIS) URF 2650 (H CHASSIS) URF 3300 (H CHASSIS) 21.1875 x 16.3125 x 26.1875 Atlet #79270 / 79271 See Note A NEW TRAY REQUIRED 48 Volt													X		B	18	SBE6341
XLL 200 39.375 x 12.375 x 29.5625 Atlet #104409 See Note A	24	12-D100-11	SP	11.64	500	100	3814	39.375	12.375	30.5	1245		X		B	18	EBC160
PPD TEMPO 30.0625 x 12.8125 x 26.1875 Atlet #117315 See Note A	24	12-D100-11		11.64	500	100	3793	30.0625	12.9375	26.125	1058		X		Mounted	0	EBC320
URF Atlet #79647 See Note A 28.5 x 20.625 x 26.3125 SET INCLUDES: IST3880 (LEFT) & IST3881 (RIGHT) FOR 48 Volt & 18.62 KWH total	24 24	12-D100-9 12-D100-9		9.31 9.31	400 400	100 100	3881 3880	28.375 24.5	20.625 20.1875	26.1875 26.1875	999 937		X X		B B	18 18	SBX6370 SBX6370
UHS 200 48 x 19.5 x 30.9375 Atlet #111713 See Note A	48 48 48	24-D125-15 24-H120-15 24-P140-15	sp sp sp	40.74 39.11 45.63	875 840 980	125 120 140	7720 7720 7720	48 48 48	19.5 19.5 19.5	30.9375 30.9375 30.9375	3344 3311 3377		X X X		B B B	18 18 18	SBE6341 SBE6341 SBE6341
USS MODEL F 40.625 x 20.9375 x 30.9375 Atlet #110340 See Note A NEW TRAY REQUIRED 48 Volt													X		D	18	SBE6341

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

sp - Special tray design per Atlet drawing.

NEW TRAY REQUIRED - Contact East Penn factory.

SP - Special tray IST7226 per Atlet drawing overall height includes bottom rails.

SP - Special tray IST7429 per Atlet drawing includes steel plates added for minimum weight requirement.

Note A - Field verification required of connector type, position, & lead lengths according to customer application.

SP - Special tray IST7291 per Atlet drawing overall height includes fork pocket channels welded to tray bottom and special lift lug design.

SP - Special tray IST7407 per Atlet drawing includes special lifting lug design.

SP - Special tray IST3555 per Atlet drawing overall height includes bottom rails and special lifting lug design.

SP - Special tray IST3814 per Atlet drawing overall height includes raised rear side.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.