



INDUSTRIAL BATTERIES

BARRETT

WALKIE, RIDER/WALKIE, TOW TRACTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
PG60, PG80, PGK60, PGK80	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	20	SB6325
STG40, STG60, WC20	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	20	SB6325
WC30, WC40, WP40, WP60	12	6-D85-13	5.94	510	85	1002	31.1875	7.75	23.1875	540	X		B	20	SB6325
WP80, WRP40, WRP60	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	20	SB6325
WRP80, WS30, WS40, WTT	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	20	SB6325
32 x 8 x Open	12	6-H80-13	5.59	480	80	1002	31.1875	7.75	23.1875	518	X		B	20	SB6325
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	20	SB6325
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	20	SB6325
	12	6-P95-13	6.63	570	95	1002	31.1875	7.75	23.1875	545	X		B	20	SB6325
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	20	SB6325
WC20, WC30, WC40, WP40 WP60, WP80, WRP40 WRP60, WRP80, WS30 WS40, WTT 32 x 13.5 x Open	12	6-D160-15	13.04	1120	160	1199	26.5625	11.875	31.125	1192	X		B	20	SB6325
TTG10, TTG15, TTG20	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	20	SB6325
TTG25, TTG30, TTG40	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	20	SB6325
31.25 x 8.125 x Open	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	20	SB6325
	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	20	SB6325
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	20	SB6325
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	20	SB6325
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	20	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating KWH	Ah	Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector	
							Length X	Width Y	Height Z		Yes	No				
WC20, WC30, WC40, WP40 WP60, WP80, WS30, WS40 32 x 8 x Open	24	12-D100-5	cm	4.66	200	100	3757	29.375	6.4375	26.1875	513	X		B	24	SB6325
	24	12-D100-5		4.66	200	100	3209	24.625	6.4375	26.1875	474	X		B	20	SB6325
	24	12-D125-5		5.82	250	125	3085	24.5625	6.5	31.0625	580	X		B	20	SB6325
	24	12-P140-5		6.52	280	140	3085	24.5625	6.5	31.0625	586	X		B	20	SB6325
EWP40 29 x 8.75 x 26.5	24	12-D100-5	cm	4.66	200	100	3526	24.25	8.3125	26.1875	514	X		B	24	SB6325
	24	12-D100-7		6.98	300	100	3523	29	8.5625	26.1875	676	X		B	20	SB6325
	24	12-D100-7		6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	20	SB6325
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	20	SB6325
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	20	SB6325
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	20	SB6325
PG60, PG80, PGX60, PGX80 SGX-1 40, SGX-1 60 SGX-1 80, SGX-1-24 SGX-1-24-F, SGX-1-24D SGX-1-24D-F, WC30, WC40 WRP40, WRP60, WRP80 WTT 32 x 13 x Open	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	950	X		B	30	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	912	X		B	30	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	960	X		B	30	SB6325
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1193	X		B	20	SB6325
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1043	X		B	20	SB6325
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1001	X		B	20	SB6325
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6325
24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1053	X		B	20	SB6325	
DG, DG-24, DG-24-D 31.75 x 13.125 x 23.5	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	950	X		B	30	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	912	X		B	30	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	960	X		B	30	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1043	X		B	20	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1001	X		B	20	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1053	X		B	20	SB6325
SG, WSR-30 32.25 x 13.25 x Open	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6329
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1193	X		B	20	SB6329
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6329
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1043	X		B	20	SB6329
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6329
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1001	X		B	20	SB6329
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6329
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1053	X		B	20	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
EWS-20, EWS-25 27.375 x 9 x Open	24	12-D100-7	6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	15	SB6329
	24	12-D125-7	8.73	375	125	3329	25.3125	8.5625	31.0625	787	X		B	15	SB6329
	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	15	SB6329
	24	12-H120-7	8.38	360	120	3329	25.3125	8.5625	31.0625	779	X		B	15	SB6329
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	15	SB6329
	24	12-P140-7	9.78	420	140	3329	25.3125	8.5625	31.0625	795	X		B	15	SB6329
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	15	SB6329
SGB200, SGB60, SGB80 See Note A 31 x 13.5 x 31	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		B	20	SB6329
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1001	X		B	20	SB6329
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1053	X		B	20	SB6329
SGB200, SGB60, SGB80 32 x 13.5 x 31	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		B	20	SB6329
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1001	X		B	20	SB6329
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1053	X		B	20	SB6329
UNICAR 140L 32.75 x 13.5 x 25.6875	24	12-D85-13	11.87	510	85	3017	31.25	12.875	22.625	1039		X	B	26	SB6325
	24	12-H80-13	11.17	480	80	3017	31.25	12.875	22.625	997		X	B	26	SB6325
	24	12-P95-13	13.27	570	95	3017	31.25	12.875	22.625	1049		X	B	26	SB6325
UNICAR 140L 38 x 13.5 x 25.625 Optional Compartment	24	12-D85-13	11.87	510	85	3159	35.5625	11.5625	22.625	1034		X	B	26	SB6325
	24	12-H80-13	11.17	480	80	3159	35.5625	11.5625	22.625	993		X	B	26	SB6325
	24	12-P95-13	13.27	570	95	3159	35.5625	11.5625	22.625	1044		X	B	26	SB6325
	24	12-D85-15	13.85	595	85	3056	35.0625	12.875	22.625	1178		X	B	26	SB6325
	24	12-H80-15	13.04	560	80	3056	35.0625	12.875	22.625	1131		X	B	26	SB6325
	24	12-P95-15	15.48	665	95	3056	35.0625	12.875	22.625	1190		X	B	26	SB6325

cm - Charge-Mate includes on board charger.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Note A - Battery compartment dimensions allow for optional battery gate.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STANDUP RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
RET20, RET25, RET30, RST30	24	12-D100-11	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
RST40	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1193	X		B	25	SB6325
32 x 13 x Open	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	25	SB6325
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		B	25	SB6325
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	25	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1001	X		B	25	SB6325
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	25	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1053	X		B	25	SB6325
RRT-130, RRT-134, RRT-140	24	12-D160-11	18.62	800	160	3764	36.0625	14	30.5	1699		X	B	20	SB6322
RST-140, RST-150	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1948		X	B	20	SB6322
38.75 x 14.5 x 32	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1929		X	B	20	SB6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1967		X	B	20	SB6322
RRT-130, RRT-134	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1853		X	B	20	SB6320
RRT-140, RST-140	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1834		X	B	20	SB6320
RST-150	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1872		X	B	20	SB6320
38.75 x 14.5 x 32															
RRT-130, RRT-134, RRT-140	24	12-D160-13	22.35	960	160	3049	35.25	15.5625	30.5625	1985		X	B	20	SB6322
RST-140, RST-150	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1948		X	B	20	SB6322
38.75 x 16.5 x 32	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1929		X	B	20	SB6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1967		X	B	20	SB6322
RRT-130, RRT-134	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2169		X	B	20	SB6320
RRT-140, RST-140	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2147		X	B	20	SB6320
RST-150	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2191		X	B	20	SB6320
38.75 x 16.5 x 32															
RRT-140, RRT-40, RRT-DR	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2837		X	B	20	SB6320
38.75 x 21.25 x 32	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2809		X	B	20	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2865		X	B	20	SB6320
OSB25, OSB30S	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1853		X	D	12	SB6320
38.75 x 13.875 x 31.5	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1834		X	D	12	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1872		X	D	12	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STANDUP RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)	Standard Connector	
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
OSB30 38.75 x 16.125 x 31.5	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2169		X	D	12	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2147		X	D	12	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2191		X	D	12	SB6320
OSB35 38.75 x 18.375 x 31.5	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2488		X	D	12	SB6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2463		X	D	12	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2513		X	D	12	SB6320
OSB40, OSB45, OSB50 38.75 x 20.75 x 31.5	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2837		X	D	12	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2809		X	D	12	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2865		X	D	12	SB6320
ORB35, ORB40 38.75 x 13.875 x 32	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1948		X	B	14	SB6320
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1929		X	B	14	SB6320
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1967		X	B	14	SB6320
ORB35, ORB40 38.75 x 13.875 x 32	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1853		X	B	14	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1834		X	B	14	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1872		X	B	14	SB6320
ORB35, ORB40 Optional Compartment 38.75 x 16.125 x 32	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	B	20	SB6320
	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	B	20	SB6320
	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	B	20	SB6320
ORB35, ORB40 Optional Compartment 38.75 x 16.125 x 32	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2169		X	B	20	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2147		X	B	20	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2191		X	B	20	SB6320
ORB30, ORB40 38.75 x 18.5 x 32	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2488		X	B	20	SB6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2463		X	B	20	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2513		X	B	20	SB6320
ORB45, ORB30D Optional Compartment 38.75 x 21 x 32	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2837		X	B	20	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2809		X	B	20	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2865		X	B	20	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STANDUP RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)	Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No		
RR35, RR30D, RR45, RS40 RS50 38.75 x 16.375 x 32 Min. Battery Wt. - 2000 lbs.	24	12-D160-13 sp	22.35	960	160	3780	37.875	15.5625	30.5625	2113		X	C 15	SB6322
RR35 Optional Compartment 38.75 x 14.375 x 32	24	12-D160-11	18.62	800	160	3577	35.0625	13.1875	30.5	1693		X	C 15	SB6322
RR35 Optional Compartment 38.75 x 14.375 x 32	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1853		X	C 15	SB6322
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1834		X	C 15	SB6322
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1872		X	C 15	SB6322
RR30D, RR35, RR45, RS40 RS50 38.75 x 16.375 x 32	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2169		X	C 15	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2147		X	C 15	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2191		X	C 15	SB6320
RR45, RR30D Optional Compartment 38.75 x 20.875 x 32	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2837		X	C 15	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2809		X	C 15	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2865		X	C 15	SB6320
RR45, RR30D Optional Compartment 38.75 x 20.875 x 32	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2837		X	C 15	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2809		X	C 15	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2865		X	C 15	SB6320

sp - Special tray IST3780 includes steel plates added for minimum weight requirement.
H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

ORDER SELECTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)	Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No		
RC0S, RCOS3000 38.75 x 14.5 x 31.5	24	12-D160-11	18.62	800	160	3764	36.0625	14	30.5	1699		X	B 20	SB6322
	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	B 20	SB6322
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1948		X	B 20	SB6322
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1929		X	B 20	SB6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1967		X	B 20	SB6322

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

ORDER SELECTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
RCOS 30 32 x 13.375 x 31.125	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	25	SB6320
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	25	SB6320
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	25	SB6320
RCS01 38.75 x 14.5 x 31.5625	24	12-D160-11	18.62	800	160	3764	36.0625	14	30.5	1699		X	B	25	SB6320
	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	B	25	SB6320
	24	12-D125-15	20.37	875	125	3692	36.0625	14	30.5	1635		X	B	25	SB6320
	24	12-D125-15	20.37	875	125	3670	36.0625	14	30.5	1749		X	B	25	SB6320
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1646		X	B	25	SB6320
	24	12-H120-15	19.56	840	120	3692	36.0625	14	30.5	1619		X	B	25	SB6320
	24	12-H120-15	19.56	840	120	3670	36.0625	14	30.5	1732		X	B	25	SB6320
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1630		X	B	25	SB6320
	24	12-P140-15	22.81	980	140	3692	36.0625	14	30.5	1651		X	B	25	SB6320
	24	12-P140-15	22.81	980	140	3670	36.0625	14	30.5	1766		X	B	25	SB6320
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1662		X	B	25	SB6320
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1948		X	B	25	SB6320
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1929		X	B	25	SB6320
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1967		X	B	25	SB6320
GRCSS25, GRCSS30, RCSS25 RCSS30, RSSS 32.5 x 13.375 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1193	X		B	25	SB6325
	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	25	SB6325
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		B	25	SB6325
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	25	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1001	X		B	25	SB6325
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	25	SB6325
RCOS, RCOS3000 38.75 x 14.5 x 31.5	36	18-D125-11	21.83	625	125	6782	38.0625	13.5625	30.5625	1887		X	B	20	SB6320
	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1853		X	B	20	SB6320
	36	18-H120-11	20.95	600	120	6782	38.0625	13.5625	30.5625	1868		X	B	20	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1834		X	B	20	SB6320
	36	18-P140-11	24.44	700	140	6782	38.0625	13.5625	30.5625	1906		X	B	20	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1872		X	B	20	SB6320

Some older models require SB6316 with 12 volt tap.

sp - IST3692 tray includes ribbed sides.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotive@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.