



INDUSTRIAL BATTERIES

BIG JOE

ORDER PICKER

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
J1 JOEY 26.375 x 8.0625 x Open	24	12-D85-5	3.96	170	85	3996	25.5	7.5	23.1875	466	X		A	11	SB6325
	24	12-H80-5	3.72	160	80	3996	25.5	7.5	23.1875	447	X		A	11	SB6325
	24	12-P95-5	4.42	190	95	3996	25.5	7.5	23.1875	471	X		A	11	SB6325

SIT DOWN RIDER

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
V-15 Battery Wt. Min = 1520 lbs 32 x 19 x 24	48	24-D85-9	15.83	340	85	7975	31.5	18.5	22.625	1520		X	A	22	SB6321
	48	24-H80-9	14.90	320	80	7975	31.5	18.5	22.625	1459	X		A	22	SB6321
	48	24-P95-9	17.69	380	95	7975	31.5	18.5	22.625	1535	X		A	22	SB6321
V-18 Battery Wt. Min = 1760 lbs 32 x 23 x 24	48	24-D85-11	19.79	425	85	7444	31.5	22.3125	22.625	1821		X	A	22	SB6321
	48	24-H80-11	18.62	400	80	7444	31.5	22.3125	22.625	1748	X		A	22	SB6321
	48	24-P95-11	22.12	475	95	7444	31.5	22.3125	22.625	1839	X		A	22	SB6321

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 419/440 31.5 x 6.875 x Open BIG JOE # 003108 WET BIG JOE # 003129 DRY	12	6-D75-11	4.36	375	75	1049	25.9375	6.4375	23.1875	433	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt Min/Max = 457/469 31.5 x 6.875 x Open BIG JOE # 003159 WET BIG JOE # 003160 DRY	12	6-D75-11	4.36 os	375	75	1006	30.5625	6.4375	23.1875	469	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 451/463 31.5 x 6.875 x Open BIG JOE # 003153 WET	12	6-D85-11	4.95	425	85	1049	25.9375	6.4375	23.1875	451	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt Min/Max = 500/521 31.5 x 13.25 x Open BIG JOE # 003109 WET BIG JOE # 003130 DRY	12	6-D75-13	5.23	450	75	1006	30.5625	6.4375	23.1875	509	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt Min/Max = 525/544 31.5 x 13.25 x Open BIG JOE # 003124 WET BIG JOE # 003131 DRY	12	6-D85-13	5.94	510	85	1006	30.5625	6.4375	23.1875	531	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt Min/Max = 515/535 31.5 x 6.875 x Open BIG JOE # 003154 WET	12	6-D100-11	5.82	500	100	1054	26.25	6.5	26.1875	515	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt Min/Max = 610/622 31.5 x 6.875 x Open BIG JOE # 003144 WET	12	6-D100-13	6.98	600	100	1022	30.5625	6.4375	26.1875	610	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WTR-60 Battery Wt Min/Max = 710/745 31.5 x 6.875 x Open BIG JOE # 003145 WET	12	6-D110-13	7.68	660	110	1050	30.5625	6.4375	31.0625	710	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt Min/Max = 460/473 31.5 x 6.875 x Open BIG JOE # 003178-01 WET BIG JOE # 003178-02 DRY	12	6-D75-11 EE	4.36 ^{os}	375	75	1181	30.5625	6.4375	23.4375	461	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 6.875 x Open BIG JOE # 003177-01 WET BIG JOE # 003177-02 DRY	12	6-D75-13 EE	5.23	450	75	1181	30.5625	6.4375	23.4375	501	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 6.875 x Open BIG JOE # 003176-01 WET BIG JOE # 003176-02 DRY	12	6-D85-11 EE	4.95	425	85	1181	30.5625	6.4375	23.4375	528	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 6.875 x Open BIG JOE # 003183-01 WET BIG JOE # 003183-02 DRY	12	6-D110-13 EE	7.68	660	110	1182	30.5625	6.4375	31.125	714	X		A	15	SB6325
CB22, PDS-25, PDS-30 WPT-45 26.375 x 9.0625 x Open	24 24 24	12-D85-7 12-H80-7 12-P95-7	5.94 5.59 6.63	255 240 285	85 80 95	3042 3042 3042	25.25 25.25 25.25	8.5625 8.5625 8.5625	23.1875 23.1875 23.1875	567 544 573	X X X		A A A	11 11 11	SB6325 SB6325 SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector	
			KWH	Ah			Length X	Width Y	Height Z		Yes	No				
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 396/419 31.5 x 6.9375 x Open BIG JOE # 003150 WET	24	12-D75-5	3.49	150	75	3081	24.625	6.4375	23.1875	404	X		A	15	SB6325	
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 403/437 31.5 x 6.9375 x Open BIG JOE # 003151 WET	24	12-D85-5	3.96	170	85	3081	24.625	6.4375	23.1875	415	X		A	15	SB6325	
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 560/590 31.5 x 6.9375 x Open BIG JOE # 003152 WET	24	12-D110-5	5.12	220	110	3085	24.5625	6.5	31.0625	560	X		A	15	SB6325	
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 6.9375 x Open BIG JOE # 003179-01 WET BIG JOE # 003179-02 DRY	24	12-D110-5	EE	5.12	220	110	3345	25.5	6.6875	31.0625	565	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 465/495 31.5 x 6.9375 x Open BIG JOE # 003209 WET BIG JOE # 003210 DRY	24	12-D100-5		4.66	200	100	3209	24.625	6.4375	26.1875	474	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 775/790 31.5 x 13.25 x Open BIG JOE # 003172-01 WET	12	6-D85-19	EE	8.90	765	85	1111	22.1875	12.875	23.5	785	X		B	15	YC7204

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 13.25 x Open BIG JOE # 003184-01 WET BIG JOE # 003184-02 DRY	12	6-D85-19	8.90	765	85	1007	22.1875	12.875	23.25	781	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 13.25 x Open BIG JOE # 003187-01 WET BIG JOE # 003187-02 DRY	12	6-D85-19 EE	8.90	765	85	1183	22.1875	12.875	23.5	785	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max =1020/1050 31.5 x 13.25 x Open BIG JOE # 003134 WET BIG JOE # 003165 DRY	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 885/907 31.5 x 13.25 x Open BIG JOE # 003141 WET	24	12-D85-11	9.89	425	85	3020	26.0625	12.75	23.25	885	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max =1177/1216 31.5 x 13.25 x Open BIG JOE # 003157 WET	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1193	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max =1390/1450 31.5 x 13.25 x Open BIG JOE # 003158 WET	24	12-D110-13	15.36	660	110	3008	30.5625	12.75	31.125	1441	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 796/816 31.5 x 13.25 x Open BIG JOE # 003161 WET	24	12-D85-9 pk	7.91	os 340	85	3019	30.5625	12.75	23.25	800	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 760/780 31.5 x 13.25 x Open BIG JOE # 003166 WET	24	12-D75-9 pk	6.98	os 300	75	3019	30.5625	12.75	23.25	770	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max =1042/1055 31.5 x 13.25 x Open BIG JOE # 003173-01 WET BIG JOE # 003173-02 DRY	24	12-D85-13 EE	11.87	510	85	3325	30.5625	12.75	23.25	1054	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 13.25 x Open BIG JOE # 003180-01 WET BIG JOE # 003180-02 DRY	24	12-D85-11 EE	9.89	425	85	3368	26.0625	12.75	23.25	917	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 13.25 x Open BIG JOE # 003185-01 WET BIG JOE # 003185-02 DRY	24	12-D75-13	110.47	450	75	3019	30.5625	12.75	23.25	999	X		A	15	SB6325
WPT-40, WPT-60, WRT-40 WRT-60 31.5 x 13.25 x Open BIG JOE # 003186-01 WET BIG JOE # 003186-02 DRY	24	12-D75-13 EE	10.47	450	75	3325	30.5625	12.75	23.25	1004	X		A	15	EC5810

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
				KWH	Ah			Length X	Width Y	Height Z		Yes	No			
WPT-40, WPT-60, WRT-40 WRT-60 Battery Wt. Min/Max = 940/970 31.5 x 13.25 x Open BIG JOE # 003212 WET	24	12-D85-11	CM	9.89	425	85	3163	31.375	12.875	23.25	950	X		A	15	SB6325
PPT-40 Battery Wt. Min/Max = 419/440 27 x 7.25 x 25.8125 BIG JOE # 003108 WET BIG JOE # 003129 DRY	12	6-D75-11		4.36	375	75	1049	25.9375	6.4375	23.1875	429	X		A	15	SB6325
PPT-40 Battery Wt. Min/Max = 451/463 27 x 7.25 x 25.8125 BIG JOE # 003153 WET	12	6-D85-11		4.95	425	85	1049	25.9375	6.4375	23.1875	451	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 419/440 30.8125 x 6.6875 x Open BIG JOE # 003108 WET BIG JOE # 003129 DRY	12	6-D75-11		4.36	375	75	1049	25.9375	6.4375	23.1875	429	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 457/469 30.8125 x 6.6875 x Open BIG JOE # 003159 WET BIG JOE # 003160 DRY	12	6-D75-11		4.36	375	75	1006	30.5625	6.4375	23.1875	457	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 451/463 30.8125 x 6.6875 x Open BIG JOE # 003153 WET	12	6-D85-11		4.95	425	85	1049	25.9375	6.4375	23.1875	451	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 515/535 30.8125 x 6.6875 x Open BIG JOE # 003154 WET	12	6-D100-11		5.82	500	100	1054	26.25	6.5	26.1875	515	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector	
			KWH	Ah			Length X	Width Y	Height Z		Yes	No				
PDC-15A, PDC-20A Battery Wt. Min/Max = 500/521 30.8125 x 6.6875 x Open BIG JOE # 003109 WET BIG JOE # 003130 DRY	12	6-D75-13	5.24	450	75	1006	30.5625	6.4375	23.1875	507	X		A	15	SB6325	
PDC-15A, PDC-20A Battery Wt. Min/Max = 525/544 30.8125 x 6.6875 x Open BIG JOE # 003124 WET BIG JOE # 003131 DRY	12	6-D85-13	5.94	510	85	1006	30.5625	6.4375	23.1875	531	X		A	15	SB6325	
PDC-15A, PDC-20A Battery Wt. Min/Max = 610/622 30.8125 x 6.6875 x Open BIG JOE # 003144 WET	12	6-D100-13	6.98	600	100	1022	30.5625	6.4375	26.1875	610	X		A	15	SB6325	
PDC-15A, PDC-20A Battery Wt. Min/Max = 710/745 30.8125 x 6.6875 x Open BIG JOE # 003145 WET	12	6-D110-13	7.68	660	110	1050	30.5625	6.4375	31.0625	730	X		A	15	SB6325	
PDC-15A, PDC-20A 30.8125 x 6.6875 x Open BIG JOE # 003176-01 WET BIG JOE # 003176-02 DRY	12	6-D85-11	EE	4.95	425	85	1181	30.5625	6.4375	23.4375	528	X		A	15	SB6325
PDC-15A, PDC-20A 30.8125 x 6.6875 x Open BIG JOE # 003177-01 WET BIG JOE # 003177-02 DRY	12	6-D75-13	EE	5.24	450	75	1181	30.5625	6.4375	23.4375	504	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 460/473 30.8125 x 6.6875 x Open BIG JOE # 003178-01 WET BIG JOE # 003178-02 DRY	12	6-D75-11	EE	4.95	os 425	85	1181	30.5625	6.4375	23.4375	460	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating KWH Ah		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
								Length X	Width Y	Height Z		Yes	No			
PDC-15A, PDC-20A 30.8125 x 6.6875 x Open BIG JOE # 003183-01 WET BIG JOE # 003183-02 DRY	12	6-D110-13	EE	7.68	660	110	1182	30.5625	6.4375	31.125	734	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 396/419 30.8125 x 6.6875 x Open BIG JOE # 003150 WET	24	12-D75-5		3.49	150	75	3081	24.625	6.4375	23.1875	404	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 403/437 30.8125 x 6.6875 x Open BIG JOE # 003151 WET	24	12-D85-5		3.96	170	85	3081	24.625	6.4375	23.1875	415	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 560/590 30.8125 x 6.6875 x Open BIG JOE # 003152 WET	24	12-D110-5		2.79	220	110	3085	24.5625	6.5	31.0625	560	X		A	15	SB6325
PDC-15A, PDC-20A 30.8125 x 6.6875 x Open BIG JOE # 003179-01 WET BIG JOE # 003179-02 DRY	24	12-D110-5	EE	2.79	220	110	3345	25.5	6.6875	31.0625	565	X		A	15	SB6325
PDC-15A, PDC-20A Battery Wt. Min/Max = 465/495 30.8125 x 6.6875 x Open BIG JOE # 003209 WET BIG JOE # 003210 DRY	24	12-D100-5		4.66	200	100	3209	24.625	6.4375	26.1875	474	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 Min Wt. Min/Max = 775/790 31.4375 x 13.125 x Open BIG JOE # 003172-01 WET	12	6-D85-19	EE	8.90	765	85	1111	22.1875	12.875	23.5	785	X		B	15	YC7204
PDC-20, PDC-25, PDC-30 31.4375 x 13.125 x Open BIG JOE # 003184-01 WET BIG JOE # 003184-02 DRY	12	6-D85-19		8.90	765	85	1007	22.1875	12.875	23.25	781	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating KWH Ah		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
								Length X	Width Y	Height Z		Yes	No			
PDC-20, PDC-25, PDC-30 31.4375 x 13.125 x Open BIG JOE # 003187-01 WET BIG JOE # 003187-02 DRY	12	6-D85-19	EE	8.90	765	85	1183	22.1875	12.875	23.5	785	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max = 1020/1050 31.4375 x 13.125 x Open BIG JOE # 003134 WET BIG JOE # 003165 DRY	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1043	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max = 885/907 31.4375 x 13.125 x Open BIG JOE # 003141 WET	24	12-D85-11		9.89	425	85	3020	26.0625	12.75	23.25	885	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max = 1177/1216 31.4375 x 13.125 x Open BIG JOE # 003157 WET	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1193	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max = 1390/1450 31.4375 x 13.125 x Open BIG JOE # 003158 WET	24	12-D110-13		15.36	660	110	3008	30.5625	12.75	31.125	1415	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max = 796/816 31.4375 x 13.125 x Open BIG JOE # 003161 WET	24	12-D85-9	pk	7.91 os	340	85	3019	30.5625	12.75	23.25	800	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max = 760/780 31.4375 x 13.125 x Open BIG JOE # 003166 WET	24	12-D75-9	pk	6.98 os	300	75	3019	30.5625	12.75	23.25	770	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating KWH Ah		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
								Length X	Width Y	Height Z		Yes	No			
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max =1042/1055 31.4375 x 13.125 x Open BIG JOE # 003173-01 WET BIG JOE # 003173-02 DRY	24	12-D85-13	EE	11.87	510	85	3325	30.5625	12.75	23.25	1054	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 31.4375 x 13.125 x Open BIG JOE # 003180-01 WET BIG JOE # 003180-02 DRY	24	12-D85-11	EE	9.89	425	85	3368	26.0625	12.75	23.25	917	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 31.4375 x 13.125 x Open BIG JOE # 003185-01 WET BIG JOE # 003185-02 DRY	24	12-D75-13		10.47	450	75	3019	30.5625	12.75	23.25	999	X		A	15	SB6325
PDC-20, PDC-25, PDC-30 31.4375 x 13.125 x Open BIG JOE # 003186-01 WET BIG JOE# 003186-02 DRY	24	12-D75-13	EE	10.48	450	75	3325	30.5625	12.75	23.25	1004	X		A	15	EC5810
PDC-20, PDC-25, PDC-30 Battery Wt. Min/Max = 940/970 31.4375 x 13.125 x Open BIG JOE # 003212 WET	24	12-D85-11	CM	9.89	425	85	3163	31.375	12.875	23.25	950	X		A	15	SB6325
PDC-25, PDC-30, PDC-40 31.375 x 11.0625 x Open	24	12-D85-9		7.92	340	85	3558	31	10.0625	23.25	768	X		A	15	SB6325
	24	12-H80-9		7.45	320	80	3558	31	10.0625	23.25	737	X		A	15	SB6325
	24	12-P95-9		8.85	380	95	3558	31	10.0625	23.25	776	X		A	15	SB6325
PDC-30, PDC-40 30.875 x 13.1875 x Open	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1043	X		A	15	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1001	X		A	15	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1053	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 419/440 30.875 x 6.6875 x Open BIG JOE # 003108 WET BIG JOE # 003129 DRY	12	6-D75-11	4.36	375	75	1049	25.9375	6.4375	23.1875	429	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 500/521 30.875 x 6.6875 x Open BIG JOE # 003109 WET BIG JOE # 003130 DRY	12	6-D75-13	5.24	450	75	1006	30.5625	6.4375	23.1875	507	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 525/544 30.875 x 6.6875 x Open BIG JOE # 003124 WET BIG JOE # 003131 DRY	12	6-D85-13	5.94	510	85	1006	30.5625	6.4375	23.1875	531	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 610/622 30.875 x 6.6875 x Open BIG JOE # 003144 WET	12	6-D100-13	6.98	600	100	1022	30.5625	6.4375	26.1875	610	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 710/745 30.875 x 6.6875 x Open BIG JOE # 003145 WET	12	6-D110-13	7.68	660	110	1050	30.5625	6.4375	31.0625	730	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector	
			KWH	Ah			Length X	Width Y	Height Z		Yes	No				
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 451/463 30.875 x 6.6875 x Open BIG JOE # 003153 WET	12	6-D85-11	4.95	425	85	1049	25.9375	6.4375	23.1875	451	X		A	15	SB6325	
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 515/535 30.875 x 6.6875 x Open BIG JOE # 003154 WET	12	6-D100-11	5.82	500	100	1054	26.25	6.5	26.1875	515	X		A	15	SB6325	
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 457/469 30.875 x 6.6875 x Open BIG JOE # 003159 WET BIG JOE # 003160 DRY	12	6-D75-11	4.36	375	75	1006	30.5625	6.4375	23.1875	457	X		A	15	SB6325	
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 6.6875 x Open BIG JOE # 003176-01 WET BIG JOE # 003176-02 DRY	12	6-D85-11	EE	4.95	425	85	1181	30.5625	6.4375	23.4375	528	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 6.6875 x Open BIG JOE # 003177-01 WET BIG JOE # 003177-02 DRY	12	6-D75-13	EE	5.24	450	75	1181	30.5625	6.4375	23.4375	504	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating KWH Ah		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
								Length X	Width Y	Height Z		Yes	No			
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 6.6875 x Open BIG JOE # 003178-01 WET BIG JOE # 003178-02 DRY	12	6-D85-11	EE	4.95	os 425	85	1181	30.5625	6.4375	23.4375	435	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 6.6875 x Open BIG JOE # 003183-01 WET BIG JOE # 003183-02 DRY	12	6-D110-13	EE	7.68	660	110	1182	30.5625	6.4375	31.125	724	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 396/419 30.875 x 6.6875 x Open BIG JOE # 003150 WET	24	12-D75-5		3.94	150	75	3081	24.625	6.4375	23.1875	404	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 403/437 30.875 x 6.6875 x Open BIG JOE # 003151 WET	24	12-D85-5		3.96	170	85	3081	24.625	6.4375	23.1875	415	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 560/590 30.875 x 6.6875 x Open BIG JOE # 003152 WET	24	12-D110-5		5.12	220	110	3085	24.5625	6.5	31.0625	560	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating KWH Ah		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
								Length X	Width Y	Height Z		Yes	No			
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 6.6875 x Open BIG JOE # 003179-01 WET BIG JOE # 003179-02 DRY	24	12-D110-5	EE	5.12	220	110	3345	25.5	6.6875	31.0625	565	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 669/695 31.625 x 11.125 x Open BIG JOE # 003139 WET BIG JOE # 908032 DRY	24	12-D75-9		6.98	300	75	3033	25.3125	10.8125	23.1875	669	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 700/730 31.625 x 11.125 x Open BIG JOE # 003140 WET	24	12-D85-9		7.92	340	85	3033	25.3125	10.8125	23.1875	700	X		A	15	SB6325
PDH-20 Battery Wt. Min/Max = 690/730 PDH-25, PDH-30, PDH-40 PDP-40, PDR-20, PDR-30 31.625 x 11.125 x Open BIG JOE # 003174-01 WET BIG JOE # 003174-02 DRY	24	12-D85-9	EE	7.92	340	85	3326	25.1875	10.8125	23.1875	717	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 31.625 x 11.125 x Open BIG JOE # 003175-01 WET BIG JOE # 003175-02 DRY	24	12-D75-9	EE	6.98	300	75	3326	25.1875	10.8125	23.1875	682	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 13.125 x Open BIG JOE # 003184-01 WET BIG JOE # 003184-02 DRY	12	6-D85-19	8.90	765	85	1007	22.1875	12.875	23.25	781	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 13.125 x Open BIG JOE # 003187-01 WET BIG JOE # 003187-02 DRY	12	6-D85-19 EE	8.90	765	85	1183	22.1875	12.875	23.5	785	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max= 1020/1050 30.875 x 13.125 x Open BIG JOE # 003134 WET BIG JOE # 003165 DRY	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 30.875 x 13.125 x Open BIG JOE # 003185-01 WET BIG JOE # 003185-02 DRY	24	12-D75-13	10.47	450	75	3019	30.5625	12.75	23.25	999	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 885/907 30.875 x 13.125 x Open BIG JOE # 003141 WET	24	12-D85-11	9.89	425	85	3020	26.0625	12.75	23.25	885	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max= 1177/1216 30.875 x 13.125 x Open BIG JOE # 003157 WET	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1193	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max= 1390/1450 30.875 x 13.125 x Open BIG JOE # 003158 WET	24	12-D110-13	15.36	660	110	3008	30.5625	12.75	31.125	1415	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 796/816 30.875 x 13.125 x Open BIG JOE # 003161 WET	24	12-D85-9 pk	7.91 os	340	85	3019	30.5625	12.75	23.25	800	X		A	15	SB6325
PDH-20, PDH-25, PDH-30 PDH-40, PDP-40, PDR-20 PDR-30 Battery Wt. Min/Max = 760/780 30.875 x 13.125 x Open BIG JOE # 003166 WET	24	12-D75-9 pk	6.98 os	300	75	3019	30.5625	12.75	23.25	770	X		A	15	SB6325
PDS-40 Battery Wt. Min = 1090 lbs 31.5625 x 13.0625 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1193	X		A	11	SB6325
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		A	11	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1001	X		A	11	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1053	X		A	11	SB6325
SSC-20 Battery Wt. Min/Max = 525/544 31.625 x 6.875 x 23.25 BIG JOE # 003124 WET BIG JOE # 003131 DRY	12	6-D85-13	5.94	510	85	1006	30.5625	6.4375	23.1875	531	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
SSC-20 Battery Wt. Min/Max = 500/521 31.625 x 6.875 x 23.25 BIG JOE # 003109 WET BIG JOE # 003130 DRY	12	6-D75-13	5.23	450	75	1006	30.5625	6.4375	23.1875	509	X		A	15	SB6325
SSC-20 Battery Wt. Min/Max = 451/463 31.625 x 6.875 x 23.25 BIG JOE # 003153 WET	12	6-D85-11	4.95	425	85	1049	25.9375	6.4375	23.1875	451	X		A	15	SB6325
SSC-20 Battery Wt. Min/Max = 419/440 31.625 x 6.875 x 23.25 BIG JOE # 003108 WET BIG JOE # 003129 DRY	12	6-D75-11	4.36	375	75	1049	25.9375	6.4375	23.1875	433	X		A	15	SB6325
SSC-20 Battery Wt Min/Max = 457/469 31.625 x 6.875 x Open BIG JOE # 003159 WET BIG JOE # 003160 DRY	12	6-D75-11	4.36 os	375	75	1006	30.5625	6.4375	23.1875	469	X		A	15	SB6325
SSC-20 Battery Wt Min/Max = 515/535 31.625 x 6.875 x Open BIG JOE # 003154 WET	12	6-D100-11	5.82	500	100	1054	26.25	6.5	26.1875	515	X		A	15	SB6325
SSC-20 Battery Wt. Min/Max = 610/622 31.625 x 6.875 x Open BIG JOE # 003144 WET	12	6-D100-13	6.98	600	100	1022	30.5625	6.4375	26.1875	610	X		A	15	SB6325
SSC-20 Battery Wt. Min/Max = 710/745 31.625 x 6.875 x Open BIG JOE # 003145 WET	12	6-D110-13	7.68	660	110	1050	30.5625	6.4375	31.0625	730	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	6 Hr. Rating		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
			KWH	Ah			Length X	Width Y	Height Z		Yes	No			
SSC-20 Battery Wt Min/Max=1020/1050 SSC-30 36 x 13.1875 x Open BIG JOE # 003134 WET BIG JOE # 003165 DRY	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1043	X		A	15	SB6325
SSC-20 Battery Wt Min/Max = 885/907 SSC-30 36 x 13.1875 x Open BIG JOE # 003141 WET	24	12-D85-11	9.89	425	85	3020	26.0625	12.75	23.25	885	X		A	15	SB6325
SSC-20 Battery Wt Min/Max=1177/1216 SSC-30 36 x 13.1875 x Open BIG JOE # 003157 WET	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1193	X		A	15	SB6325
SSC-20 Battery Wt Min/Max=1390/1450 SSC-30 36 x 13.1875 x Open BIG JOE # 003158 WET	24	12-D110-13	15.36	660	110	3008	30.5625	12.75	31.125	1441	X		A	15	SB6325
SSC-20 Battery Wt Min/Max = 796/800 SSC-30 36 x 13.1875 x Open BIG JOE # 003161 WET	24	12-D85-9 pk	7.91 os	340	85	3019	30.5625	12.75	23.25	800	X		A	15	SB6325
SSC-20 Battery Wt Min/Max = 760/780 SSC-30 36 x 13.1875 x Open BIG JOE # 003166 WET	24	12-D75-9 pk	6.98 os	300	75	3019	30.5625	12.75	23.25	770	X		A	15	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIES (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		6 Hr. Rating KWH Ah		Plate Rating Ah	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Position/ Lead Length (in.)		Standard Connector
								Length X	Width Y	Height Z		Yes	No			
SSC-20 Battery Wt Min/Max=1042/1055 SSC-30 36 x 13.1875 x Open BIG JOE # 003173-01 WET BIG JOE # 003173-02 DRY	24	12-D85-13	EE	11.87	510	85	3325	30.5625	12.75	23.25	1054	X		A	15	SB6325
SSC-20, SSC-30 36 x 13.1875 x Open BIG JOE # 003180-01 WET BIG JOE # 003180-02 DRY	24	12-D85-11	EE	9.89	425	85	3368	26.0625	12.75	23.25	917	X		A	15	SB6325
SSC-20, SSC-30 36 x 13.1875 x Open BIG JOE # 003182-01 WET BIG JOE # 003182-02 DRY	24	12-D125-15	EE	20.37	875	125	3327	35.0625	12.875	31.125	1677	X		D-REAR	15	SB6325
SSC-20, SSC-30 36 x 13.1875 x Open BIG JOE # 003185-01 WET BIG JOE # 003185-02 DRY	24	12-D75-13		10.47	450	75	3019	30.5625	12.75	23.25	999	X		A	15	SB6325
SSC-20, SSC-30 36 x 13.1875 x Open BIG JOE # 003186-01 WET BIG JOE # 003186-02 DRY	24	12-D75-13	EE	10.47	450	75	3325	30.5625	12.75	23.25	1004	X		A	15	EC5810
SSC-20 Battery Wt Min/Max = 940/970 SSC-30 36 x 13.1875 x Open BIG JOE # 003212 WET	24	12-D85-11	CM	9.89	425	85	3163	31.375	12.875	23.25	950	X		A	15	SB6325
WPT-45 26.375 x 8.0625 x Open	24	12-D85-5		3.96	170	85	3996	25.5	7.5	23.1875	466	X		A	11	SB6325
	24	12-H80-5		3.72	160	80	3996	25.5	7.5	23.1875	447	X		A	11	SB6325
	24	12-P95-5		4.42	190	95	3996	25.5	7.5	23.1875	471	X		A	11	SB6325
WRT-60 Battery Wt. Min = 975 lbs 31.125 x 13.125 x 31.625	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1043	X		A	11	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1001	X		A	11	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1053	X		A	11	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

os - OVERSIZED, number of plates have been reduced for lower A.H. rating.
EE - Sparkproof battery and tray design.
pk - Packing included.
CM - Charge-Mate includes on-board charger.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.