

Deka's rugged  
Outdoorsman line  
provides maintenance-  
free performance.



## Key Features and Benefits of the Deka Lawn & Garden/Small Engine Line

- **Plenty of cranking amps** to power tractors and recreational vehicles across the roughest terrain. Outdoorsman batteries have the power to perform in winter's bitter cold and summer's scorching heat.
- A calcium **maintenance-free design**, eliminates the need to add water and delivers more power-per-pound and **longer storage life** season after season.
- The **flush cover** eliminates the danger of harmful acid spills and lost vent caps, providing **safer and easier operation**. Flush cover batteries replace original equipment batteries more easily because there are no pod vents to interfere with hold-downs and cables.
- **Envelope separators** protect all sides of the plates, preventing internal shorting and providing **superior cranking capacity**.
- Tough **lightweight polypropylene cases** resist breakage under the roughest conditions.
- More than **250 quality control checks** guarantee the highest quality.

# Deka L&G/Small Engine Batteries

GROUP NO.	PARTNUMBER		PERFORMANCE LEVEL				DRY: QTS. OF ACID REQUIRED	MAXIMUM OVERALL DIMENSIONS						CORE VALUE	FOOTNOTES											
	WET	DRY	CCA	RC	REF. CA	10H CAP.		LENGTH		WIDTH		HEIGHT														
															in	mm	in	mm	in	mm						
<b>12-VOLT LAWN &amp; GARDEN / SMALL ENGINE APPLICATIONS - 12 MONTHS FREE</b>																										
U1	11U1L	—	350	—	430	—	—	7-3/4	197	5-1/8	130	7-1/4	184	0.5	22,Z											
	10U1L	—	300	—	370	—	—																			
	8U1L	8U1LD	230	—	285	—	2.3																			
	7U1L	—	195	—	240	—	—																			
	4U1L	—	150	—	185	—	—																			
U1R	11U1R	—	350	—	430	—	—	7-3/4	197	5-1/8	130	7-1/4	184	0.5	22,Y											
	10U1R	—	300	—	370	—	—																			
	8U1R	8U1RD	230	—	285	—	2.3																			
	7U1R	—	195	—	240	—	—																			
	4U1R	—	150	—	185	—	—																			
<b>U1L = left front positive; U1R = right front positive (with terminal side of battery to front)</b>																										
22F	522FMF	—	425	65	525	—	—	9-3/8	238	6-3/4	171	8-1/4	210	1.0	—											
22NF	322NF	—	360	58	445	—	—	9-3/8	238	5-1/2	140	9	229	0.5	12											
<b>12 VOLT — OTHER SIZES USED IN LAWN &amp; GARDEN / SMALL ENGINE APPLICATIONS</b>																										
75/86	775DT	—	690	95	850	—	—	9-3/4	248	7	178	8-1/8	206	1.0	14,16,17,18,22,37											
	675DT	—	650	90	800	—	—																			
	575DT	—	540	85	665	—	—																			
34/78	778DT	—	800	115	985	—	—	10-3/4	273	6-7/8	175	8	203	1.0	14,16,17,18,22,37											
	678DT	—	690	110	850	—	—																			
	578DT	—	550	90	675	—	—																			
24	724MF	—	725	120	890	—	—	10-3/4	273	6-3/4	171	9	229	1.0	17,22											
	624MF	—	650	115	800	—	—																			
	524MF	—	550	90	675	—	—																			
	424MF	—	460	70	565	—	—																			
24F	724FMF	—	725	120	890	—	—	10-3/4	273	6-3/4	171	9	229	1.0	17,22											
	624FMF	—	650	115	800	—	—																			
	524FMF	—	550	90	675	—	—																			
	424FMF	—	460	70	565	—	—																			
25	525MF	—	550	90	675	—	—	9-3/4	248	6-7/8	175	8-7/8	225	1.0	17,22											
	526MF	—	540	80	665	—	—	8-3/4	222	6-3/4	171	8	203	1.0	17,18,22,37											
26	426MF	—	450	55	555	—	—																			
	526RMF	—	540	80	665	—	—	8-3/4	222	6-3/4	171	8	203	1.0	17,18,22,37											
426RMF	—	450	55	555	—	—																				
27	727MF	—	840	140	1035	—	—	12-5/8	321	6-3/4	171	9	229	1.0	17,21											
	627MF	—	710	120	875	—	—	12	305	6-3/4	171	9	229		21											
34	734MF	—	800	115	985	—	—	10-3/4	273	6-7/8	175	8	203	1.0	17,18,22,37											
	634MF	—	690	110	850	—	—																			
	534MF	—	550	90	675	—	—																			
35	735MF	—	640	95	785	—	—	9-9/16	247	6-7/8	175	8-7/8	225	1.0	17,22											
	535MF	—	550	90	675	—	—																			
41	641MF	—	650	100	800	—	—	11-9/16	293	6-7/8	175	6-7/8	175	1.0	22											
45	545MF	—	485	65	595	—	—	9-3/8	238	5-1/2	140	9	229	1.0	—											
49	649MF	—	900	185	1105	—	—	3-15/16	354	6-7/8	175	7-1/2	190	1.0	17,22,26											
51	551MF	—	450	70	555	—	—	9-3/8	238	5	127	8-3/4	222	1.0	22											
	651RMF	—	500	75	615	—	—	9-3/8	238	5	127	8-3/4	222	1.0	22											
51R	551RMF	—	450	70	555	—	—																			
55	655MF	—	540	75	665	—	—	8-3/4	222	6	152	8-1/2	216	1.0	17,18											
58	658MF	—	580	85	715	—	—	10	254	7-1/4	184	7	178	1.0	17,22											
	558MF	—	500	75	615	—	—																			
70	570MF	—	540	80	665	—	—	8-3/4	222	7	178	7-1/8	181	1.0	17,18,22,37											
—	—	12N93A	—	—	—	9	0.7	5-5/16	135	3	75	5-1/2	139	0.2	11											
—	—	YB9BFP	—	—	—	9	INCLUDED	5-5/16	135	3	75	5-1/2	139													
—	—	YB12AAFP	—	—	—	12	INCLUDED	5-5/16	135	3-3/16	80	6-5/8	160													
—	—	YB14AA2FP	—	—	—	14	INCLUDED	5-5/16	135	3-1/2	89	6-9/16	166													
—	—	YB14LA2FP	—	—	—	14	INCLUDED	5-5/16	135	3-1/2	89	6-9/16	166													
—	—	YB16BFP	—	—	—	19	INCLUDED	6-7/8	175	4	100	6-1/8	155													
—	—	YB18LAFP	—	—	—	18	INCLUDED	7-1/8	180	3-9/16	90	6-3/8	162													
—	—	Y50N18LA3FP	—	—	—	20	INCLUDED	8-1/8	205	3-9/16	90	6-3/8	162													
<b>12 VOLT — AGM — BATTERIES USED IN LAWN &amp; GARDEN / SMALL ENGINE APPLICATIONS</b>																										
—	—	YTX4LBSFP	—	—	—	3	INCLUDED	4-1/2	114	2-13/16	71	3-3/8	86	0.2	—											
—	ETX15	—	220	—	—	14	—	5-1/4	134	3-1/2	90	6-9/16	166		2,38,39,42,76											
—	ETX15L	—	220	—	—	14	—	5-1/4	134	3-1/2	90	6-9/16	166		2,38,39											
—	ETX16	—	325	—	—	19	—	6-7/8	175	4	100	6-1/8	155		2,38,39,42,74											
—	ETX18L	—	340	—	—	20	—	8-1/8	206	3-9/16	91	6-3/8	163		2,38,39											
—	ETX20L	—	310	—	—	17.5	—	6-7/8	175	3-7/16	88	6-1/8	155		2,38,39											

- Batteries are maintenance-free calcium grids, except where noted  
 - Batteries manufactured in polypropylene cases & covers, except where noted  
 - Batteries manufactured in black cases & covers, except where noted  
 - SAE or DIN auto posts used, unless noted (Excludes Power Sports Sizes)  
 - CA rating @ 32°F is an approximation, for comparison only  
 - CCA and RC ratings conform to B.C.I. specifications

**FOOTNOTES:**

- 2 - Black cover / Gray case
- 8 - Dry charged batteries have black covers & white cases
- 11 - Low maintenance - low antimony grids
- 12 - Hybrid construction
- 14 - Centerline terminal posts
- 17 - Includes handle
- 18 - Includes top adapter
- 19 - Includes lifting edges
- 21 - Anchor lock elements
- 20 - Hard rubber, multi-cell cover construction
- 22 - Flush manifold vented cover

- 23 - Flush manifold vented cover when shipped wet, standard cover when shipped dry or FP
- 30 - Available dry-add "D" suffix to part number
- 37 - For height with adapter add 7/8" (22 mm)
- 42 - For height with adapter add 7/8" (22 mm)
- 74 - Shipped with 20mm adapter
- 97 - AGM, activated, ready to install
- S - SAE "automotive type" post
- Y - Small L terminal with round holes
- Z - Small L terminal with square holes



**PROPOSITION 65 WARNING:** Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**



East Penn Manufacturing Co. Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781 [www.dekabatteries.com](http://www.dekabatteries.com)

E.P.M. Form No. 0008 8/18 © 2018 by EPM Printed in U.S.A.

All data subject to change without notice. No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.