

**SOME LIKE IT HOT**



## HT30

- Helios™ Additive reduces float current up to 75% enhancing high temperature life
- Microcat® Catalyst lowers float current, mitigates thermal buildup and cell dryout
- Exclusive IPF® Technology optimizes power capacity, cell consistency, and long-term reliability
- TempX™ Alloy inhibits corrosion under the highest temperature extremes
- Advanced AGM technology for superior power
- Puncture resistant micro-porous glass mat separators extend life
- Reinforced case resists bulging and meets safety requirements (UL 94 V-0)
- Case & cover heat sealed and 100% tested to prevent leaks
- Epoxy-sealed posts eliminate leaks
- Flame arresting, low pressure, self-sealing valves are 100% factory tested
- Computer-aided design and manufacturing control processes and standards to ensure quality products
- All batteries meet or exceed IEEE recommended practices
- Battery design and construction meet UL recognition requirements



### SPECIFICATIONS

**Nominal Voltage:** 12-Volts

**Rating:** 28.2 Ampere-Hours @ 8 hr. rate to 1.75 V.P.C.

**Positive Plate:** >98% Pure lead with tin-calcium alloy

**Negative Plate:** Pure lead, calcium alloy

**Post Seal:** Top access, 1/4" – 20 threaded insert

**Case/Cover:** Flame-retardant, polypropylene – UL 94 V-0/>28% L.O.I.

**Catalyst:** Microcat®

**Safety Vent:** Low positive pressure, self-sealing w/ flame arrestor

**Float Voltage:** 2.25 V.P.C. ± 0.01 V.P.C. @ 77°F (25°C)  
Range: (13.44V to 13.56V per battery)

**Design life:** 12 years in float applications @ 77°F (25°C)


**Dimensions:** Length - 7.82" (199 mm)  
Width - 5.29" (134.3 mm)  
Height - 6.71" (170 mm)

**Weight:** 26 lbs. (12 kg)

### DISCHARGE RATINGS IN AMPS @ 77°F (25°C)<sup>†</sup>

Volts per Cell (V.P.C.)	1 HR.	2 HR.	3 HR.	4 HR.	5 HR.	8 HR.	12 HR.	20 HR.	24 HR.
1.75	22.9	12.5	8.7	6.7	5.5	3.5	2.4	1.5	1.2
1.80	22.3	12.2	8.6	6.6	5.4	3.5	2.4	1.4	1.2
1.85	20.9	11.6	8.2	6.3	5.2	3.3	2.3	1.4	1.2
1.88	19.3	10.9	7.7	6.0	4.9	3.2	2.2	1.3	1.1
1.90	18.1	10.3	7.3	5.7	4.7	3.0	2.1	1.3	1.1

<sup>†</sup>Subject to change without notice.



## INSTALLATION AND OPERATING INSTRUCTIONS

<http://www.eastpennmanufacturing.com/wp-content/uploads/Fahrenheit-10-Manual-2100.pdf>

**PROPOSITION 65 WARNING:** Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**



[www.dekabatteries.com](http://www.dekabatteries.com)

QUALITY SYSTEM  
CERTIFIED  
**ISO 9001**  
**IATF 16949**  
ENVIRONMENTAL  
SYSTEM CERTIFIED  
**ISO 14001**

**UL**  
®  
UL Recognized Component



East Penn Manufacturing Co.

Lyon Station, PA 19536-0147

Phone: 610-682-3263

Fax: 610-682-0891

e-mail: [reservepowersales@dekabatteries.com](mailto:reservepowersales@dekabatteries.com)