

NO WATERING REQUIRED



DOMINATOR[®]

MOTIVE POWER BATTERIES

QUALITY SYSTEM
CERTIFIED
ISO 9001
ISO/TS 16949
ENVIRONMENTAL
SYSTEM CERTIFIED
ISO 14001





MADE IN U.S.A.
WITH U.S. AND
IMPORTED MATERIALS



DOMINATOR®

DEKA DOMINATOR BATTERIES feature sealed gel technology cells offering high quality performance with zero watering required.

Decrease downtime and raise profitability with **DEKA BATTERIES**. Precision-built **DEKA BATTERIES** provide dependable power for all your material handling needs.

Designed and manufactured with the finest materials under strict computer control, **DEKA BATTERIES** require fewer non-productive changeouts, reducing downtime. All **DEKA BATTERIES** pass through more than 250 quality control checks to assure consistent quality every time, and **DEKA BATTERIES** have the smallest percentage of warranty claims in the industry, substantially decreasing your cost-per-cycle and raising your productivity and profits.

DEKA BATTERIES are backed by a nationwide sales and service team, ready to handle all your industrial battery and charger repair and maintenance needs. Our highly skilled technicians come directly to your business site to conduct emergency repairs, preventative maintenance and routine inspections. This on-site service keeps your equipment up and running rather than sitting idle while batteries are sent out for repairs.

Compare these features which are standard on every Deka battery:

- East Penn uses exclusive formation processes that ensures optimized power capacity, cell consistency, and long term reliability from every plate and ultimately each cell, in terms of amp- hour capacity and cycle life.
- Superior non-porous, precision-cast grids are designed for maximum current-carrying capacity exclusively for motive power applications. The grids are pasted with active material that delivers reliable performance throughout a long service life. All phases of plate production are computer controlled to meet rigid quality control specifications.
- Both the positive and negative plates are cured in temperature/humidity-controlled ovens to ensure optimum plate curing regardless of external environmental conditions.
- The positive plate is protected by a multiple-step retention system, including two layers of vertical mats consisting of fiberglass tape and interwoven glass fibers, a horizontal glass fiber mat, and a perforated retainer envelope. This ensures optimum active material retention for longer life, and provides increased plate insulation for added performance. The positive plates are also surrounded by deep channeled, microporous separators that provide a durable barrier between positive and negative plates, while allowing the free flow of electrolyte throughout the cell, optimizing performance and extending service life.
- No other industrial battery manufacturer can claim these and other features, plus ensure the highest quality material, workmanship and superior engineering technology. All of these important components make the Deka name synonymous with number one quality in the production of precision-built batteries.
- Manufactured in compliance with American National Standards Institute and Underwriters Laboratories Standard Number ANSI/UL583.
- Federal Specification Number W-B-133D.
- Complies with Industrial Truck Association Recommended Practices.



e-mail: epmmotive@eastpenn-deka.com www.dekabatteries.com



East Penn Manufacturing Co. Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781 Order Hotline: 610-682-3260