



# INDUSTRIAL BATTERIES

## MITSUBISHI

### WALKIE, RIDER/WALKIE, TOW TRACTORS

| Truck Model and Maximum Battery Size (Inches)  | Volt | Battery Type |    | 6 Hr. Rating |      | Plate Rating Ah | IST Tray No. | Battery Dimensions (in.) |         |          | Approx. Serv. Wt. (lbs.) | Cover |    | Position/Lead Length (in.) |    | Standard Connector |
|--|------|--------------|----|--------------|------|-----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|----------------------------|----|--------------------|
|  |      |              |    | KWH          | Ah   |                 |              | Length X                 | Width Y | Height Z |                          | Yes   | No |                            |    |                    |
| NTT90T, PLDM20, PLDM20A<br>PLDM20B, PLDM30, PLDM30A<br>PLDM30B<br>32 x 8.0625 x 23.5 | 12   | 6-D85-11     | cm | 4.95         | 425  | 85              | 1061         | 31.25                    | 7.75    | 23.1875  | 516                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-H80-11     | cm | 4.66         | 400  | 80              | 1061         | 31.25                    | 7.75    | 23.1875  | 495                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-P95-11     | cm | 5.53         | 475  | 95              | 1061         | 31.25                    | 7.75    | 23.1875  | 521                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-D85-13     |    | 5.94         | 510  | 85              | 1088         | 30.5                     | 7.75    | 23.1875  | 538                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-H80-13     |    | 5.59         | 480  | 80              | 1088         | 30.5                     | 7.75    | 23.1875  | 516                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-P95-13     |    | 6.63         | 570  | 95              | 1088         | 30.5                     | 7.75    | 23.1875  | 543                      | X     |    | B                          | 12 | SB6325             |
| NTT90TA, PLDM20AA<br>PLDM20BA, PLDM300BA<br>PLDM30AA<br>32 x 13.25 x 23.5            | 24   | 12-D85-11    | cm | 9.89         | 425  | 85              | 3163         | 31.375                   | 12.875  | 23.25    | 950                      | X     |    | B                          | 12 | SB6325             |
|  | 24   | 12-H80-11    | cm | 9.31         | 400  | 80              | 3163         | 31.375                   | 12.875  | 23.25    | 912                      | X     |    | B                          | 12 | SB6325             |
|  | 24   | 12-P95-11    | cm | 11.06        | 475  | 95              | 3163         | 31.375                   | 12.875  | 23.25    | 960                      | X     |    | B                          | 12 | SB6325             |
|  | 24   | 12-D85-13    |    | 11.87        | 510  | 85              | 3019         | 30.5625                  | 12.75   | 23.25    | 1043                     | X     |    | B                          | 12 | SB6325             |
|  | 24   | 12-H80-13    |    | 11.17        | 480  | 80              | 3019         | 30.5625                  | 12.75   | 23.25    | 1001                     | X     |    | B                          | 12 | SB6325             |
|  | 24   | 12-P95-13    |    | 13.27        | 570  | 95              | 3019         | 30.5625                  | 12.75   | 23.25    | 1053                     | X     |    | B                          | 12 | SB6325             |
| NTT90T<br>32 x 13.25 x 23.375  | 12   | 6-D85-25     |    | 11.87        | 1020 | 85              | 1215         | 31                       | 12.875  | 23.25    | 1027                     | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-D85-25     |    | 11.87        | 1020 | 85              | 1040         | 28.9375                  | 12.875  | 23.25    | 999                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-H80-25     |    | 11.17        | 960  | 80              | 1215         | 31                       | 12.875  | 23.25    | 986                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-H80-25     |    | 11.17        | 960  | 80              | 1040         | 28.9375                  | 12.875  | 23.25    | 959                      | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-P95-25     |    | 13.27        | 1140 | 95              | 1215         | 31                       | 12.875  | 23.25    | 1037                     | X     |    | B                          | 12 | SB6325             |
|  | 12   | 6-P95-25     |    | 13.27        | 1140 | 95              | 1040         | 28.9375                  | 12.875  | 23.25    | 1009                     | X     |    | B                          | 12 | SB6325             |
| NTT100<br>35.1875 x 19.0625 x 14.75  | 48   | 24-D35-11    |    | 8.15         | 175  | 35              | 7092         | 34.5625                  | 19      | 13       | 851                      | X     |    | B                          | 15 | SB6325             |
| NTF200PN<br>35.5625 x 26.5625 x 17.875   | 48   | 24-D45-15    |    | 14.67        | 315  | 45              | 7977         | 35.0625                  | 26.0625 | 15.75    | 1422                     | X     |    | A                          | 12 | 6325               |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches)                  | Volt | Battery<br>Type | 6 Hr. Rating<br>KWH | Ah    | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) |   | Standard<br>Connector |        |
|--|------|-----------------|---------------------|-------|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|---|-----------------------|--------|
|  |      |                 |                     |       |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |   |                       |        |
| PMW20<br>29.375 x 8.875 x 26.5                                       | 24   | 12-D100-5       | cm                  | 4.66  | 200                   | 100                | 3526                     | 24.25      | 8.3125      | 26.1875                        | 514   | X  |                                   | B | 12                    | SB6325 |
|  | 24   | 12-D100-7       |                     | 6.98  | 300                   | 100                | 3123                     | 25.3125    | 8.5625      | 26.1875                        | 649   | X  |                                   | B | 12                    | SB6325 |
|  | 24   | 12-D85-7        |                     | 5.94  | 255                   | 85                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 567   | X  |                                   | B | 12                    | SB6325 |
|  | 24   | 12-H80-7        |                     | 5.59  | 240                   | 80                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 544   | X  |                                   | B | 12                    | SB6325 |
|  | 24   | 12-P95-7        |                     | 6.63  | 285                   | 95                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 573   | X  |                                   | B | 12                    | SB6325 |
| PMW30<br>32 x 9.1875 x 24  | 24   | 12-D85-7        |                     | 5.94  | 255                   | 85                 | 3447                     | 30.5       | 8.5625      | 23.25                          | 595   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-D85-7        | cm                  | 5.94  | 255                   | 85                 | 3415                     | 30.5       | 8.5625      | 23.1875                        | 606   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-D85-7        |                     | 5.94  | 255                   | 85                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 567   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H80-7        |                     | 5.59  | 240                   | 80                 | 3447                     | 30.5       | 8.5625      | 23.25                          | 571   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H80-7        | cm                  | 5.59  | 240                   | 80                 | 3415                     | 30.5       | 8.5625      | 23.1875                        | 582   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H80-7        |                     | 5.59  | 240                   | 80                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 544   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-P95-7        |                     | 6.63  | 285                   | 95                 | 3447                     | 30.5       | 8.5625      | 23.25                          | 601   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-P95-7        | cm                  | 6.63  | 285                   | 95                 | 3415                     | 30.5       | 8.5625      | 23.1875                        | 612   | X  |                                   | B | 18                    | SB6325 |
| PMWR30, PMWR40<br>31.9375 x 13.5 x 30.9375                           | 24   | 12-D100-11      | cm                  | 11.64 | 500                   | 100                | 3539                     | 31.375     | 12.875      | 26.25                          | 1068  | X  |                                   | B | 30                    | SB6325 |
|  | 24   | 12-D85-11       | cm                  | 9.89  | 425                   | 85                 | 3163                     | 31.375     | 12.875      | 23.25                          | 950   | X  |                                   | B | 30                    | SB6325 |
|  | 24   | 12-H80-11       | cm                  | 9.31  | 400                   | 80                 | 3163                     | 31.375     | 12.875      | 23.25                          | 912   | X  |                                   | B | 30                    | SB6325 |
|  | 24   | 12-P95-11       | cm                  | 11.06 | 475                   | 95                 | 3163                     | 31.375     | 12.875      | 23.25                          | 960   | X  |                                   | B | 30                    | SB6325 |
|  | 24   | 12-D100-13      |                     | 13.97 | 600                   | 100                | 3015                     | 30.5625    | 12.75       | 26.25                          | 1193  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-D85-13       |                     | 11.87 | 510                   | 85                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1043  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H80-13       |                     | 11.17 | 480                   | 80                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1001  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-P95-13       |                     | 13.27 | 570                   | 95                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1053  | X  |                                   | B | 18                    | SB6325 |
| PMWR30, PMWR30N, PMWR40<br>PW30L<br>32 x 13.5625 x 31.25             | 24   | 12-D100-13      |                     | 13.97 | 600                   | 100                | 3015                     | 30.5625    | 12.75       | 26.25                          | 1193  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-D125-13      |                     | 17.46 | 750                   | 125                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1455  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-D85-13       |                     | 11.87 | 510                   | 85                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1043  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H120-13      |                     | 16.76 | 720                   | 120                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1440  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H80-13       |                     | 11.17 | 480                   | 80                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1001  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-P140-13      |                     | 19.56 | 840                   | 140                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1470  | X  |                                   | B | 18                    | SB6325 |
| PMCR30, PMCR40, PMW30<br>(Optional Compartment)<br>32 x 13.4375 x 24 | 24   | 12-D85-11       | cm                  | 9.89  | 425                   | 85                 | 3163                     | 31.375     | 12.875      | 23.25                          | 950   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H80-11       | cm                  | 9.31  | 400                   | 80                 | 3163                     | 31.375     | 12.875      | 23.25                          | 912   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-P95-11       | cm                  | 11.06 | 475                   | 95                 | 3163                     | 31.375     | 12.875      | 23.25                          | 960   | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-D85-13       |                     | 11.87 | 510                   | 85                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1043  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-H80-13       |                     | 11.17 | 480                   | 80                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1001  | X  |                                   | B | 18                    | SB6325 |
|  | 24   | 12-P95-13       |                     | 13.27 | 570                   | 95                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1053  | X  |                                   | B | 18                    | SB6325 |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

# WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches)  | Volt      | Battery<br>Type | 6 Hr. Rating<br>KWH | Ah    | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) |    | Standard<br>Connector |        |
|--|-----------|-----------------|---------------------|-------|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|----|-----------------------|--------|
|  |           |                 |                     |       |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |    |                       |        |
| PMCR40<br>31.5 x 13.4375 x 31.5  | 24        | 12-D100-11      | cm                  | 11.64 | 500                   | 100                | 3539                     | 31.375     | 12.875      | 26.25                          | 1068  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D85-11       | cm                  | 9.89  | 425                   | 85                 | 3163                     | 31.375     | 12.875      | 23.25                          | 950   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H80-11       | cm                  | 9.31  | 400                   | 80                 | 3163                     | 31.375     | 12.875      | 23.25                          | 912   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-P95-11       | cm                  | 11.06 | 475                   | 95                 | 3163                     | 31.375     | 12.875      | 23.25                          | 960   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D100-13      |                     | 13.97 | 600                   | 100                | 3015                     | 30.5625    | 12.75       | 26.25                          | 1193  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D125-13      |                     | 17.46 | 750                   | 125                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1455  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D85-13       |                     | 11.87 | 510                   | 85                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1043  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H120-13      |                     | 16.76 | 720                   | 120                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1440  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H80-13       |                     | 11.17 | 480                   | 80                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1001  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-P140-13      |                     | 19.56 | 840                   | 140                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1470  | X  |                                   | B  | 18                    | SB6325 |
| 24   | 12-P95-13 |                 | 13.27               | 570   | 95                    | 3019               | 30.5625                  | 12.75      | 23.25       | 1053                           | X     |    | B                                 | 18 | SB6325                |        |
| PMWS15<br>31.875 x 13.375 x Open   | 24        | 12-D100-11      | cm                  | 11.64 | 500                   | 100                | 3539                     | 31.375     | 12.875      | 26.25                          | 1068  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D85-11       | cm                  | 9.89  | 425                   | 85                 | 3163                     | 31.375     | 12.875      | 23.25                          | 950   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H80-11       | cm                  | 9.31  | 400                   | 80                 | 3163                     | 31.375     | 12.875      | 23.25                          | 912   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-P95-11       | cm                  | 11.06 | 475                   | 95                 | 3163                     | 31.375     | 12.875      | 23.25                          | 960   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D100-13      |                     | 13.97 | 600                   | 100                | 3015                     | 30.5625    | 12.75       | 26.25                          | 1193  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D125-13      |                     | 17.46 | 750                   | 125                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1455  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D85-13       |                     | 11.87 | 510                   | 85                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1043  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H120-13      |                     | 16.76 | 720                   | 120                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1440  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H80-13       |                     | 11.17 | 480                   | 80                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1001  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-P140-13      |                     | 19.56 | 840                   | 140                | 3008                     | 30.5625    | 12.75       | 31.125                         | 1470  | X  |                                   | B  | 18                    | SB6325 |
| 24   | 12-P95-13 |                 | 13.27               | 570   | 95                    | 3019               | 30.5625                  | 12.75      | 23.25       | 1053                           | X     |    | B                                 | 18 | SB6325                |        |
| PMT90, PMT, PMWS15<br>PMWT15, PMWT20<br>31.5 x 13.4375 x 24<br>Min. Battery Wt. - 975 lbs. | 24        | 12-D85-11       | cm                  | 9.89  | 425                   | 85                 | 3163                     | 31.375     | 12.875      | 23.25                          | 950   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H80-11       | cm                  | 9.31  | 400                   | 80                 | 3163                     | 31.375     | 12.875      | 23.25                          | 912   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-P95-11       | cm                  | 11.06 | 475                   | 95                 | 3163                     | 31.375     | 12.875      | 23.25                          | 960   | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-D85-13       |                     | 11.87 | 510                   | 85                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1043  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-H80-13       |                     | 11.17 | 480                   | 80                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1001  | X  |                                   | B  | 18                    | SB6325 |
|  | 24        | 12-P95-13       |                     | 13.27 | 570                   | 95                 | 3019                     | 30.5625    | 12.75       | 23.25                          | 1053  | X  |                                   | B  | 18                    | SB6325 |
| PMWT15N, PMWT18N<br>25.25 x 11.25 x 25.5   | 24        | 12-D85-9        |                     | 7.92  | 340                   | 85                 | 3150                     | 25.1875    | 10.8125     | 22.5625                        | 696   |    | X                                 | A  | 12                    | SB6325 |
|  | 24        | 12-H80-9        |                     | 7.45  | 320                   | 80                 | 3150                     | 25.1875    | 10.8125     | 22.5625                        | 668   |    | X                                 | A  | 12                    | SB6325 |
|  | 24        | 12-P95-9        |                     | 8.85  | 380                   | 95                 | 3150                     | 25.1875    | 10.8125     | 22.5625                        | 703   |    | X                                 | A  | 12                    | SB6325 |
| PMW23N<br>26.25 x 8.75 x 25  | 24        | 12-D85-7        |                     | 5.94  | 255                   | 85                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 567   | X  |                                   | A  | 18                    | SB6325 |
|  | 24        | 12-H80-7        |                     | 5.59  | 240                   | 80                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 544   | X  |                                   | A  | 18                    | SB6325 |
|  | 24        | 12-P95-7        |                     | 6.63  | 285                   | 95                 | 3042                     | 25.25      | 8.5625      | 23.1875                        | 573   | X  |                                   | A  | 18                    | SB6325 |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches)         | Volt | Battery<br>Type | 6 Hr. Rating |     | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) |    | Standard<br>Connector |
|---|------|-----------------|--------------|-----|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|----|-----------------------|
|   |      |                 | KWH          | Ah  |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |    |                       |
| PMW23NL<br>31.25 x 8.75 x 31.25                             | 24   | 12-D100-7       | 6.98         | 300 | 100                   | 3456               | 30.5                     | 8.5625     | 26.1875     | 672                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-D100-7       | 6.98         | 300 | 100                   | 3346               | 30.5                     | 8.5625     | 26.1875     | 693                            | X     |    | A                                 | 24 | SB6325                |
|   | 24   | 12-D100-7       | 6.98         | 300 | 100                   | 3123               | 25.3125                  | 8.5625     | 26.1875     | 649                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-D125-7       | 8.73         | 375 | 125                   | 3824               | 29.1875                  | 8.6875     | 31.125      | 851                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-D125-7       | 8.73         | 375 | 125                   | 3329               | 25.3125                  | 8.5625     | 31.0625     | 787                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-D85-7        | 5.94         | 255 | 85                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 567                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-H120-7       | 8.38         | 360 | 120                   | 3824               | 29.1875                  | 8.6875     | 31.125      | 842                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-H120-7       | 8.38         | 360 | 120                   | 3329               | 25.3125                  | 8.5625     | 31.0625     | 779                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-H80-7        | 5.59         | 240 | 80                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 544                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-P140-7       | 9.78         | 420 | 140                   | 3824               | 29.1875                  | 8.6875     | 31.125      | 860                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-P140-7       | 9.78         | 420 | 140                   | 3329               | 25.3125                  | 8.5625     | 31.0625     | 795                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-P95-7        | 6.63         | 285 | 95                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 573                            | X     |    | A                                 | 18 | SB6325                |
| PMW30N<br>25.25 x 8.875 x 25<br>Min. Battery Wt. - 485 lbs. | 24   | 12-D85-7        | 5.94         | 255 | 85                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 567                            | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-H80-7        | 5.59         | 240 | 80                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 544                            | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-P95-7        | 6.63         | 285 | 95                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 573                            | X     |    | B                                 | 18 | SB6325                |
| PMW30NL<br>31.5 x 13.5 x 31.1875                            | 24   | 12-D100-11      | 11.64        | 500 | 100                   | 3539               | 31.375                   | 12.875     | 26.25       | 1068                           | X     |    | B                                 | 30 | SB6325                |
|   | 24   | 12-D85-11       | 9.89         | 425 | 85                    | 3163               | 31.375                   | 12.875     | 23.25       | 950                            | X     |    | B                                 | 30 | SB6325                |
|   | 24   | 12-H80-11       | 9.31         | 400 | 80                    | 3163               | 31.375                   | 12.875     | 23.25       | 912                            | X     |    | B                                 | 30 | SB6325                |
|   | 24   | 12-P95-11       | 11.06        | 475 | 95                    | 3163               | 31.375                   | 12.875     | 23.25       | 960                            | X     |    | B                                 | 30 | SB6325                |
|   | 24   | 12-D100-13      | 13.97        | 600 | 100                   | 3015               | 30.5625                  | 12.75      | 26.25       | 1193                           | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-D125-13      | 17.46        | 750 | 125                   | 3008               | 30.5625                  | 12.75      | 31.125      | 1455                           | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-D85-13       | 11.87        | 510 | 85                    | 3019               | 30.5625                  | 12.75      | 23.25       | 1043                           | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-H120-13      | 16.76        | 720 | 120                   | 3008               | 30.5625                  | 12.75      | 31.125      | 1440                           | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-H80-13       | 11.17        | 480 | 80                    | 3019               | 30.5625                  | 12.75      | 23.25       | 1001                           | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-P140-13      | 19.56        | 840 | 140                   | 3008               | 30.5625                  | 12.75      | 31.125      | 1470                           | X     |    | B                                 | 18 | SB6325                |
|   | 24   | 12-P95-13       | 13.27        | 570 | 95                    | 3019               | 30.5625                  | 12.75      | 23.25       | 1053                           | X     |    | B                                 | 18 | SB6325                |
| PW23, PW30<br>26.8125 x 9.375 x 26.625                      | 24   | 12-D85-7        | 5.94         | 255 | 85                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 567                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-H80-7        | 5.59         | 240 | 80                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 544                            | X     |    | A                                 | 18 | SB6325                |
|   | 24   | 12-P95-7        | 6.63         | 285 | 95                    | 3042               | 25.25                    | 8.5625     | 23.1875     | 573                            | X     |    | A                                 | 18 | SB6325                |
| PW23, PW30<br>25.75 x 9.375 x 26.5625                       | 24   | 12-D100-7       | 6.98         | 300 | 100                   | 3165               | 25.5                     | 8.6875     | 25.5625     | 640                            |       | X  | B                                 | 18 | SB6325                |
|   | 24   | 12-D85-7        | 5.94         | 255 | 85                    | 3084               | 25.25                    | 8.5625     | 22.5625     | 556                            |       | X  | B                                 | 18 | SB6325                |
|   | 24   | 12-H80-7        | 5.59         | 240 | 80                    | 3084               | 25.25                    | 8.5625     | 22.5625     | 534                            |       | X  | B                                 | 18 | SB6325                |
|   | 24   | 12-P95-7        | 6.63         | 285 | 95                    | 3084               | 25.25                    | 8.5625     | 22.5625     | 562                            |       | X  | B                                 | 18 | SB6325                |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and Maximum Battery Size (Inches)         | Volt | Battery Type | 6 Hr. Rating |     | Plate Rating Ah | IST Tray No. | Battery Dimensions (in.) |         |          | Approx. Serv. Wt. (lbs.) | Cover |    | Position/Lead Length (in.) |    | Standard Connector |
|---|------|--------------|--------------|-----|-----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|----------------------------|----|--------------------|
|   |      |              | KWH          | Ah  |                 |              | Length X                 | Width Y | Height Z |                          | Yes   | No |                            |    |                    |
| PW23L<br>32.25 x 9.375 x 26.5625                      | 24   | 12-D100-7    | 6.98         | 300 | 100             | 3302         | 31.5                     | 8.75    | 26.1875  | 685                      | X     |    | B                          | 18 | SB6325             |
|   | 24   | 12-D85-7     | 5.94         | 255 | 85              | 3324         | 31.125                   | 8.5625  | 23.1875  | 595                      | X     |    | B                          | 18 | SB6325             |
|   | 24   | 12-H80-7     | 5.59         | 240 | 80              | 3324         | 31.125                   | 8.5625  | 23.1875  | 571                      | X     |    | B                          | 18 | SB6325             |
|   | 24   | 12-P95-7     | 6.63         | 285 | 95              | 3324         | 31.125                   | 8.5625  | 23.1875  | 601                      | X     |    | B                          | 18 | SB6325             |
| PMWT15N, PMWT18N<br>28.25 x 11 x 23.625<br>See Note A | 24   | 12-D85-9     | 7.92         | 340 | 85              | 3150         | 25.1875                  | 10.8125 | 22.5625  | 696                      |       | X  | A                          | 12 | SB6325             |
|   | 24   | 12-H80-9     | 7.45         | 320 | 80              | 3150         | 25.1875                  | 10.8125 | 22.5625  | 668                      |       | X  | A                          | 12 | SB6325             |
|   | 24   | 12-P95-9     | 8.85         | 380 | 95              | 3150         | 25.1875                  | 10.8125 | 22.5625  | 703                      |       | X  | A                          | 12 | SB6325             |
| PWT13, PWT15, PWT18<br>25.6875 x 11.5 x 27.375        | 24   | 12-D100-9    | 9.31         | 400 | 100             | 3683         | 25.1875                  | 10.9375 | 25.625   | 819                      |       | X  | A                          | 32 | SB6325             |
|   | 24   | 12-D85-9     | 7.92         | 340 | 85              | 3150         | 25.1875                  | 10.8125 | 22.5625  | 696                      |       | X  | A                          | 32 | SB6325             |
|   | 24   | 12-H80-9     | 7.45         | 320 | 80              | 3150         | 25.1875                  | 10.8125 | 22.5625  | 668                      |       | X  | A                          | 32 | SB6325             |
|   | 24   | 12-P95-9     | 8.85         | 380 | 95              | 3150         | 25.1875                  | 10.8125 | 22.5625  | 703                      |       | X  | A                          | 32 | SB6325             |

cm - Charge-Mate includes on board charger.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Note A - Battery compartment includes spacer to accommodate smaller battery.

## STRADDLE, STRADDLE REACH TRUCKS

| Truck Model and Maximum Battery Size (Inches)          | Volt | Battery Type | 6 Hr. Rating |     | Plate Rating Ah | IST Tray No. | Battery Dimensions (in.) |         |          | Approx. Serv. Wt. (lbs.) | Cover |    | Position/Lead Length (in.) |    | Standard Connector |
|--|------|--------------|--------------|-----|-----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|----------------------------|----|--------------------|
|  |      |              | KWH          | Ah  |                 |              | Length X                 | Width Y | Height Z |                          | Yes   | No |                            |    |                    |
| FBR12, FBRW12<br>38.5 x 13.1875 x 22.5625              | 24   | 12-D65-15    | 10.59        | 455 | 65              | 3449         | 35.0625                  | 12.875  | 20       | 1017                     |       | X  | D                          | 18 | SB6325             |
|  | 24   | 12-D85-15 dh | 13.85        | 595 | 85              | 3204         | 35.0625                  | 12.875  | 21.625   |                          |       | X  | D                          | 18 | SB6325             |
|  | 24   | 12-H80-15 dh | 13.04        | 560 | 80              | 3204         | 35.0625                  | 12.875  | 21.625   |                          |       | X  | D                          | 18 | SB6325             |
|  | 24   | 12-P95-15 dh | 15.48        | 665 | 95              | 3204         | 35.0625                  | 12.875  | 21.625   |                          |       | X  | D                          | 18 | SB6325             |
| FBR13, FBRW13<br>38 x 13.1875 x 23.5                   | 24   | 12-D85-15    | 13.85        | 595 | 85              | 3056         | 35.0625                  | 12.875  | 22.625   | 1178                     |       | X  | D                          | 18 | SB6325             |
|  | 24   | 12-H80-15    | 13.04        | 560 | 80              | 3056         | 35.0625                  | 12.875  | 22.625   | 1131                     |       | X  | D                          | 18 | SB6325             |
|  | 24   | 12-P95-15    | 15.48        | 665 | 95              | 3056         | 35.0625                  | 12.875  | 22.625   | 1190                     |       | X  | D                          | 18 | SB6325             |
| FBR15, FBR18, FBRW15<br>FBRW18<br>37.875 x 18.5 x 23.5 | 48   | 24-D85-11    | 19.79        | 425 | 85              | 7158         | 37.8125                  | 17.5625 | 22.6875  | 1730                     |       | X  | D                          | 18 | SB6325             |
|  | 48   | 24-H80-11    | 18.62        | 400 | 80              | 7158         | 37.8125                  | 17.5625 | 22.6875  | 1661                     |       | X  | D                          | 18 | SB6325             |
|  | 48   | 24-P95-11    | 22.12        | 475 | 95              | 7158         | 37.8125                  | 17.5625 | 22.6875  | 1747                     |       | X  | D                          | 18 | SB6325             |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## STRADDLE, STRADDLE REACH TRUCKS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches) | Volt | Battery<br>Type | 6 Hr. Rating |      | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) |    | Standard<br>Connector |
|---|------|-----------------|--------------|------|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|----|-----------------------|
|   |      |                 | KWH          | Ah   |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |    |                       |
| FER3000LD, FER3000LD-15D                            | 24   | 12-D160-13      | 22.35        | 960  | 160                   | 3049               | 35.25                    | 15.5625    | 30.5625     | 1985                           |       | X  | C                                 | 18 | SB6320                |
| FER4000LD, FER4000LD-20D                            | 24   | 12-D125-15      | 20.37        | 875  | 125                   | 3036               | 35.0625                  | 12.875     | 30.5        | 1646                           |       | X  | C                                 | 18 | SB6320                |
| 38.5 x 16.625 x 32.5625                             | 24   | 12-H120-15      | 19.56        | 840  | 120                   | 3036               | 35.0625                  | 12.875     | 30.5        | 1630                           |       | X  | C                                 | 18 | SB6320                |
|   | 24   | 12-P140-15      | 22.81        | 980  | 140                   | 3036               | 35.0625                  | 12.875     | 30.5        | 1662                           |       | X  | C                                 | 18 | SB6320                |
|   | 24   | 12-D125-17      | 23.28        | 1000 | 125                   | 3127               | 38.1875                  | 13.5       | 30.5625     | 1948                           |       | X  | C                                 | 18 | SB6320                |
|   | 24   | 12-H120-17      | 22.35        | 960  | 120                   | 3127               | 38.1875                  | 13.5       | 30.5625     | 1929                           |       | X  | C                                 | 18 | SB6320                |
|   | 24   | 12-P140-17      | 26.07        | 1120 | 140                   | 3127               | 38.1875                  | 13.5       | 30.5625     | 1967                           |       | X  | C                                 | 18 | SB6320                |
| FER3000LC, FER3000LC-15C                            | 36   | 18-D125-13      | 26.19        | 750  | 125                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2169                           |       | X  | C                                 | 18 | SB6322                |
| FER4000LC, FER4000LC-20C                            | 36   | 18-H120-13      | 25.14        | 720  | 120                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2147                           |       | X  | C                                 | 18 | SB6322                |
| 38.5 x 16.625 x 32.25                               | 36   | 18-P140-13      | 29.33        | 840  | 140                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2191                           |       | X  | C                                 | 18 | SB6322                |
| EDR13N, EDR24, ESR15N                               | 24   | 12-D125-17      | 23.28        | 1000 | 125                   | 3127               | 38.1875                  | 13.5       | 30.5625     | 1948                           |       | X  | B                                 | 12 | SB6322                |
| ESR18N, ESR20N, ESR24                               | 24   | 12-H120-17      | 22.35        | 960  | 120                   | 3127               | 38.1875                  | 13.5       | 30.5625     | 1929                           |       | X  | B                                 | 12 | SB6322                |
| ESS15N, ESS20N, ESS24                               | 24   | 12-P140-17      | 26.07        | 1120 | 140                   | 3127               | 38.1875                  | 13.5       | 30.5625     | 1967                           |       | X  | B                                 | 12 | SB6322                |
| 38.625 x 14.25 x 31.625                             |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| EDR13N, EDR24, ESR24                                | 24   | 12-D125-19      | 26.19        | 1125 | 125                   | 3134               | 38.1875                  | 15         | 30.5625     | 2126                           |       | X  | B                                 | 12 | SB6322                |
| ESS24, ESS24-15                                     | 24   | 12-H120-19      | 25.14        | 1080 | 120                   | 3134               | 38.1875                  | 15         | 30.5625     | 2105                           |       | X  | B                                 | 12 | SB6322                |
| ESS24-20  | 24   | 12-P140-19      | 29.33        | 1260 | 140                   | 3134               | 38.1875                  | 15         | 30.5625     | 2147                           |       | X  | B                                 | 12 | SB6322                |
| 38.625 x 16.25 x 31.625                             |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| EDR13N, EDR15HN, EDR15N                             | 36   | 18-D125-13      | 26.19        | 750  | 125                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2169                           |       | X  | B                                 | 12 | SB6320                |
| EDR36, ESR18N, ESR20HN                              | 36   | 18-H120-13      | 25.14        | 720  | 120                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2147                           |       | X  | B                                 | 12 | SB6320                |
| ESR20N, ESR23HN, ESR23N                             | 36   | 18-P140-13      | 29.33        | 840  | 140                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2191                           |       | X  | B                                 | 12 | SB6320                |
| ESR36, ESS20N, ESS36                                |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| 38.625 x 16.25 x 31.625                             |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| ESR36, EDR36, ESS36                                 | 36   | 18-D125-17      | 34.92        | 1000 | 125                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2837                           |       | X  | B                                 | 12 | SB6320                |
| ESS36-15, ESS36-20                                  | 36   | 18-H120-17      | 33.52        | 960  | 120                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2809                           |       | X  | B                                 | 12 | SB6320                |
| 38.625 x 21.5 x 31.625                              | 36   | 18-P140-17      | 39.11        | 1120 | 140                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2865                           |       | X  | B                                 | 12 | SB6320                |
| Optional Compartment                                |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| EDR13N, ESR15N, ESS15N                              | 36   | 18-D125-11      | 21.83        | 625  | 125                   | 6016               | 37.8125                  | 13.3125    | 30.5625     | 1853                           |       | X  | B                                 | 12 | SB6320                |
| 38.625 x 14.25 x 31.6875                            | 36   | 18-H120-11      | 20.95        | 600  | 120                   | 6016               | 37.8125                  | 13.3125    | 30.5625     | 1834                           |       | X  | B                                 | 12 | SB6320                |
|   | 36   | 18-P140-11      | 24.44        | 700  | 140                   | 6016               | 37.8125                  | 13.3125    | 30.5625     | 1872                           |       | X  | B                                 | 12 | SB6320                |

dh - Special tray design IST3204 includes drop handles. Overall height to top of terminal is 22.06".

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are  $\pm 1/16"$ . Battery weights may vary  $\pm 5\%$ . Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

# ORDER PICKERS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | 6 Hr. Rating |      | Plate Rating Ah | IST Tray No. | Battery Dimensions (in.) |         |          | Approx. Serv. Wt. (lbs.) | Cover |    | Position/Lead Length (in.) |    | Standard Connector |
|---|------|--------------|--------------|------|-----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|----------------------------|----|--------------------|
|   |      |              | KWH          | Ah   |                 |              | Length X                 | Width Y | Height Z |                          | Yes   | No |                            |    |                    |
| EOP11N2, EOP15HN2<br>33.25 x 17.6875 x 32.125 | 24   | 12-D125-13   | 17.46        | 750  | 125             | 3A54         | 32.8125                  | 17.25   | 30.5625  | 2000                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-H120-13   | 16.76        | 720  | 120             | 3A54         | 32.8125                  | 17.25   | 30.5625  | 1980                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-P140-13   | 19.56        | 840  | 140             | 3A54         | 32.8125                  | 17.25   | 30.5625  | 2020                     |       | X  | C                          | 12 | SB6322             |
| EOP15HN, EOP15N<br>38.625 x 13.25 x 32.25     | 24   | 12-D125-15   | 20.37        | 875  | 125             | 3A47         | 38.0625                  | 12.75   | 30.5     | 1656                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-H120-15   | 19.56        | 840  | 120             | 3A47         | 38.0625                  | 12.75   | 30.5     | 1639                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-P140-15   | 22.81        | 980  | 140             | 3A47         | 38.0625                  | 12.75   | 30.5     | 1673                     |       | X  | C                          | 12 | SB6322             |
| EOP15HN, EOP15N<br>38.625 x 14.25 x 32.25     | 24   | 12-D125-17   | 23.28        | 1000 | 125             | 3127         | 38.1875                  | 13.5    | 30.5625  | 1948                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-H120-17   | 22.35        | 960  | 120             | 3127         | 38.1875                  | 13.5    | 30.5625  | 1929                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-P140-17   | 26.07        | 1120 | 140             | 3127         | 38.1875                  | 13.5    | 30.5625  | 1967                     |       | X  | C                          | 12 | SB6322             |
| EOP15-24, EOP15-24P<br>31.5 x 13.25 x 32.25   | 24   | 12-D125-13   | 17.46        | 750  | 125             | 3093         | 30.5625                  | 12.75   | 30.5     | 1430                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-H120-13   | 16.76        | 720  | 120             | 3093         | 30.5625                  | 12.75   | 30.5     | 1416                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-P140-13   | 19.56        | 840  | 140             | 3093         | 30.5625                  | 12.75   | 30.5     | 1444                     |       | X  | C                          | 12 | SB6322             |
| EOP15-24, EOP15-24P<br>36.75 x 14.5 x 32.25   | 24   | 12-D125-15   | 20.37        | 875  | 125             | 3036         | 35.0625                  | 12.875  | 30.5     | 1646                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-H120-15   | 19.56        | 840  | 120             | 3036         | 35.0625                  | 12.875  | 30.5     | 1630                     |       | X  | C                          | 12 | SB6322             |
|   | 24   | 12-P140-15   | 22.81        | 980  | 140             | 3036         | 35.0625                  | 12.875  | 30.5     | 1662                     |       | X  | C                          | 12 | SB6322             |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

# STAND-UP RIDERS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | 6 Hr. Rating |     | Plate Rating Ah | IST Tray No. | Battery Dimensions (in.) |         |          | Approx. Serv. Wt. (lbs.) | Cover |    | Position/Lead Length (in.) |    | Standard Connector |
|---|------|--------------|--------------|-----|-----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|----------------------------|----|--------------------|
|   |      |              | KWH          | Ah  |                 |              | Length X                 | Width Y | Height Z |                          | Yes   | No |                            |    |                    |
| FBC15KS, FBC18KS<br>38.5 x 18.5 x 32.25       | 36   | 18-D125-15   | 30.56        | 875 | 125             | 6045         | 38.1875                  | 17.8125 | 30.5625  | 2488                     |       | X  | B                          | 15 | SB6320             |
|   | 36   | 18-H120-15   | 29.33        | 840 | 120             | 6045         | 38.1875                  | 17.8125 | 30.5625  | 2463                     |       | X  | B                          | 15 | SB6320             |
|   | 36   | 18-P140-15   | 34.22        | 980 | 140             | 6045         | 38.1875                  | 17.8125 | 30.5625  | 2513                     |       | X  | B                          | 15 | SB6320             |
| FBC15KS, FBC18KS<br>38.5 x 16.25 x 32.25      | 36   | 18-D125-13   | 26.19        | 750 | 125             | 6005         | 37.8125                  | 15.5625 | 30.5625  | 2169                     |       | X  | B                          | 15 | SB6320             |
|   | 36   | 18-H120-13   | 25.14        | 720 | 120             | 6005         | 37.8125                  | 15.5625 | 30.5625  | 2147                     |       | X  | B                          | 15 | SB6320             |
|   | 36   | 18-P140-13   | 29.33        | 840 | 140             | 6005         | 37.8125                  | 15.5625 | 30.5625  | 2191                     |       | X  | B                          | 15 | SB6320             |
| FBC15KS, FBC18KS<br>38.5 x 13.5625 x 32.25    | 36   | 18-D125-11   | 21.83        | 625 | 125             | 6016         | 37.8125                  | 13.3125 | 30.5625  | 1853                     |       | X  | B                          | 15 | SB6320             |
|   | 36   | 18-H120-11   | 20.95        | 600 | 120             | 6016         | 37.8125                  | 13.3125 | 30.5625  | 1834                     |       | X  | B                          | 15 | SB6320             |
|   | 36   | 18-P140-11   | 24.44        | 700 | 140             | 6016         | 37.8125                  | 13.3125 | 30.5625  | 1872                     |       | X  | B                          | 15 | SB6320             |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## STAND-UP RIDERS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches)      | Volt | Battery<br>Type | 6 Hr. Rating |      | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) | Standard<br>Connector |        |
|--|------|-----------------|--------------|------|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|-----------------------|--------|
|  |      |                 | KWH          | Ah   |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |                       |        |
| FBC20KS<br>38.5 x 21.25 x 32.25                          | 36   | 18-D125-17      | 34.92        | 1000 | 125                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2837                           |       | X  | B                                 | 15                    | SB6320 |
|  | 36   | 18-H120-17      | 33.52        | 960  | 120                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2809                           |       | X  | B                                 | 15                    | SB6320 |
|  | 36   | 18-P140-17      | 39.11        | 1120 | 140                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2865                           |       | X  | B                                 | 15                    | SB6320 |
| FBC20KS<br>38.5 x 18.5 x 32.25                           | 36   | 18-D125-15      | 30.56        | 875  | 125                   | 6045               | 38.1875                  | 17.8125    | 30.5625     | 2488                           |       | X  | B                                 | 15                    | SB6320 |
|  | 36   | 18-H120-15      | 29.33        | 840  | 120                   | 6045               | 38.1875                  | 17.8125    | 30.5625     | 2463                           |       | X  | B                                 | 15                    | SB6320 |
|  | 36   | 18-P140-15      | 34.22        | 980  | 140                   | 6045               | 38.1875                  | 17.8125    | 30.5625     | 2513                           |       | X  | B                                 | 15                    | SB6320 |
| FBC25KS<br>38.5 x 23.75 x 32.25                          | 36   | 18-D125-19      | 39.29        | 1125 | 125                   | 6089               | 38.1875                  | 22.3125    | 30.5625     | 3126                           |       | X  | B                                 | 15                    | SB6320 |
|  | 36   | 18-H120-19      | 37.71        | 1080 | 120                   | 6089               | 38.1875                  | 22.3125    | 30.5625     | 3095                           |       | X  | B                                 | 15                    | SB6320 |
|  | 36   | 18-P140-19      | 44.00        | 1260 | 140                   | 6089               | 38.1875                  | 22.3125    | 30.5625     | 3157                           |       | X  | B                                 | 15                    | SB6320 |
| FBC15NS, FBC18NS<br>38.5625 x 14.25 x 31.6875            | 36   | 18-D125-11      | 21.83        | 625  | 125                   | 6016               | 37.8125                  | 13.3125    | 30.5625     | 1853                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-H120-11      | 20.95        | 600  | 120                   | 6016               | 37.8125                  | 13.3125    | 30.5625     | 1834                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-P140-11      | 24.44        | 700  | 140                   | 6016               | 37.8125                  | 13.3125    | 30.5625     | 1872                           |       | X  | C                                 | 20                    | SB6320 |
| FBC15NS, FBC18NS<br>38.625 x 16.25 x 31.75               | 36   | 18-D125-13      | 26.19        | 750  | 125                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2169                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-H120-13      | 25.14        | 720  | 120                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2147                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-P140-13      | 29.33        | 840  | 140                   | 6005               | 37.8125                  | 15.5625    | 30.5625     | 2191                           |       | X  | C                                 | 20                    | SB6320 |
| FBC15NS, FBC18NS<br>FBC20NS<br>38.5625 x 18.25 x 31.6875 | 36   | 18-D125-15      | 30.56        | 875  | 125                   | 6045               | 38.1875                  | 17.8125    | 30.5625     | 2488                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-H120-15      | 29.33        | 840  | 120                   | 6045               | 38.1875                  | 17.8125    | 30.5625     | 2463                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-P140-15      | 34.22        | 980  | 140                   | 6045               | 38.1875                  | 17.8125    | 30.5625     | 2513                           |       | X  | C                                 | 20                    | SB6320 |
| FBC20NS<br>38.625 x 21.25 x 31.75                        | 36   | 18-D125-17      | 34.92        | 1000 | 125                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2837                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-H120-17      | 33.52        | 960  | 120                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2809                           |       | X  | C                                 | 20                    | SB6320 |
|  | 36   | 18-P140-17      | 39.11        | 1120 | 140                   | 6069               | 38.1875                  | 20.0625    | 30.5625     | 2865                           |       | X  | C                                 | 20                    | SB6320 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

## SIT DOWN RIDERS

| Truck Model and<br>Maximum Battery Size<br>(Inches) | Volt | Battery<br>Type | 6 Hr. Rating |     | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) | Standard<br>Connector |        |
|---|------|-----------------|--------------|-----|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|-----------------------|--------|
|   |      |                 | KWH          | Ah  |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |                       |        |
| FEF2000, FEF2500                                    | 24   | 12-D85-19       | 17.81        | 765 | 85                    | 3096               | 38.0625                  | 14.875     | 22.625      | 1494                           |       | X  | B                                 | 18                    | SB6322 |
| FET2000-10C, FET2000-13C                            | 24   | 12-H80-19       | 16.76        | 720 | 80                    | 3096               | 38.0625                  | 14.875     | 22.625      | 1434                           |       | X  | B                                 | 18                    | SB6322 |
| FET2500-10C, FET2500-13C<br>39.25 x 15.5 x 25.5     | 24   | 12-P95-19       | 19.90        | 855 | 95                    | 3096               | 38.0625                  | 14.875     | 22.625      | 1509                           |       | X  | B                                 | 18                    | SB6322 |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are  $\pm 1/16"$ . Battery weights may vary  $\pm 5\%$ . Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.



## SIT DOWN RIDERS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches) | Volt | Battery<br>Type | 6 Hr. Rating |      | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) |    | Standard<br>Connector |
|---|------|-----------------|--------------|------|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|----|-----------------------|
|   |      |                 | KWH          | Ah   |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |    |                       |
| FEF3000, FEF3500                                    | 24   | 12-D85-25       | 23.75        | 1020 | 85                    | 3076               | 38.1875                  | 19.5       | 22.6875     | 1970                           |       | X  | B                                 | 18 | SB6322                |
| FET3000-15C, FET3000-18C                            | 24   | 12-H80-25       | 22.35        | 960  | 80                    | 3076               | 38.1875                  | 19.5       | 22.6875     | 1891                           |       | X  | B                                 | 18 | SB6322                |
| FET3500-15C, FET3500-18C<br>39.25 x 21.375 x 25.5   | 24   | 12-P95-25       | 26.54        | 1140 | 95                    | 3076               | 38.1875                  | 19.5       | 22.6875     | 1990                           |       | X  | B                                 | 18 | SB6322                |
| FB15P<br>38.375 x 26.375 x 18.6875                  | 48   | 24-D55-15       | 17.93        | 385  | 55                    | 7033               | 38.1875                  | 23.5625    | 18.1875     | 1761                           |       | X  | B                                 | 18 | SB6325                |
| FB20P, FB25P<br>38.375 x 29 x 23.0625               | 48   | 24-D85-17       | 31.66        | 680  | 85                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2705                           |       | X  | B                                 | 18 | SB6321                |
|   | 48   | 24-H80-17       | 29.80        | 640  | 80                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2597                           |       | X  | B                                 | 18 | SB6321                |
|   | 48   | 24-P95-17       | 35.39        | 760  | 95                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2732                           |       | X  | B                                 | 18 | SB6321                |
| FE3000LB, FE4000LB                                  | 36   | 18-D85-23       | 32.65        | 935  | 85                    | 6009               | 38.1875                  | 26.9375    | 22.6875     | 2715                           |       | X  | B                                 | 18 | SB6320                |
| FE5000LB  | 36   | 18-H80-23       | 30.73        | 880  | 80                    | 6009               | 38.1875                  | 26.9375    | 22.6875     | 2606                           |       | X  | B                                 | 18 | SB6320                |
| 39.25 x 28 x 23.125                                 | 36   | 18-P95-23       | 36.49        | 1045 | 95                    | 6009               | 38.1875                  | 26.9375    | 22.6875     | 2742                           |       | X  | B                                 | 18 | SB6320                |
| FE3000LB, FE4000LB                                  | 48   | 24-D85-17       | 31.66        | 680  | 85                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2705                           |       | X  | B                                 | 18 | SB6321                |
| FE5000LB  | 48   | 24-H80-17       | 29.80        | 640  | 80                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2597                           |       | X  | B                                 | 18 | SB6321                |
| 39.25 x 28 x 23.125                                 | 48   | 24-P95-17       | 35.39        | 760  | 95                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2732                           |       | X  | B                                 | 18 | SB6321                |
| FE15C, FE20C, FE25C                                 | 36   | 18-D85-23       | 32.65        | 935  | 85                    | 6009               | 38.1875                  | 26.9375    | 22.6875     | 2715                           |       | X  | B                                 | 18 | SB6320                |
| 39.1875 x 28 x 23.25                                | 36   | 18-H80-23       | 30.73        | 880  | 80                    | 6009               | 38.1875                  | 26.9375    | 22.6875     | 2606                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-P95-23       | 36.49        | 1045 | 95                    | 6009               | 38.1875                  | 26.9375    | 22.6875     | 2742                           |       | X  | B                                 | 18 | SB6320                |
| FE15C, FE20C, FE25C                                 | 48   | 24-D85-17       | 31.66        | 680  | 85                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2705                           |       | X  | B                                 | 18 | SB6320                |
| 39.1875 x 28 x 23.25                                | 48   | 24-H80-17       | 29.80        | 640  | 80                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2597                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-P95-17       | 35.39        | 760  | 95                    | 7002               | 38.1875                  | 26.6875    | 22.6875     | 2732                           |       | X  | B                                 | 18 | SB6320                |
| FE6000LB  | 72   | 36-D85-13       | 35.62        | 510  | 85                    | 8002               | 37.8125                  | 30.6875    | 22.6875     | 3059                           |       | X  | B                                 | 30 | SB6320                |
| 39.25 x 33.25 x 23.125                              | 72   | 36-H80-13       | 33.52        | 480  | 80                    | 8002               | 37.8125                  | 30.6875    | 22.6875     | 2937                           |       | X  | B                                 | 30 | SB6320                |
|   | 72   | 36-P95-13       | 39.81        | 570  | 95                    | 8002               | 37.8125                  | 30.6875    | 22.6875     | 3090                           |       | X  | B                                 | 30 | SB6320                |
| FE30C   | 36   | 18-D85-27       | 38.59        | 1105 | 85                    | 6026               | 38.1875                  | 31.4375    | 22.6875     | 3149                           |       | X  | B                                 | 18 | SB6320                |
| 39.1875 x 33.6875 x 23.25                           | 36   | 18-H80-27       | 36.32        | 1040 | 80                    | 6026               | 38.1875                  | 31.4375    | 22.6875     | 3023                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-P95-27       | 43.13        | 1235 | 95                    | 6026               | 38.1875                  | 31.4375    | 22.6875     | 3180                           |       | X  | B                                 | 18 | SB6320                |
| FE30C   | 48   | 24-D85-21       | 39.58        | 850  | 85                    | 7004               | 38.1875                  | 32.6875    | 22.6875     | 3295                           |       | X  | B                                 | 18 | SB6320                |
| 39.1875 x 33.6875 x 23.25                           | 48   | 24-H80-21       | 37.25        | 800  | 80                    | 7004               | 38.1875                  | 32.6875    | 22.6875     | 3163                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-P95-21       | 44.23        | 950  | 95                    | 7004               | 38.1875                  | 32.6875    | 22.6875     | 3328                           |       | X  | B                                 | 18 | SB6320                |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are  $\pm 1/16"$ . Battery weights may vary  $\pm 5\%$ . Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## SIT DOWN RIDERS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches)   | Volt | Battery<br>Type | 6 Hr. Rating |      | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) |    | Standard<br>Connector |
|---|------|-----------------|--------------|------|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|----|-----------------------|
|   |      |                 | KWH          | Ah   |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |    |                       |
| FBC15<br>36.375 x 26.6875 x 22.6875   | 36   | 18-D85-19       | 26.71        | 765  | 85                    | 6226               | 34.9375                  | 25.5625    | 22.6875     | 2284                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-H80-19       | 25.14        | 720  | 80                    | 6226               | 34.9375                  | 25.5625    | 22.6875     | 2193                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-P95-19       | 29.86        | 855  | 95                    | 6226               | 34.9375                  | 25.5625    | 22.6875     | 2307                           |       | X  | B                                 | 18 | SB6320                |
| FBC15<br>36.375 x 26.6875 x 22.6875   | 48   | 24-D85-15       | 27.70        | 595  | 85                    | 7049               | 35.1875                  | 25.5625    | 22.6875     | 2338                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-H80-15       | 26.07        | 560  | 80                    | 7049               | 35.1875                  | 25.5625    | 22.6875     | 2244                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-P95-15       | 30.96        | 665  | 95                    | 7049               | 35.1875                  | 25.5625    | 22.6875     | 2361                           |       | X  | B                                 | 18 | SB6320                |
| FBC20, FBC20K, FBC25<br>FBC25K<br>39.9375 x 30.5625 x 22.6875   | 36   | 18-D85-25       | 35.62        | 1020 | 85                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2924                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-H80-25       | 33.52        | 960  | 80                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2807                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-P95-25       | 39.81        | 1140 | 95                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2953                           |       | X  | B                                 | 18 | SB6320                |
| FBC20, FBC20K, FBC25<br>FBC25K<br>39.9375 x 30.5625 x 22.6875   | 48   | 24-D85-19       | 35.62        | 765  | 85                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 2970                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-H80-19       | 33.52        | 720  | 80                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 2851                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-P95-19       | 39.81        | 855  | 95                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 3000                           |       | X  | B                                 | 18 | SB6320                |
| FBC25, FBC30<br>40.6875 x 36.6875 x 22.6875   | 36   | 18-D85-31       | 44.52        | 1275 | 85                    | 6164               | 38.1875                  | 35.9375    | 22.6875     | 3603                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-H80-31       | 41.90        | 1200 | 80                    | 6164               | 38.1875                  | 35.9375    | 22.6875     | 3459                           |       | X  | B                                 | 18 | SB6320                |
|   | 36   | 18-P95-31       | 49.76        | 1425 | 95                    | 6164               | 38.1875                  | 35.9375    | 22.6875     | 3639                           |       | X  | B                                 | 18 | SB6320                |
| FBC25, FBC30<br>40.6875 x 36.6875 x 22.6875   | 48   | 24-D85-23       | 43.53        | 935  | 85                    | 7059               | 38.1875                  | 35.6875    | 22.6875     | 3573                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-H80-23       | 40.97        | 880  | 80                    | 7059               | 38.1875                  | 35.6875    | 22.6875     | 3430                           |       | X  | B                                 | 18 | SB6320                |
|   | 48   | 24-P95-23       | 48.66        | 1045 | 95                    | 7059               | 38.1875                  | 35.6875    | 22.6875     | 3609                           |       | X  | B                                 | 18 | SB6320                |
| 2FBC15, 2FBC18, FBC15<br>FBC15K, FBC15N, FBC18<br>FBC18K, FBC18KL, FBC18LN<br>FBC18N<br>35.6875 x 27.6875 x 23.25 | 36   | 18-D85-19       | 26.71        | 765  | 85                    | 6226               | 34.9375                  | 25.5625    | 22.6875     | 2284                           |       | X  | B                                 | 24 | SB6320                |
|   | 36   | 18-H80-19       | 25.14        | 720  | 80                    | 6226               | 34.9375                  | 25.5625    | 22.6875     | 2193                           |       | X  | B                                 | 24 | SB6320                |
|   | 36   | 18-P95-19       | 29.86        | 855  | 95                    | 6226               | 34.9375                  | 25.5625    | 22.6875     | 2307                           |       | X  | B                                 | 24 | SB6320                |
| 2FBC15, 2FBC18, FBC15<br>FBC15K, FBC15N, FBC18<br>FBC18K, FBC18KL, FBC18LN<br>FBC18N<br>35.6875 x 27.6875 x 23.25 | 48   | 24-D85-15       | 27.70        | 595  | 85                    | 7049               | 35.1875                  | 25.5625    | 22.6875     | 2338                           |       | X  | B                                 | 24 | SB6321                |
|   | 48   | 24-H80-15       | 26.07        | 560  | 80                    | 7049               | 35.1875                  | 25.5625    | 22.6875     | 2244                           |       | X  | B                                 | 24 | SB6321                |
|   | 48   | 24-P95-15       | 30.96        | 665  | 95                    | 7049               | 35.1875                  | 25.5625    | 22.6875     | 2361                           |       | X  | B                                 | 24 | SB6321                |
| 2FBC20, FBC20, FBC20K<br>FBC20N, FBC25N<br>38.875 x 30.5 x 23.25  | 36   | 18-D85-25       | 35.62        | 1020 | 85                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2924                           |       | X  | B                                 | 24 | SB6320                |
|   | 36   | 18-H80-25       | 33.52        | 960  | 80                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2807                           |       | X  | B                                 | 24 | SB6320                |
|   | 36   | 18-P95-25       | 39.81        | 1140 | 95                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2953                           |       | X  | B                                 | 24 | SB6320                |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## SIT DOWN RIDERS (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches)           | Volt | Battery<br>Type | 6 Hr. Rating |      | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) |    | Standard<br>Connector |
|---|------|-----------------|--------------|------|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|----|-----------------------|
|   |      |                 | KWH          | Ah   |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |    |                       |
| 2FBC20, FBC20, FBC20K   | 48   | 24-D85-19       | 35.62        | 765  | 85                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 2970                           |       | X  | B                                 | 24 | SB6321                |
| FBC20N, FBC25N  | 48   | 24-H80-19       | 33.52        | 720  | 80                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 2851                           |       | X  | B                                 | 24 | SB6321                |
| 38.875 x 30.5 x 23.25   | 48   | 24-P95-19       | 39.81        | 855  | 95                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 3000                           |       | X  | B                                 | 24 | SB6321                |
| 2FBC25, FBC25   | 36   | 18-D85-25       | 35.62        | 1020 | 85                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2924                           |       | X  | B                                 | 24 | SB6320                |
| 38.875 x 30.5 x 23.25   | 36   | 18-H80-25       | 33.52        | 960  | 80                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2807                           |       | X  | B                                 | 24 | SB6320                |
| Min. Battery Wt. - 2900 lbs.                                  | 36   | 18-P95-25       | 39.81        | 1140 | 95                    | 6030               | 38.1875                  | 29.1875    | 22.6875     | 2953                           |       | X  | B                                 | 24 | SB6320                |
| 2FBC25, FBC25   | 48   | 24-D85-19       | 35.62        | 765  | 85                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 2970                           |       | X  | B                                 | 24 | SB6321                |
| 38.875 x 30.5 x 23.25   | 48   | 24-H80-19       | 33.52        | 720  | 80                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 2851                           |       | X  | B                                 | 24 | SB6321                |
| Min. Battery Wt. - 2900 lbs.                                  | 48   | 24-P95-19       | 39.81        | 855  | 95                    | 7003               | 38.1875                  | 29.6875    | 22.6875     | 3000                           |       | X  | B                                 | 24 | SB6321                |
| 2FBC25E, 2FBC25KE   | 36   | 18-D85-29       | 41.55        | 1190 | 85                    | 6021               | 38.1875                  | 33.6875    | 22.6875     | 3392                           |       | X  | B                                 | 24 | SB6320                |
| 2FBC30, FBC25, FBC25E   | 36   | 18-H80-29       | 39.11        | 1120 | 80                    | 6021               | 38.1875                  | 33.6875    | 22.6875     | 3256                           |       | X  | B                                 | 24 | SB6320                |
| FBC25EN, FBC25KE  | 36   | 18-P95-29       | 46.44        | 1330 | 95                    | 6021               | 38.1875                  | 33.6875    | 22.6875     | 3426                           |       | X  | B                                 | 24 | SB6320                |
| FBC25KL, FBC25LN, FBC30<br>FBC30K, FBC30KL, FBC30LN<br>FBC30N |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| 38.875 x 34.375 x 23.25<br>Min. Battery Wt. - 3100 lbs.       |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| 2FBC25E, 2FBC25KE   | 48   | 24-D85-21       | 39.58        | 850  | 85                    | 7004               | 38.1875                  | 32.6875    | 22.6875     | 3295                           |       | X  | B                                 | 24 | SB6321                |
| 2FBC30, FBC25, FBC25E   | 48   | 24-H80-21       | 37.25        | 800  | 80                    | 7004               | 38.1875                  | 32.6875    | 22.6875     | 3163                           |       | X  | B                                 | 24 | SB6321                |
| FBC25EN, FBC25KE  | 48   | 24-P95-21       | 44.23        | 950  | 95                    | 7004               | 38.1875                  | 32.6875    | 22.6875     | 3328                           |       | X  | B                                 | 24 | SB6321                |
| FBC25KL, FBC25LN, FBC30<br>FBC30K, FBC30KL, FBC30LN<br>FBC30N |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| 38.875 x 34.375 x 23.25<br>Min. Battery Wt. - 3100 lbs.       |      |                 |              |      |                       |                    |                          |            |             |                                |       |    |                                   |    |                       |
| FBC35N, FBC40N, FBC45N  | 36   | 18-D85-33       | 47.49        | 1360 | 85                    | 6818               | 40                       | 40         | 22.6875     | 3766                           |       | X  | B                                 | 30 | SB6320                |
| FBC55N  | 36   | 18-D85-33       | 47.49        | 1360 | 85                    | 6065               | 38.1875                  | 38.1875    | 22.6875     | 3887                           |       | X  | B                                 | 30 | SB6320                |
| 46.125 x 40.625 x 24.3125                                     | 36   | 18-H80-33       | 44.70        | 1280 | 80                    | 6818               | 40                       | 40         | 22.6875     | 3615                           |       | X  | B                                 | 30 | SB6320                |
| Min. Battery Wt. - 3600 lbs.                                  | 36   | 18-H80-33       | 44.70        | 1280 | 80                    | 6065               | 38.1875                  | 38.1875    | 22.6875     | 3732                           |       | X  | B                                 | 30 | SB6320                |
|   | 36   | 18-P95-33       | 53.08        | 1520 | 95                    | 6818               | 40                       | 40         | 22.6875     | 3804                           |       | X  | B                                 | 30 | SB6320                |
|   | 36   | 18-P95-33       | 53.08        | 1520 | 95                    | 6065               | 38.1875                  | 38.1875    | 22.6875     | 3926                           |       | X  | B                                 | 30 | SB6320                |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

## SIT DOWN RIDERS (continued)

| Truck Model and Maximum Battery Size (Inches)             | Volt | Battery Type | 6 Hr. Rating |      | Plate Rating Ah | IST Tray No. | Battery Dimensions (in.) |         |          | Approx. Serv. Wt. (lbs.) | Cover |    | Position/Lead Length (in.) | Standard Connector |
|---|------|--------------|--------------|------|-----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|----------------------------|--------------------|
|   |      |              | KWH          | Ah   |                 |              | Length X                 | Width Y | Height Z |                          | Yes   | No |                            |                    |
| FBC35N, FBC40N, FBC45N                                    | 48   | 24-D85-29    | 55.41        | 1190 | 85              | 7067         | 44.6875                  | 38.1875 | 22.6875  | 4497                     |       | X  | B 30                       | SB6321             |
| FBC55N  | 48   | 24-H80-29    | 52.15        | 1120 | 80              | 7067         | 44.6875                  | 38.1875 | 22.6875  | 4317                     |       | X  | B 30                       | SB6321             |
| 46.125 x 40.625 x 24.3125<br>Min. Battery Wt. - 3600 lbs. | 48   | 24-P95-29    | 61.92        | 1330 | 95              | 7067         | 44.6875                  | 38.1875 | 22.6875  | 4542                     |       | X  | B 30                       | SB6321             |
| FBP20K  | 80   | 40-D125-9    | 38.80        | 500  | 125             | 9185         | 39.75                    | 26.75   | 30.5625  | 3447                     |       | X  | B 16                       | SB6320             |
| 40.75 x 28.3125 x 30.9375                                 | 80   | 40-H120-9    | 37.25        | 480  | 120             | 9185         | 39.75                    | 26.75   | 30.5625  | 3413                     |       | X  | B 16                       | SB6320             |
| Min. Battery Wt. - 3050 lbs.                              | 80   | 40-P140-9    | 43.46        | 560  | 140             | 9185         | 39.75                    | 26.75   | 30.5625  | 3481                     |       | X  | B 16                       | SB6320             |
| FBP30K, FBP35K  | 80   | 40-D125-13   | 58.20        | 750  | 125             | 9115         | 40.6875                  | 33.8125 | 30.5625  | 4760                     |       | X  | B 16                       | SB6320             |
| 40.75 x 33.9375 x 30.9375                                 | 80   | 40-H120-13   | 55.87        | 720  | 120             | 9115         | 40.6875                  | 33.8125 | 30.5625  | 4712                     |       | X  | B 16                       | SB6320             |
| Min. Battery Wt. - 4123 lbs.                              | 80   | 40-P140-13   | 65.18        | 840  | 140             | 9115         | 40.6875                  | 33.8125 | 30.5625  | 4808                     |       | X  | B 16                       | SB6320             |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

## SIT DOWN RIDERS - 3 WHEEL

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | 6 Hr. Rating |     | Plate Rating Ah | IST Tray No. | Battery Dimensions (in.) |         |          | Approx. Serv. Wt. (lbs.) | Cover |    | Position/Lead Length (in.) | Standard Connector |
|---|------|--------------|--------------|-----|-----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|----------------------------|--------------------|
|   |      |              | KWH          | Ah  |                 |              | Length X                 | Width Y | Height Z |                          | Yes   | No |                            |                    |
| FET10, FET13                                  | 36   | 18-D85-13    | 17.81        | 510 | 85              | 6062         | 37.6875                  | 15.4375 | 22.625   | 1507                     |       | X  | B 18                       | SB6320             |
| 39.3125 x 16.125 x 25.5                       | 36   | 18-H80-13    | 16.76        | 480 | 80              | 6062         | 37.6875                  | 15.4375 | 22.625   | 1447                     |       | X  | B 18                       | SB6320             |
|   | 36   | 18-P95-13    | 19.90        | 570 | 95              | 6062         | 37.6875                  | 15.4375 | 22.625   | 1522                     |       | X  | B 18                       | SB6320             |
| FET15, FET18                                  | 36   | 18-D85-19    | 26.71        | 765 | 85              | 6041         | 38.1875                  | 22.3125 | 22.6875  | 2242                     |       | X  | B 18                       | SB6320             |
| 39.3125 x 22.8125 x 25.5                      | 36   | 18-H80-19    | 25.14        | 720 | 80              | 6041         | 38.1875                  | 22.3125 | 22.6875  | 2152                     |       | X  | B 18                       | SB6320             |
|   | 36   | 18-P95-19    | 29.86        | 855 | 95              | 6041         | 38.1875                  | 22.3125 | 22.6875  | 2264                     |       | X  | B 18                       | SB6320             |
| FBS15   | 36   | 18-D85-17    | 23.75        | 680 | 85              | 6015         | 38.1875                  | 20.0625 | 22.6875  | 2041                     |       | X  | D 30                       | SB6320             |
| 39.5625 x 20.75 x 24.5625                     | 36   | 18-H80-17    | 22.35        | 640 | 80              | 6015         | 38.1875                  | 20.0625 | 22.6875  | 1959                     |       | X  | D 30                       | SB6320             |
|   | 36   | 18-P95-17    | 26.54        | 760 | 95              | 6015         | 38.1875                  | 20.0625 | 22.6875  | 2061                     |       | X  | D 30                       | SB6320             |
| FB16PNT                                       | 36   | 18-D85-17    | 23.75        | 680 | 85              | 6E75         | 39.0625                  | 20.25   | 22.6875  | 2032                     |       | X  | B 20                       | SB6320             |
| 39.5625 x 20.75 x 24.75                       | 36   | 18-H80-17    | 22.35        | 640 | 80              | 6E75         | 39.0625                  | 20.25   | 22.6875  | 1951                     |       | X  | B 20                       | SB6320             |
|   | 36   | 18-P95-17    | 26.54        | 760 | 95              | 6E75         | 39.0625                  | 20.25   | 22.6875  | 2052                     |       | X  | B 20                       | SB6320             |
| FB16PNT                                       | 48   | 24-D85-13    | 23.75        | 510 | 85              | 7071         | 38.125                   | 20.4375 | 22.6875  | 2015                     |       | X  | B 20                       | SB6320             |
| 39.5625 x 20.75 x 24.75                       | 48   | 24-H80-13    | 22.35        | 480 | 80              | 7071         | 38.125                   | 20.4375 | 22.6875  | 1934                     |       | X  | B 20                       | SB6320             |
|   | 48   | 24-P95-13    | 26.54        | 570 | 95              | 7071         | 38.125                   | 20.4375 | 22.6875  | 2035                     |       | X  | B 20                       | SB6320             |

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are  $\pm 1/16"$ . Battery weights may vary  $\pm 5\%$ . Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

### SIT DOWN RIDERS - 3 WHEEL (continued)

| Truck Model and<br>Maximum Battery Size<br>(Inches) | Volt | Battery<br>Type | 6 Hr. Rating |     | Plate<br>Rating<br>Ah | IST<br>Tray<br>No. | Battery Dimensions (in.) |            |             | Approx.<br>Serv. Wt.<br>(lbs.) | Cover |    | Position/<br>Lead Length<br>(in.) | Standard<br>Connector |        |
|---|------|-----------------|--------------|-----|-----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------------------------|-----------------------|--------|
|   |      |                 | KWH          | Ah  |                       |                    | Length<br>X              | Width<br>Y | Height<br>Z |                                | Yes   | No |                                   |                       |        |
| FB18PNT, FB20PNT<br>39.5625 x 25.0625 x 24.75       | 36   | 18-D85-21       | 29.68        | 850 | 85                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2484                           |       | X  | B                                 | 20                    | SB6320 |
|   | 36   | 18-H80-21       | 27.94        | 800 | 80                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2385                           |       | X  | B                                 | 20                    | SB6320 |
|   | 36   | 18-P95-21       | 33.17        | 950 | 95                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2509                           |       | X  | B                                 | 20                    | SB6320 |
| FB18PNT, FB20PNT<br>39.5625 x 25.0625 x 24.75       | 48   | 24-D85-15       | 27.70        | 595 | 85                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2340                           |       | X  | B                                 | 20                    | SB6320 |
|   | 48   | 24-H80-15       | 26.07        | 560 | 80                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2246                           |       | X  | B                                 | 20                    | SB6320 |
|   | 48   | 24-P95-15       | 30.96        | 665 | 95                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2363                           |       | X  | B                                 | 20                    | SB6320 |
| FBS15<br>39.5625 x 20.75 x 24.5625                  | 48   | 24-D85-13       | 23.75        | 510 | 85                    | 7017               | 37.8125                  | 20.5625    | 22.6875     | 2038                           |       | X  | D                                 | 30                    | SB6321 |
|   | 48   | 24-H80-13       | 22.35        | 480 | 80                    | 7017               | 37.8125                  | 20.5625    | 22.6875     | 1956                           |       | X  | D                                 | 30                    | SB6321 |
|   | 48   | 24-P95-13       | 26.54        | 570 | 95                    | 7017               | 37.8125                  | 20.5625    | 22.6875     | 2058                           |       | X  | D                                 | 30                    | SB6321 |
| FBS18, FBS20<br>39.5625 x 25 x 24.5625              | 36   | 18-D85-21       | 29.68        | 850 | 85                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2484                           |       | X  | D                                 | 30                    | SB6320 |
|   | 36   | 18-H80-21       | 27.94        | 800 | 80                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2385                           |       | X  | D                                 | 30                    | SB6320 |
|   | 36   | 18-P95-21       | 33.17        | 950 | 95                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2509                           |       | X  | D                                 | 30                    | SB6320 |
| FBS18, FBS20<br>39.5625 x 25 x 24.5625              | 48   | 24-D85-15       | 27.70        | 595 | 85                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2340                           |       | X  | D                                 | 30                    | SB6321 |
|   | 48   | 24-H80-15       | 26.07        | 560 | 80                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2246                           |       | X  | D                                 | 30                    | SB6321 |
|   | 48   | 24-P95-15       | 30.96        | 665 | 95                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2363                           |       | X  | D                                 | 30                    | SB6321 |
| FB16KT, FB16NT<br>40 x 20.875 x 24.75               | 36   | 18-D85-17       | 23.75        | 680 | 85                    | 6015               | 38.1875                  | 20.0625    | 22.6875     | 2041                           |       | X  | B                                 | 20                    | SB6320 |
|   | 36   | 18-H80-17       | 22.35        | 640 | 80                    | 6015               | 38.1875                  | 20.0625    | 22.6875     | 1959                           |       | X  | B                                 | 20                    | SB6320 |
|   | 36   | 18-P95-17       | 26.54        | 760 | 95                    | 6015               | 38.1875                  | 20.0625    | 22.6875     | 2061                           |       | X  | B                                 | 20                    | SB6320 |
| FB16KT, FB16NT<br>40 x 20.875 x 24.75               | 48   | 24-D85-13       | 23.75        | 510 | 85                    | 7017               | 37.8125                  | 20.5625    | 22.6875     | 2038                           |       | X  | B                                 | 20                    | SB6320 |
|   | 48   | 24-H80-13       | 22.35        | 480 | 80                    | 7017               | 37.8125                  | 20.5625    | 22.6875     | 1956                           |       | X  | B                                 | 20                    | SB6320 |
|   | 48   | 24-P95-13       | 26.54        | 570 | 95                    | 7017               | 37.8125                  | 20.5625    | 22.6875     | 2058                           |       | X  | B                                 | 20                    | SB6320 |
| FB18KT, FB18NT, FB20KT<br>FB20NT<br>40 x 25 x 24.75 | 36   | 18-D85-21       | 29.68        | 850 | 85                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2484                           |       | X  | B                                 | 20                    | SB6320 |
|   | 36   | 18-H80-21       | 27.94        | 800 | 80                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2385                           |       | X  | B                                 | 20                    | SB6320 |
|   | 36   | 18-P95-21       | 33.17        | 950 | 95                    | 6010               | 38.1875                  | 24.5625    | 22.6875     | 2509                           |       | X  | B                                 | 20                    | SB6320 |
| FB18KT, FB20KT, FB20NT<br>40 x 25 x 24.75           | 48   | 24-D85-15       | 27.70        | 595 | 85                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2340                           |       | X  | B                                 | 20                    | SB6320 |
|   | 48   | 24-H80-15       | 26.07        | 560 | 80                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2246                           |       | X  | B                                 | 20                    | SB6320 |
|   | 48   | 24-P95-15       | 30.96        | 665 | 95                    | 7031               | 38.1875                  | 23.5625    | 22.6875     | 2363                           |       | X  | B                                 | 20                    | SB6320 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

***EAST PENN manufacturing co., inc.***

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212  
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are  $\pm 1/16"$ . Battery weights may vary  $\pm 5\%$ . Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.