



INDUSTRIAL BATTERIES

NISSAN

WALKIE

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
WC-30, WC-40, WCN-20	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	20	SB6325
WCN-30, WCN-40, WPN-40	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	20	SB6325
WPN-60, WPN-80, WTTN	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	20	SB6325
32 x 8.25 x 31.125	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	20	SB6325
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	20	SB6325
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	20	SB6325
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	20	SB6325
DGN-24, DGN-24D, RPB-60	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6325
RPB-80, RPN-60, RPN-80	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6325
SGB, SGN-1-24	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6325
SGN-1-24-D, SGN-1-24-D-F	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6325
SGN-1-24-F, SGN-200	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6325
SGN-24, SGN-24D	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6325
SGN-24DF, SGN-2HF	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6325
SGXN-60, SGXN-80															
SHGN-1-24, SHGN-1-24-F															
SHGN-24F, SHGN-29, SPB60															
SPB80, SPN-60, SPN-80															
WC-30, WC-40, WCN-30															
WCN-40, WPB-60, WPB-80															
WPN-40, WPN-60, WPN-80															
WRPN-40, WRPN-60															
WRPN-80															
32 x 13.5 x Open															

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
WC-40, WS-30, WSN-30	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	20	SB6325
WSN-40	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	20	SB6325
34.5 x 8.25 x 31.125	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	20	SB6325
	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	20	SB6325
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	20	SB6325
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	20	SB6325
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	20	SB6325
WS-30, WS-40, WSN-30	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6325
WSN-40	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6325
34.5 x 13.5 x 31.125	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6325
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6325
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6325
EWPN-45	12	6-D85-11	4.95	425	85	1087	25.875	7.75	23.1875	455	X		B	20	SB6325
28.25 x 9 x Open	12	6-H80-11	4.66	400	80	1087	25.875	7.75	23.1875	437	X		B	20	SB6325
	12	6-P95-11	5.53	475	95	1087	25.875	7.75	23.1875	460	X		B	20	SB6325
EWPN-45	24	12-D100-7	6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	20	SB6325
28.25 x 9 x Open	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	20	SB6325
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	20	SB6325
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	20	SB6325
WSRN-30	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6329
32.25 x 13 x Open	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6329
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6329
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6329
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6329
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6329
EWSN-20, EWSN-25	24	12-D125-7	8.73	375	125	3329	25.3125	8.5625	31.0625	792	X		B	15	SB6329
27.375 x 9 x Open	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	15	SB6329
	24	12-H120-7	8.38	360	120	3329	25.3125	8.5625	31.0625	784	X		B	15	SB6329
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	15	SB6329
	24	12-P140-7	9.78	420	140	3329	25.3125	8.5625	31.0625	800	X		B	15	SB6329
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	15	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
WSN-30, WSN-40 30.875 x 8.25 x 31	12	6-D85-13	5.94	510	85	1013	30.5	7.75	23.1875	533	X		B	20	SB6325
	12	6-H80-13	5.59	480	80	1013	30.5	7.75	23.1875	512	X		B	20	SB6325
	12	6-P95-13	6.63	570	95	1013	30.5	7.75	23.1875	538	X		B	20	SB6325
EWP2-45 28.5 x 9 x Open	24	12-D85-7	5.94	255	85	3373	27.875	8.875	23.25	598	X		B	20	SB6329
	24	12-H80-7	5.59	240	80	3373	27.875	8.875	23.25	574	X		B	20	SB6329
	24	12-P95-7	6.63	285	95	3373	27.875	8.875	23.25	604	X		B	20	SB6329
WRPN-40, WRPN-60 WRPN-80, WSN-30, WSN-40 30.875 x 13.5 x 31	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6325
EWP2-45 31.25 x 9 x 24	24	12-D85-7	5.94	255	85	3487	29.1875	8.5625	23.1875	590	X		B	20	SB6325
	24	12-H80-7	5.59	240	80	3487	29.1875	8.5625	23.1875	566	X		B	20	SB6325
	24	12-P95-7	6.63	285	95	3487	29.1875	8.5625	23.1875	596	X		B	20	SB6325

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

PLATINUM 4-WHEEL SIT DOWN RIDER (CUSHION TIRE)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
BX30, BX35 35.1875 x 26.75 x 23.4375	36	18-D85-17	23.75	680	85	6001	33.1875	25.5625	22.6875	2090		X	B	18	SB6320
	36	18-H80-17	22.35	640	80	6001	33.1875	25.5625	22.6875	2006		X	B	18	SB6320
	36	18-P95-17	26.54	760	95	6001	33.1875	25.5625	22.6875	2111		X	B	18	SB6320
BX30, BX35 35.1875 x 26.75 x 23.4375	48	24-D85-13	23.75	510	85	7007	30.6875	25.3125	22.6875	2033		X	B	18	SB6320
	48	24-H80-13	22.35	480	80	7007	30.6875	25.3125	22.6875	1952		X	B	18	SB6320
	48	24-P95-13	26.54	570	95	7007	30.6875	25.3125	22.6875	2053		X	B	18	SB6320
BX40, BX50, BX50EE 39.125 x 28.3125 x 23.4375	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	18	SB6320
	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	18	SB6320
	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	18	SB6320
BX40, BX50, BX50EE 39.125 x 28.3125 x 23.4375	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	18	SB6320
	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	18	SB6320
	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

PLATINUM 4-WHEEL SIT DOWN RIDER (CUSHION TIRE) (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
BX50L, BX60 39.125 x 34.1875 x 23.4375	36	18-D85-29	41.55	1190	85	6021	38.1875	33.6875	22.6875	3394		X	B	18	SB6320	
	36	18-H80-29	39.11	1120	80	6021	38.1875	33.6875	22.6875	3258		X	B	18	SB6320	
	36	18-P95-29	46.44	1330	95	6021	38.1875	33.6875	22.6875	3428		X	B	18	SB6320	
BX50L, BX60 39.125 x 34.1875 x 23.4375	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	18	SB6320	
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	18	SB6320	
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	18	SB6320	
BX80 39.125 x 34.1875 x 23.4375 Min. Battery Wt. - 3351 lbs.	36	18-D85-29	41.55	1190	85	6021	38.1875	33.6875	22.6875	3394		X	B	18	SB6320	
	36	18-H80-29	39.11	1120	80	6021	38.1875	33.6875	22.6875	3258		X	B	18	SB6320	
	36	18-P95-29	46.44	1330	95	6021	38.1875	33.6875	22.6875	3428		X	B	18	SB6320	
BX80 39.125 x 34.1875 x 23.4375 Min. Battery Wt. - 3351 lbs.	48	24-D85-21	sp	39.58	850	85	7166	38.625	33.25	22.6875	3364		X	B	18	SB6320
	48	24-H80-21	sp	37.25	800	80	7166	38.625	33.25	22.6875	3229		X	B	18	SB6320
	48	24-P95-21	sp	44.23	950	95	7166	38.625	33.25	22.6875	3398		X	B	18	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

sp - Special tray IST7166 with steel added for minimum weight requirement.

PLATINUM 4-WHEEL SIT DOWN RIDER (PNEUMATIC TIRE)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
BXP30, BXP35 38.8125 x 26.375 x 18.5	48	24-D55-17	sp	20.49	440	55	7645	38.5625	26.4375	18.75	2035		X	B	25	SB6320
BXP30L, BXP35L, BXP40 BXP50 38.8125 x 33.875 x 18.5	48	24-D55-21	sp	25.61	550	55	7646	38.5625	33.8125	18.75	2538		X	B	25	SB6320
BXP40L, BXP50L 38.8125 x 39.9375 x 22.875	48	24-D85-25	sp	47.49	1020	85	7647	38.5625	38.6875	22.75	3807		X	B	25	SB6320
	48	24-H80-25	sp	44.70	960	80	7647	38.5625	38.6875	22.75	3655		X	B	25	SB6320
	48	24-P95-25	sp	53.08	1140	95	7647	38.5625	38.6875	22.75	3845		X	B	25	SB6320
BXP30S, BXP35S 38.8125 x 23.8125 x 18.75 Min. Battery Wt. - 1529 lbs.	48	24-D55-15		17.93	385	55	7644	38.5625	23.5625	18.5	1781		X	B	25	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

PLATINUM 4-WHEEL SIT DOWN RIDER (PNEUMATIC TIRE) (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
QX40, QX50 40.625 x 28.1875 x 31.625	80	40-D125-9	38.80	500	125	9384	40	27.5	30.5625	3357		X	A	16	SBE6359
	80	40-H120-9	37.25	480	120	9384	40	27.5	30.5625	3323		X	A	16	SBE6359
	80	40-P140-9	43.46	560	140	9384	40	27.5	30.5625	3391		X	A	16	SBE6359
QX50L, QX60 40.625 x 33.5 x 31.625	80	40-D125-11	48.50	625	125	9548	40.125	33	30.5625	3953		X	A	16	SBE6359
	80	40-H120-11	46.56	600	120	9548	40.125	33	30.5625	3913		X	A	16	SBE6359
	80	40-P140-11	54.32	700	140	9548	40.125	33	30.5625	3993		X	A	16	SBE6359

sp - Special tray with special lift lugs, gussets on corners, bracket and pin on sides for lock down.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

REACH STRADDLE TRUCKS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
OR 35, OR 40 38.75 x 13.375 x 32	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	B	14	SB6320
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	B	14	SB6320
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	B	14	SB6320
OR 35, OR 40 38.75 x 16.125 x 32	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	B	14	SB6320
	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	B	14	SB6320
	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	B	14	SB6320
OR 35, OR 40 38.75 x 13.875 x 32	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	20	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	20	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	20	SB6320
OR 35, OR 40 38.75 x 16.125 x 32	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	20	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	20	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	20	SB6320
OR 45, ORDR 30 38.75 x 16.125 x 32	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	14	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	14	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	14	SB6320
OR 45, ORDR 30 38.75 x 18.5 x 32	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	14	SB6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	14	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	14	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH STRADDLE TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
OR 45, ORDR 30 38.75 x 21 x 32	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	14	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	14	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	14	SB6320
RRN 35, RSN 40 38.75 x 16.375 x 32 Min. Battery Wt. - 2000 lbs.	24	12-D160-13 sp	22.35	960	160	3780	37.875	15.5625	30.5625	2113		X	C	15	SB6322
RRN 35, RSN 40 38.75 x 14.375 x 32 Min. Battery Wt. - 1600 lbs.	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	C	15	SB6322
RRN 35, RSN 40 38.75 x 14.375 x 32 Min. Battery Wt. - 1600 lbs.	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	C	15	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	C	15	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	C	15	SB6320
RRN 35, RRN 30D, RRN 45 RSN 40, RSN 50 38.75 x 16.375 x 32 Min. Battery Wt. - 2000 lbs.	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	C	15	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	C	15	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	C	15	SB6320
RRN 45, RRN 30D, RSN 50 38.75 x 20.875 x 32 Min. Battery Wt. - 2600 lbs.	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	C	15	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	C	15	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	C	15	SB6320
SCX-30SN 32.25 x 13.25 x Open	24	12-D125-13	17.46	750	125	3093	30.5625	12.75	30.5	1444		X	B	14	SB6320
	24	12-H120-13	16.76	720	120	3093	30.5625	12.75	30.5	1430		X	B	14	SB6320
	24	12-P140-13	19.56	840	140	3093	30.5625	12.75	30.5	1458		X	B	14	SB6320
OR-35, OR-40 38.875 x 13.375 x 32 Min. Battery Wt. - 2000 lbs. NEW TRAY REQUIRED												X	B	14	SB6320
OR-35, OR-40 38.875 x 13.375 x 32 Min. Battery Wt. - 2000 lbs. NEW TRAY REQUIRED												X	B	14	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH STRADDLE TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
OR-35, OR-40, OR-45	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	14	SB6320
ORDR-30, RRN-30D	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	14	SB6320
38.875 x 16.1875 x 32	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	14	SB6320
Min. Battery Wt. - 2000 lbs.															
SCX-30N												X	B	14	SB6320
38.5 x 16.25 x 32															
Min. Battery Wt. - 2175 lbs.															
NEW TRAY REQUIRED															
OR-45, ORDR-30, SCX-30N	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	14	SB6320
SCX-40N	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	14	SB6320
38.5 x 18.375 x 32	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	14	SB6320
Min. Battery Wt. - 2460 lbs.															
OR-45, ORDR-30, RRN-30D	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	14	SB6320
SCX-40N	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	14	SB6320
38.5 x 20.5 x 32	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	14	SB6320
Min. Battery Wt. - 2460 lbs.															

sp - Special tray IST3780 includes steel plates added for minimum weight requirement.
H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.
NEW TRAY REQUIRED - Contact East Penn Factory.

ORDER SELECTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
RCOSN 30	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	B	20	SB6322
38.75 x 14.5 x 31.5	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	20	SB6322
Min. Battery Wt. - 1200 lbs.	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	20	SB6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	20	SB6322
RCOSN 30	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	20	SB6320
38.75 x 14.5 x 31.5	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	20	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	20	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

ORDER SELECTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
OSN 30	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	C	15	SB6322
36.25 x 13.9375 x 31.5	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	C	15	SB6322
Min. Battery Wt. - 1650 lbs.	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	C	15	SB6322

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

STAND-UP RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
OS 25S, OS 30S	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	D	12	SB6320
38.75 x 13.875 x 32	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	D	12	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	D	12	SB6320
OS 30	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	D	12	SB6320
38.75 x 16.125 x 32	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	D	12	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	D	12	SB6320
OS 35	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	D	12	SB6320
38.75 x 18.375 x 32	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	D	12	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	D	12	SB6320
OS 40, OS 45, OS 50	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	D	12	SB6320
38.75 x 20.75 x 32	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	D	12	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	D	12	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.
blankblank

FOUR WHEEL SIT-DOWN RIDERS

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

FOUR WHEEL SIT-DOWN RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
E-2000, E-2500, E-3000	36	18-D85-17	23.75	680	85	6001	33.1875	25.5625	22.6875	2090		X	B	18	SB6320
E-3500, E20, E20YEE, E25	36	18-H80-17	22.35	640	80	6001	33.1875	25.5625	22.6875	2006		X	B	18	SB6320
E25YEE, E30, E35, PE20Y	36	18-P95-17	26.54	760	95	6001	33.1875	25.5625	22.6875	2111		X	B	18	SB6320
PE25Y, PE30Y, PE30YEE	36	18-D85-19	26.71	765	85	6226	34.9375	25.5625	22.6875	2274		X	B	18	SB6320
PE35Y, PE35YEE	36	18-H80-19	25.14	720	80	6226	34.9375	25.5625	22.6875	2183		X	B	18	SB6320
35.1875 x 26.6875 x 23.375	36	18-P95-19	29.86	855	95	6226	34.9375	25.5625	22.6875	2297		X	B	18	SB6320
See Note A															
E-2000, E-2500, E-3000	48	24-D85-13	23.75	510	85	7007	30.6875	25.3125	22.6875	2033		X	B	18	SB6320
E-3500, E20, E20YEE, E25	48	24-H80-13	22.35	480	80	7007	30.6875	25.3125	22.6875	1952		X	B	18	SB6320
E25YEE, E30, E35, PE20Y	48	24-P95-13	26.54	570	95	7007	30.6875	25.3125	22.6875	2053		X	B	18	SB6320
PE25Y, PE30Y, PE30YEE	48	24-D85-15	27.70	595	85	7049	35.1875	25.5625	22.6875	2332		X	B	18	SB6320
PE35Y, PE35YEE	48	24-H80-15	26.07	560	80	7049	35.1875	25.5625	22.6875	2239		X	B	18	SB6320
35.1875 x 26.6875 x 23.375	48	24-P95-15	30.96	665	95	7049	35.1875	25.5625	22.6875	2355		X	B	18	SB6320
See Note A															
E-4000, E-5000, E40, E50	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	B	18	SB6320
PE40Y, PE40YEE, PE50Y	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	B	18	SB6320
PE50YEE	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	B	18	SB6320
39.0625 x 28.25 x 23.375	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	18	SB6320
See Note A	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	18	SB6320
	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	18	SB6320
E-4000, E40, E50, E5000	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2332		X	B	18	SB6320
PE40Y, PE40YEE, PE50Y	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2239		X	B	18	SB6320
PE50YEE	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2355		X	B	18	SB6320
39.0625 x 28.25 x 23.375	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	18	SB6320
See Note A	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	18	SB6320
	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	18	SB6320
E-5500, E-6000, E5000L	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	18	SB6320
E50L, E50YEE, E55	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	18	SB6320
E55YEE, E60, E65, PE50LY	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	18	SB6320
PE60Y, PE60YEE	36	18-D85-29	41.55	1190	85	6021	38.1875	33.6875	22.6875	3394		X	B	18	SB6320
39.0625 x 34.8125 x 23.375	36	18-H80-29	39.11	1120	80	6021	38.1875	33.6875	22.6875	3258		X	B	18	SB6320
See Note A	36	18-P95-29	46.44	1330	95	6021	38.1875	33.6875	22.6875	3428		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

FOUR WHEEL SIT-DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
E5000L, E50L, E50YEE	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2984		X	B	18	SB6320
E55, E5500, E55YEE, E60	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2865		X	B	18	SB6320
E6000, E60YEE, E65	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3014		X	B	18	SB6320
PE50LY, PE60Y	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	18	SB6320
39.0625 x 34.1875 x 23.375	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	18	SB6320
See Note A	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	18	SB6320
ET-2000, MA01L10S	24	12-D100-17	18.62	800	100	3073	38.0625	13.375	25.625	1537		X	B	21	SB6320
39.0625 x 13.75 x 26.1875	24	12-D85-17	15.83	680	85	3135	38.125	13.375	22.625	1361		X	B	21	SB6320
	24	12-H80-17	14.90	640	80	3135	38.125	13.375	22.625	1307		X	B	21	SB6320
	24	12-P95-17	17.69	760	95	3135	38.125	13.375	22.625	1375		X	B	21	SB6320
ET-2500, ET-3000, ET25	24	12-D100-21	23.28	1000	100	3139	38.1875	16.5	25.6875	1910		X	B	21	SB6320
ET30, MA01L13S, MA01L15S	24	12-D85-21	19.79	850	85	3031	38.0625	16.375	22.625	1620		X	B	21	SB6320
39.0625 x 17.5 x 26.1875	24	12-H80-21	18.62	800	80	3031	38.0625	16.375	22.625	1555		X	B	21	SB6320
	24	12-P95-21	22.12	950	95	3031	38.0625	16.375	22.625	1636		X	B	21	SB6320
N30, N30C, N35, N35C	48	24-D85-13	23.75	510	85	7077	37.8125	20.5625	23.5625	2100	X		B	21	SB6320
39.1875 x 20.875 x 25.8125	48	24-H80-13	22.35	480	80	7077	37.8125	20.5625	23.5625	2016	X		B	21	SB6320
	48	24-P95-13	26.54	570	95	7077	37.8125	20.5625	23.5625	2121	X		B	21	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Note A - Models ending with "EE" accept standard with cover style batteries.

THREE WHEEL SIT-DOWN RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
OT 25S, OT 30S	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	D	18	SB6320
38.875 x 13.75 x 31	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	D	18	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	D	18	SB6320
OT 30, OT 35, OT 40	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	D	18	SB6320
OT 45, OT 50	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	D	18	SB6320
38.875 x 20.5 x 31	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	D	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

THREE WHEEL SIT-DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
TN 30, TN 35, TNX30	36	18-D100-17	27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	B	14	SB6320
TNX35, TX 30, TX 35	36	18-D85-17	23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	B	14	SB6320
39.125 x 20.875 x 25.75	36	18-H80-17	22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	B	14	SB6320
	36	18-P95-17	26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	B	14	SB6320
N 30, N 35, TX 30, TX 35 39.125 x 20.875 x 25.75	48	24-D100-13	27.94	600	100	7106	37.875	20.5625	25.6875	2342		X	B	14	SB6320
	48	24-D85-13	23.75	510	85	7017	37.8125	20.5625	22.6875	2030		X	B	14	SB6320
	48	24-H80-13	22.35	480	80	7017	37.8125	20.5625	22.6875	1949		X	B	14	SB6320
	48	24-P95-13	26.54	570	95	7017	37.8125	20.5625	22.6875	2050		X	B	14	SB6320
TX 40 39.1875 x 25.25 x 25.8125	36	18-D100-21	34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	B	14	SB6320
TX 40 39.1875 x 25.25 x 25.8125	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	B	14	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

TOW TRACTOR

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
WTTN 32 x 8.25 x 31.125	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	20	SB6325
	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	20	SB6325
	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	20	SB6325
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	20	SB6325
SGN200 32 x 13.5 x 31.125	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6329
	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6329
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6329
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6329

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.