

CARBON LOADED ACTIVE MATERIAL ADDITIVE

Increases charge acceptance which decreases the risk of a battery that's not properly charged.

SPECIAL GLASS FIBER COATED SEPARATORS

> Provides greater durability in frequent cycling applications to extend service life.

EFB is ideal for low- to mid-level vehicles. AGM is a confident replacement for all types. When in doubt, install AGM. If EFB is specified, EFB or AGM will satisfy.

GROUP NO.	PART NO.	PERFORMANCE LEVEL				MAXIMUM OVERALL DIMENSIONS						
		CCA	REF. CA	20 HR CAP.	(lb.)	LENGTH		WIDTH		HEIGHT		FOOT- NOTES
						in	mm	in	mm	in	mm	
12 - VOLT ULTIMATE® ENHANCED FLOODED (EFB)												
47 (H5/L2)	47EFB	600	740	60	36.5	9-9/16	242	6-7/8	175	7-1/2	190	8,17
48 (H6/L3)	48EFB	700	860	70	42	11	278	6-7/8	175	7-1/2	190	8,17

Phone: 610-682-6361

Batteries are Maintenance-Free Weights are Approximates

Footnotes

- 8 Black cover / White case
- 17 Includes handle

PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**



